
I N D E X

A

ABS resin, 393
blends, 305, 362
crazing, 394
as graft copolymer, 10
impact strength, 199
preparation, 361
properties, 359, 390
rubber phase, 304
toughening, 200
accelerator, 370, 371
acetal (*see* polyoxymethylene)
acetaldehyde, 64, 363
acetate, 341
acetylene polymerization, 50
Achras sapota, 339
acrylamide
 polymerization, 69
 Q-e values, 43
acrylate
 copolymerization, 355
 polymer, 527
acrylic acid copolymer, 364
acrylic fiber, 3, 340, 346, 347, 349
acrylics, 526

acrylonitrile
 copolymer, 347, 364
 copolymerization, 360, 369
 polymerization, 69
 Q-e values, 43
 rate constants, 35
acrylonitrile-butadiene rubber, 361
ACS nomenclature, 14
activation energy
 of initiator dissociation, 30
 of secondary relaxation, 200
activator, 370
activity, 94
addition polymers, 4
additives, 283, 284
adenine, 331
adhesive, 308
adriamycin, 521
aerobic degradation, 277
affine deformation, 255
AflasTM, 373
AIBN, 31, 60
alanine, 327
Alcaligenes eutrophus, 277
Alfin catalyst, 368
Alfrey, 42
aliphatic diesters, 288

alkenyl sodium compounds, 368
alkyd, 430
alkyltin, 291
N-allylacrylamide graft, 518
 α -helix, 329
 α -keratin, 329
alumina trihydrate, 292
aluminosilicate layers, 316
aluminum, 522
aluminum chloride, 61
aluminum foil, 524
aluminum oxide, 356
aluminum trialkyls, 356
aluric acid, 345
amidation, 24
amino acid, 326, 327, 328
2,2-bis[(4-aminophenoxy)phenyl]hexa-fluoropropane, 408
aminoplast, 382, 384
ammonium persulfate, 347
amorphous state, 19
amorphous Teflon, 403
amphoteric, 363
amylase, 337
amylopectin, 280, 335
amylose, 280, 335, 336
anaerobic degradation, 277
angular frequency, 208
anhydroglucose, 62
annular die, 428
annular flow, 459
annulus, 472
anticancer drug, 521
antimony mercaptide, 291
antimony oxide, 292
antioxidant, 270, 370
antiplasticization, 289
antistatic agent, 294
apparent shear rate, 463
apparent viscosity, 231, 440, 441
aramid, 345, 392, 421
arginine, 327
Arrhenius relationship, 443
arsenic pentafluoride, 522
artificial hip replacement, 358
aspargine, 327

aspartic acid, 327
ASTM nomenclature, 14
atactic, 10
ATR spectroscopy, 72
autoacceleration, 53
Avogadro's number, 134
Avrami equation, 165
axial annular Couette flow, 460
axial annular drag flow, 475
azeotrope, 44
azobenzene dendrimer, 423
2,2'-azobisisobutyronitrile (*see* AIBN)
azo compound, 293, 363, 364

B

Baekeland, 2, 429
Bagley, 464
Bagley correction, 466
Bagley plot, 465
Bakelite, 2, 383
balata, 338, 338, 339
band gap, 523
barrier properties, 392, 486
Barus effect, 452
batteries, 524
Bayer, 373
benzoic acid, 175
benzophenone, 270, 292
benzothiazoles, 370
benzothiazolyl group, 370
benzotriazoles, 292
benzoyl peroxide, 30
Bingham behavior, 448
Bingham fluid, 449
binodal, 110, 296, 300, 301
biocide, 292
biocompatibility, 61, 518
biodegradation, 264, 277, 280
biomass, 277, 280
biomedical applications, 404
biomedical engineering, 517
2,2'-bipyridine, 70
birefringence, 172
bischloroformates, 373, 374
bismaleimide, 409
bisphenol-A, 379

blade coating, 438
blend
 heterogeneous, 305
 phase behavior, 304
 properties, 303
 volume change of mixing, 304
blowing agent, 294, 360
blow molding, 435, 436
body force, 455
Boltzmann constant, 96
Boltzmann relation, 96, 252
Boltzmann superposition principle, 245
Bombyx mori, 340
boron fiber, 289, 290, 319
boron trifluoride, 47
Boyer, 173
Boyer crankshaft motion, 157
Bragg peak, 167
Brownian motion, 154, 155
buckminsterfullerene, 289
bulk-molding compound, 317
butadiene
 block copolymerization, 49
 copolymerization, 369
 graft, 304
 $Q\text{-}e$ values, 43
butene-1
 copolymerization, 358
 polymerization, 50
n-butyllithium, 368
t-butyl peroxide, 60
butyl rubber, 48, 371, 372, 494
butyraldehyde, 64

C

calcium carbonate, 290, 291, 447
calcium stearate, 290, 291
calendering, 428, 437, 449
calorimetry, 174
capacitance, 233
capillary
 die, 428, 457, 472
 flow, 456, 457, 458, 459, 464
 pressure profile, 464
capillary rheometry, 457, 462
 ε -caprolactam polymerization, 346

carbamate group, 374
carbamic acid, 374
carbanion, 45
carbon black, 270, 397, 447
carbon disulfide, 342
carbon fiber, 522
carbonium, 45, 47
carbon nanotubes, 289
carboxylic acid anhydrides, 379
carboxymethylcellulose, 337, 337
Carothers, 4, 27, 325
Carreau model, 449
cast polymerization, 53, 54
cation-exchange resin, 62
ceiling temperature, 39, 40, 265, 266
Celgard™, 507, 510
cellophane, 63, 342, 519
celluloid, 432
cellulose, 335
 acetylation, 343
 chemical structure, 334
 dissolution, 337
 fiber, 63, 340, 343
 membrane, 130
 properties, 62
 regenerated, 130, 342, 350, 519
 structure, 336
 triacetate, 63
 xanthate, 63
cellulose acetate
 from cellulose, 337, 343
 critical concentration, 445
 dual-mode parameters, 504
 fiber, 339, 340, 341, 349
 Mark-Houwink constants, 140
 membrane, 490, 492, 511
 as modified polymer, 61
 for packaging, 435
 permeability, 494
 reduced viscosity plot, 141
 solubility parameter, 115
 solution properties, 138
 specific viscosity, 446
cellulose diacetate, 343
cellulose ethers, 337
cellulose gum, 337

- cellulose nitrate, 61, 337, 383, 432
cellulose triacetate, 343, 490
cellulose xanthate, 342, 343
ceric ion, 280
chain expansion factor, 92
chain growth, 8
chain scission, 265
chain transfer, 34
chain-transfer coefficient, 38
characteristic pressure, 107
characteristic ratio, 92, 94, 94
characteristic temperature, 124
charge density, 233
Charpy impact test, 186, 199
chelating agent, 336
chemical potential, 100, 108, 110, 129
chemical shifts, 76
chemical vapor deposition, 525
chewing gum, 339, 369
chicle, 339
chitin, 326, 334, 336, 336
chitosan, 336, 336, 337
chlor-alkali process, 498, 508, 509
chloroacetic acid, 337
chlorofluorocarbons, 60
chloromethylation, 61
4-chlorostyrene copolymerization, 41
cholesteric, 417
cholesteryl esters, 416
chrome yellow, 294
chromium oxide, 356
clay, 317
cloud-point temperature, 297
coating, 437, 438
cocatalyst, 47
codon assignments, 298
cohesive energy density, 113
cold drawing, 193
cold sterilized, 489
collagen, 71, 329
colorants, 284, 293
combination, 33
compatibilizer, 69, 295, 305, 397
complex compliance, 224, 245
complex dielectric constant, 236
complex heat capacity, 240
complex modulus, 210, 245
complex stress, 210
compliance, 189, 195
composites, 308
 applications, 308
 continuous reinforced, 309
 dynamic mechanical properties, 313
 fabrication, 317
 heat-distortion temperature, 310
 interface, 309, 312, 313
 linear expansion coefficient, 311
 market, 308
 maximum strength, 311
 mechanical properties, 309
 metal-filled, 525
 modulus, 310
 packing fraction, 310
 particulate, 289, 310, 311
 processing, 309
 spray-up, 317
 strength, 311
 uniaxially oriented, 310
compressibility coefficient, 105, 117, 170
compression molding, 429, 430, 449
compression section, 428
condensation polymers, 4
conduction band, 523
conductive polymer, 419, 522
cone-and-plate rheometer, 231, 452, 467
configuration, 10, 88
conformation, 10
conformational entropy, 244
conservation of energy, 455
conservation of momentum, 455
consistency, 448
constitutive equation, 441, 448, 449, 454, 456
constrained-chain models, 255
contact lens, 364
contact sites, 106
continuity equation, 456, 479
continuum mechanics, 255
controlled release, 277, 308, 364, 519, 521
converging flow, 440
copolyester, 378, 402, 417
copolymer nomenclature, 15

copolymerization
 alternating, 41, 44
 free-radical, 40
 ideal, 44
 random, 41
copolymerization equation, 41, 42
copper, 522
core volumes, 106
cornstarch, 280
Cossee mechanism, 50
cotton, 339, 340, 342
Couchman–Karasz equation, 182
Couette flow, 439, 466, 469
Couette rheometry, 231, 461, 465
counterion, 46
coupled transport, 500, 507, 508
coupling agent, 309, 312
Cox-Merz rule, 231
craze, 184, 306
crazing, 183
creep, 186, 195, 222
creep compliance, 196, 197, 228
Crick, 331
crimp, 346, 348
critical micelle concentration, 55
critical molecular weight, 155
critical point, 111
critical strain, 271
crosslink density, 183, 253
crystalline-melting temperature, 20, 160,
 180, 302
crystallization
 shear-induced, 442
 strain-induced, 193, 253
cull, 431
cuprammonium process, 337, 342
curing agents, 293
curtain coating, 438
Cyamopsis tetragonolobus, 453
cyclooctadiene, 376
cyclopentadienyl ligands, 52
bis(cyclopentadienyl)zirconium dichloride,
 357
cysteine, 327
cytosine, 331, 332

D

Dacron, 344
dashpot, 221
deacetylation, 337
Debye, 237
Debye equation, 138
de Gennes, 155
degree of polymerization, 27, 37
dehydrofluorination, 404
dehydrohalogenation, 267
dendrimer, 404, 422, 529
dendrons, 422
denier, 340
density measurements, 165
depolarization, 265
depolymerization, 39
desalination, 516
desmosine, 338
devolatilization, 429
dextrose, 278
4,4'-di(5-nonyl)-2,2'-bipyridine, 70
dialkyl phthalate, 288
dialysis, 488, 497
4,4-diamino diphenyl ether, 406
dichlorosilane, 415
dicyclopentadiene, 376
die characteristic, 458, 459, 469, 471
dielectric analysis, 232
dielectric constant, 233
dielectric relaxational strength, 235
dielectrics, 525
dielectric spectroscopy, 218
diene elastomers, 366
die swell, 427, 450, 452
diethylaluminum chloride, 358
differential scanning calorimetry, 174
dihydric alcohol, 344
diisocyanates, 373, 434
diisooctyl phthalate, 287
dilatant, 442
dilatometry, 168, 172, 478
dimethyl distearyl ammonium chloride, 316
dimethyl ditallow ammonium bromide, 316
dimethylol, 385, 386
dimethyl stearyl benzyl ammonium
 chloride, 316

- dimethyl sulfoxide, 445
dimethyl terephthalate, 276
dimethyl terephthalate acid, 365
dioctyl adipate, 288
dioctyl phthalate, 287
diols, 373, 374
dipole moment, 232
disproportionation, 33
dissymmetry method, 137
dissymmetry ratio, 137
disulfide, 30, 329, 339
divinylbenzene
 copolymer, 62, 361
 copolymerization, 142, 307
DNA, 71, 329, 331, 332, 332, 333
Doolittle equation, 477
double helix, 332
drag flow, 459, 469, 473
drag reducers, 453
drag reduction, 440, 453, 453
draw stress, 192
drug delivery, 518, 519, 521
dry spinning, 349
dual-mode model, 502, 505
dual-mode parameters, 503, 504, 507
duct flow, 459
ductile failure, 193
Durham process, 419
dyeability, 364
dynamic compliance, 211
dynamic equations, 455, 479
dynamic mechanical analysis, 208
dynamic moduli, 225
dynamic viscosity, 230
- E**
- ebonite, 370
efflux times, 140
E-glass, 289, 290, 318, 319
Ehrenfest transition, 168
Einstein coefficient, 447
elastic properties, 450
elastin, 71, 338
electrical insulators, 521
electrically-conductive, 521
electrochromic displays, 525
- electrocoating, 490
electrodialysis, 497, 497, 516
electromagnetic shielding, 289, 524, 525
electron donor, 522
electronic shielding, 525
electron-withdrawing, 45
electroosmosis, 497
electrophilic substitution, 399
electropolymerization, 421
elution volume, 144
emeraldine salt, 523
encapsulation, 65, 415, 525
encapsulated, 519
end-to-end distance, 89, 135
endurance limit, 200
energy equations, 455
energy of vaporization, 113
energy storage, 335
engineering plastics, 389, 391
engineering strain, 186
engineering stress, 186
enrichment factor, 496
entanglements, 154, 190, 441, 442, 445
entropy of mixing, 98
environmental agents, 263, 264
environmental stress cracking, 271
EPDM, 306, 371, 376, 378
epichlorohydrin, 379
epoxide, 288, 379
epoxidized soybean oil, 288
epoxy
 amine cure, 380
 anhydride cure, 380
 encapsulants, 526
 formation, 379
 functionality, 312
 market data, 3
 production, 379
 properties, 309, 379
 RIM, 435
 as thermoset, 378
epoxy-silane coupling agent, 312
equation-of-state theories, 103
equilibrium melting temperature, 162
ESCA, 59
Escherichia coli, 71, 278

ester groups, 379
esterification, 24, 333, 365
ester interchange, 24, 25, 365
ethylcellulose, 492
ethylene
 ceiling temperature, 40
 copolymer, 54, 403
 heat of polymerization, 40
 metallocene polymerization, 357
 polymerization, 356, 358
 Q-e values, 43
 rate constants, 35
 reactivity ratios, 43
ethylene-cycloalkene copolymer, 52
ethylene diamine, 375
ethylene-ethyl acrylate copolymer, 356
ethylene-methacrylic acid copolymer, 356
ethylene-propylene rubber, 3, 367, 371, 376
ethylene-propylene-diene rubber (*see* EPDM)
ethylene-vinyl acetate copolymer, 294, 305, 356
ethylene-vinyl alcohol copolymer, 356
di-2-ethylhexyl phthalate, 287
tris(2-ethylhexyl trimellitate), 288
ethylidene norbornene, 376
Euler's identity, 210, 248
evapomeation, 496
Ewart, 57
exchange interaction parameter, 107, 112
excluded volume, 91
exfoliated, 316
exfoliation, 317
exit pressure, 427, 452, 461, 464
exit region, 452
extensional flow, 453
extensional viscosity, 440, 453
extension ratio, 253
external degrees of freedom, 107
external lubricants, 293
external plasticization, 286
extruder, 470
extrusion, 428, 449, 468

F

facilitated transport, 500, 507
failure envelope, 194
fatigue life, 200
fatigue test, 186, 200
fatty acid, 371
6FDA, 408
feed section, 428
fibers, 339
 asymmetric, 350
 high-performance, 421
 naturally occurring, 339
 surface modification, 313
 suspension, 453
 U.S. production figures, 341
Fiberglas®, 308
fibroin, 340
Fick's first law, 505, 506
filament winding, 309, 318, 409
filler, 284, 289
filtration, 488, 495
first law of thermodynamics, 249
first normal stress difference, 451
first-order transition, 168
flame retardant, 284, 292
flash, 430
Flory, 16, 96, 99, 100, 102, 103, 104, 416
Flory constant, 142
Flory distribution, 18
Flory equation of state, 103, 106, 112, 118, 123, 299, 300, 301
Flory-Huggins equation, 101, 103, 111, 118, 502
Flory-Huggins theory, 96, 102, 163, 298, 299, 502
Flory interaction parameter, 302
Flory-Krigbaum theory, 102
Flory partition function, 104
flue gas, 489
Fluorel, 373
fluorinated ethylene-propylene copolymer, 404
fluorinated polyolefins, 372
fluoroelastomers, 366, 371, 372, 373
fluoropolymers, 60, 75, 402, 526
foam, 435

forced oscillation techniques, 214
 forced-vibration methods, 218
 force field, 455
 formaldehyde-based resins, 378
 Fox equation, 182
 Fox–Flory equation, 180
 Fox–Flory parameters, 180
 Fox–Loshaek equation, 183
 free energy of fusion, 162
 freely jointed chain, 88
 free-radical scavenger, 291
 free volume, 118, 123, 124, 156, 180, 181,
 244, 304, 444, 477, 477, 478,
 493, 500, 505
 Friedel-Crafts, 61, 399, 420
 Friend, 528
 FTIR, 72
 fuel cell, 412, 498, 508
 fugacity, 94
 fumaric acid, 381

G

gage length, 186
 gamma function, 139
 γ -irradiation, 30, 273, 364
 gas
 diffusivity, 501
 kinetic diameter, 500
 mean free path, 500
 permeation, 516
 separation, 491
 solubility, 492, 501
 Gauss's flux theorem, 233
 Gaussian distribution, 88, 253, 255
 Gaussian radial distribution function, 252
 Gee, 94
 gegen ion, 47
 gel effect, 53
 gel-permeation chromatography, 128, 142,
 143
 generalized Newtonian fluid, 441, 463
 genetic engineering, 71
 geometric isomers, 178
 geotextiles, 347
 Gibbs–Dimarzio theory, 156

Gibbs free energy of mixing, 100, 101,
 295, 298
 glass fiber, 308
 glass transition, 156, 443
 glass transition temperature
 blends, 287
 copolymers, 286
 definition, 154
 effect of crosslinks, 183
 heating rate effect, 183
 ionomers, 411
 mixtures, 180
 molecular weight dependence, 180
 plasticized PVC, 287
 pressure dependence, 182
 glassy plateau, 285
 D-glucosamine polysaccharide, 518
 glucose, 335
 glutamic acid, 327
 glutamine, 327
 glycine, 326, 327
 glycogen, 334, 335
 glycolide, 279
 glycolysis, 276
 glyptal, 2, 381
 godet, 347
 Goodyear, 2, 339
 Gordon–Taylor equation, 286
 Gore-Tex®, 510
 Gossamer Albatross, 393
 Gough, 249
 Gough–Joule effect, 249
 Graham, 491
 graphite fiber, 289, 290, 308, 319
 graphite filaments, 347
 Grignard reagent, 46
 group-contribution methods, 113
 group interaction parameter, 122
 guanine, 331, 332
 guar, 453
 Guth–Smallwood equation, 253
 gutta percha, 338, 339, 411, 428, 428
 gyromagnetic ratio, 75

H

Hagen–Poiseuille equation, 458

hair, 340
Halley's comet, 397
Halpin-Tsai equation, 310
Hansen, 118
Hansen solubility parameter, 271
head-to-tail polymerization, 32
heat-distortion temperature, 176, 294, 305
heat of fusion, 175
heat of mixing, 118
heat of polymerization, 38, 40
Heeger, 522
Helmholtz free energy, 252
heme, 329
hemicellulose, 335
hemoglobin, 329
Henis, 514
Henry's law, 501, 502, 503, 505
heparin, 58, 518
Hevea brasiliensis, 338, 339
Hevea rubber, 2, 339, 369
hexabromocyclododecane, 360
hexachlorocyclotriphosphazene
 polymerization, 66
hexadecyltrimethylammonium bromide,
 316
1,4-hexadiene, 376
hexafluoroethylene copolymer, 404
hexafluoroisobutylene copolymer, 403
hexafluoropropane, 407
hexafluoropropylene, 403
hexamethylene diammonium adipate salt,
 345
hexamethylenediisocyanate, 375
hexamethylenetetramine, 384
hexene-1 copolymerization, 358
tris(2-hexyl)trimellitate, 286
hindered amine, 291, 397
hindered phenols, 291
histidine, 327
homolytic cleavage, 265
Hookean material, 195, 210
Hooke's law, 188, 191, 195, 208
hopper, 428
Hoy, 113
Huggins, 96, 99, 100
Huggins coefficient, 139

Huggins equations, 139
Human Genome Project, 329
Hyatt, 432, 435
hydrazine derivatives, 294
hydrodynamic volume, 144
hydrogel, 520
hydrogen as chain-transfer agent, 358
hydrogen bond, 329, 331, 332, 364
hydrogen bonding, 376, 391
hydrolysis, 264, 271, 276, 415
hydrolytic stability, 271
hydroxyapatite, 279
p-hydroxybenzoic acid, 418
o-hydroxybenzophenone, 292
hydroxycaproic acid, 24
hydroxyethyl methacrylate, 364
hydroxyl-containing polymers, 364
2-(*o*-hydroxyphenol)benzotriazole, 292
hyperbranched, 69, 422, 423
hyperpolarizability, 526

I

ideal mixture, 95, 97
iminodiacetic acid, 70
impact modifier, 284, 291, 294
impact testing, 199
incineration, 276
incompressibility, 192
incompressible fluid, 455
inertial terms, 456
initial modulus, 189
initiator
 association, 30
 dissociation, 30, 35
 efficiency, 36
injection blow molding, 436
injection molding, 430, 432, 432, 449
inorganic polymers, 415
insulin, 329
interaction energy, 300, 301
interaction parameter, 100, 101, 102, 103,
 112, 112, 163, 298
interfacial adhesion, 304
interfacial slip, 452
intermolecular energy, 106
internal lubricants, 293

internal plasticization, 286
interpenetrating network, 306, 307, 307,
307
intrinsic viscosity, 128, 139
inverse emulsion, 57
inverse gas chromatography, 112
inverse rule of mixtures, 182
ion-exchange resin, 55, 62, 308
ionic copolymerization, 48
ionic polymers, 411
ionizing agents, 264
ionizing radiation, 370
ionomer, 356, 404
iron oxides, 294
iron porphyrins, 329
isobutylene
 polymerization, 47
 Q-e values, 43
isocyanates, 374
isocyanate-terminated prepolymer, 375
isocyanic acid, 374
isoentropic state, 156
isofree volume, 156, 181
isoleucine, 327
isopentylpyrophosphate polymerization,
 339
isoprene
 copolymer, 372
 copolymerization, 48
isotactic, 10
isothermal flow, 456, 458, 473
isoviscous state, 156, 444
IUPAC nomenclature, 14, 140
ivory, 432
Izod impact test, 186, 199

J

jute, 339

K

Kalrez, 373
Kaminsky, 51, 357
Kapton, 405, 409, 525
Kel-F, 373, 403
Kelley–Bueche equation, 181, 285

Kendrew, 329
keratin, 340
Kerimid, 409
Kevlar, 289, 290, 308, 345, 391, 392, 393,
421
kidney dialysis, 519
Kinel, 409
kinetic chain length, 37
Knudsen flow, 500, 501
Knudsen number, 500
Koningsveld, 103
Krigbaum, 102
Kronecker delta, 456
Kynar, 403

L

lactam polymerization, 346
lactide, 278
ladder polymer, 347, 410
lamellae, 158
landfill, 280, 280
Langmuir capacity, 503, 505, 506
Langmuir mode, 502
Langmuir sites, 505, 506
Langmuir-type microvoids, 500
latent solvent, 512
latex, 57, 339, 447
lattice model, 99
Lee, 511
Legendre transformation, 170
Lennard-Jones collision parameters, 499
Lennard-Jones potential, 500, 504
leucine, 327
Lewis, 42
Lewis acid, 47, 358, 372
Lewis–Randall law, 97
light-emitting diode, 525, 528
light scattering, 133
light-scattering instrumentation, 135
lignin, 490
liquid-crystal polymer, 416, 417
liquid–liquid equilibria, 118
liquid separation, 494
lithium hexafluoroarsenate, 524
lithium perchlorate, 524
lithium tetrafluoroborate, 524

lithium triflate, 524
logarithmic rule of mixtures, 182
log decrement, 214
loss compliance, 211
loss modulus, 211, 248
low-angle laser light scattering, 138, 145
lower critical solution temperature, 111, 296, 297
lubrication approximation, 469, 473
lysine, 327
lysozyme, 329

M

MacDiarmid, 522
macromer, 69
maleic anhydride
 copolymer, 364
 copolymerization, 360, 381
 $Q\text{-}e$ values, 43
Maltese cross, 159
market data, 3
Mark–Houwink parameters, 139, 144
Mark–Houwink–Sakurada equation, 139
mass flow rate, 475
master curve, 197, 242
mastication, 274
material functions, 452
maturation agent, 317
Matyjaszewski, 69
Maxwell element, 221
Maxwell equation, 223
Maxwell model, 237
Maxwell–Wiechert model, 226, 227, 228
Mayo, 42
McMaster, 299
mean-field expression, 100
mechanodegradation, 264, 274, 441
medical applications, 518
medical packaging, 519
melamine–formaldehyde resin, 385
melamine resin, 3
melt fracture, 427, 452
melt index, 356
melting-point depression, 112, 163, 163, 175
melt instabilities, 452

melt spinning, 346, 347
membrane
 asymmetric, 511, 514
 capillary modules, 517
 composite, 514
 concentration polarization, 494, 519
 fouling, 490
 hollow-fiber, 350, 511, 516, 516, 517
 ion-exchange, 497
 macroporous, 508
 microporous, 510
 module fabrication, 516
 plate and frame, 516
 preparation, 510
 resistance model, 514
 spiral-wound, 516, 517
 track etching, 510
 tubular, 516, 517
membrane osmometry, 129, 131
mercury, 522
Merrifield, 329
Merrifield synthesis, 61
metallocene catalyst, 51, 357, 358, 361
metallocene-polymerized, 519
metastable region, 110
metathesis, 60, 66, 66, 369, 420
metering section, 428, 469
methacrylate coupling agent, 312
methacrylic acid, 43, 411
methanolysis, 276
methionine, 327
4-methoxy-4'-nitrostilbene moiety, 527
methylaluminoxane, 52
2-methyl-1,3-butadiene polymerization, 369
4-methyl-2,6-di-*tert*-butylphenol, 291
methylcellulose, 337
4,4'methylene-bis(cyclohexylisocyanate), 375
methylene bridges, 386
methylene-4,4'-diphenyldiisocyanate, 374, 375
methyl methacrylate
 copolymer, 364
 copolymerization, 44
 heat of polymerization, 40

- polymerization, 67, 68
 $Q\text{-}e$ values, 43
 rate constants, 35
 reactivity ratio, 43
 methyl methacrylate-acrylonitrile-butadiene-styrene copolymer, 294, 305
 methyl methacrylate-butadiene-styrene copolymer, 294, 305, 362
 methylol, 383, 384
 p -methylphenylsulfonate, 523
 α -methyl styrene polymerization, 40
 mica, 289
 micelle, 55, 56
 Michael addition, 409
 microcomposite, 316
 microfiber, 289
 microfilter, 489
 microfiltration, 489, 490, 491, 516
 microporous, 492
 microsphere, 308
 microvoids, 505
Mimusops globosa, 338
 mineralization, 277
 mineral oil, 293, 466
 miscibility, 109
 modacrylic fiber, 347
 molar attraction constant, 113, 114
 molar permachor, 488
 mold-release agents, 293
 molecular sieving, 501
 molecular weight
 averages, 15
 critical, 155, 442
 determination, 128
 between entanglements, 155, 190, 446
 number-average, 16
 viscosity-average, 128, 139
 weight-average, 16
 z-average, 16
 monoethylophenol, 383
 monomethylol, 386
 montmorillonite, 316
 Mooney, 448
 Mooney–Rivlin equation, 254, 255
 multiplet, 411
 myoglobin, 329
N
 Nafion, 412, 497, 498, 509
 nanocomposite, 315
 nanofilter, 490
 nanofiltration, 490, 491
 naphthalene, 49
 naphthalene dicarboxylate, 402
 naphthalene-1,5-diisocyanate, 375
 Natta, 2, 50, 358, 360
 natural rubber, 521
 biosynthesis, 339
 doped, 521
 Flory EOS parameters, 106
 membrane, 491
 permeability, 494
 Poisson's ratio, 188
 stress-strain data, 254
 thermal oxidation, 291
 WLF parameters, 244
 Navier-Stokes equations, 456
 nematic, 417
 neoprene, 377
 Newtonian fluid, 196, 221, 439, 440, 447, 448, 458, 460, 466, 473, 475, 477
 Newtonian plateau, 441
 Newtonian viscosity, 471, 474
 Newton's law of viscosity, 196, 209, 230, 231, 439, 440, 448
 nitrile rubber, 366
 blend, 302, 303
 production figures, 3, 367
 properties, 369
 nitro-displacement reaction, 408
 3-nitrophthalic anhydride, 408
 NMR, 75, 77, 77
 nomenclature, 13
 Nomex, 20, 345, 391, 392, 421
 nondiene elastomers, 366, 371
 nonlinear optical effects, 527
 nonlinear optical material, 419, 525
 nonlinear optical polymers, 526
 nonlinear optics, 526
 non-Newtonian behavior, 446

non-Newtonian flow, 440, 455, 469
non-Newtonian fluid, 449, 454, 462
non-zero pressure drop, 452
norbornene
 end-functionality, 407
 polymerization, 66, 67
normal stress, 450, 451, 452
normal-stress coefficient, 452
normal-stress difference, 451
Norrish-Smith effect, 53
Noryl, 283, 396
no-slip assumption, 439, 456, 459, 468
novolac, 383, 384
nucleation index, 165
nucleation track etching, 510
nucleic acids, 329
nucleophilic displacement, 413
nucleophilic substitution, 399
nucleotides, 331
nylon
 fiber, 3, 3, 340, 344, 453
 hydrogen bonding, 161
 nomenclature, 14
 production figures, 354
nylon-6
 density, 166
 nanocomposite, 315
 properties, 390
 structure, 391
nylon-11, 391
nylon-12, 392
nylon-4,6, 392
nylon-6,10, 7, 14, 391
nylon-6,6
 density, 166
 heat-distortion temperature, 177
 hydrogen bonding, 162
 nomenclature, 14
 properties, 390
 structure, 391
 synthesis, 5, 7, 24, 25, 28, 345, 345
 T_g , 161
 T_m , 161
water sorption, 391

O

octene-1 copolymerization, 358
Ohm's law, 514
Oishi, 123
olefin fiber, 3, 340, 347
oligomer, 2
oligo(oxyethylene), 524
oligosaccharides, 337
open discharge, 469
operating parameters, 471
optical band gap, 526
optical signal processing, 526
optical storage, 526
organometallic compounds, 46
organo-tin compounds, 362
orientation hardening, 192
osmium tetroxide, 304
osmometry, 129
osmotic pressure, 129
osmotic pump, 520
Ostwald-de Waele-Nutting behavior, 448
Ostwald-Fenske viscometer, 141
oxidative stability, 269
10,10'-oxybisphenoxyarsine, 293
ozone, 264
ozonide structure, 270
ozonolysis, 270

P

P. aeruginosa, 280
packing fraction, 448
paint, 445, 524
Palagium oblongifolium, 338
paper maché, 429
paraffin, 290
paraformaldehyde, 384
parallel plate flow, 459
parallel-plate rheometer, 452
parison, 435
partial-immobilization theory, 505, 507
particle scattering function, 134
PBI, 20, 409, 410, 421
pectin, 335
PEEK, 166, 309, 311, 312, 312, 312, 312, 412, 413, 413

- Pelouze, 432
pentaerythrityl tetrastearate, 133
pentose sugar, 330
perfluorinated vinyl ether, 412, 508
perfluoro-(2,2-dimethyl-1,3-dioxole), 403
perfluoroalkoxy, 403
perfluoromethyl vinyl ether, 404
perfluorosulfonate ionomer, 412, 497, 498, 500, 508
period of oscillation, 214
Permachor, 486
permeability, 486, 487, 501
permselectivity, 493
peroxides, 30, 363, 364, 376, 381
persulfate-ferrous initiator, 55
pertraction, 496
pervaporation, 494, 495, 507, 516
phantom chain approximation, 255
phase angle, 208
phase equilibria, 108
phase inversion, 512
PHEMA, 520
1,10-phenanthroline, 70
phenol-formaldehyde resin, 378, 383, 429
phenolic resin, 3, 378, 379, 383, 429, 430
phenoplast, 382, 383
phenylalanine, 328
1-phenylethyl chloride, 70
Philips catalyst, 356
phosgene, 395
phosphinic ligands, 61
phosphoric acid, 329
photoconductive polymers, 421
photoconductivity, 421
photolysis, 292
photonic polymer, 526
phononics, 525
photooxidation, 264, 270
photoresist, 58, 415
phthalic anhydride, 381
pigments, 291
pitch, 289
plane Couette flow, 440, 459, 470
plasma polymerization, 514
plasmid, 71
plasticizer permanence, 286
plasticizers, 284, 285, 286
plastisol, 447
plateau modulus, 190
platinum, 522
Plunket, 403
PMP, 414, 494
PMR-15, 407
Poiseuille flow, 457
Poisson's ratio, 188, 192, 310
polarization, 232, 234
polyacetylene, 404, 419, 521, 522, 523, 524, 526
polyacrylamide, 54, 453
poly(acrylic acid), 54
polyacrylonitrile
as carbon fiber precursor, 289
cyclization, 268, 346
fiber, 347, 350
membrane, 517
permeability, 486, 487
solubility parameter, 115
structure, 6
 T_g , 179
polyalkenamers, 66
polyalkenlenes, 8
polyalkylenes, 8
poly(alkyl sulfide), 524
poly(3-alkyl-thiophene), 523
polyalkynlenes, 8
polyallomers, 378
poly(amic acid), 405, 406
polyamidation, 25
polyamide, 391
aromatic, 24, 391, 392
blend, 396
classification, 24
fiber, 347
FTIR, 75
membrane, 490, 490
RIM, 435
poly(amide-imide), 406, 408
poly(amino acid), 521
polyanhydrides, 9
polyaniline, 420, 492, 522, 523, 524, 524, 526
polyarylate, 401

- poly(aryl ether ether ketone) (*see* PEEK)
poly(aryl ether ketone), 404, 412
polybenzamide, 269
polybenzimidazole, 269 (*see also* PBI)
polybenzobisoxazole, 421, 422
polybenzobisthiazole, 421, 422
poly(γ -benzyl-L-glutamate), 71, 416
polybismaleimide, 409
cis-1,4-poly(1,3-butadiene), 161
trans-1,4-poly(1,3-butadiene), 161
polybutadiene
 in ABS resin, 393
 as elastomer, 366
 geometric isomers, 12, 178
 in HIPS, 360
 market data, 2
 production figures, 367
 rubber properties, 369
 structure, 368
 synthesis, 13, 54
 T_g , 178
poly(butylene terephthalate), 166, 360, 364, 401
polycaprolactone, 20, 24, 25, 161, 161, 280, 288, 303
polycarbamate, 374
polycarbonate
 blend, 395
 classification, 24
 crazing, 183
 critical molecular weight, 155
 critical strain, 184
 from cyclohexanonebisphenol, 395
 degradation, 292
 density, 166
 dielectric spectroscopy, 239
 dual-mode parameters, 504
 enthalpy of fusion, 163
 entropy of fusion, 163
 FTIR spectrum, 72, 73
 heat-distortion temperature, 177
 impact-modified, 305
 impact strength, 199
 M_e , 155
 Mark-Houwink parameters, 140
 mechanical properties, 194
 membrane, 510
 nomenclature, 14
 permeability, 494
 Poisson's ratio, 188
 power-law parameters, 449
 properties, 390, 394
 secondary relaxations, 158
 stress-relaxation data, 243
 synthesis, 5, 7, 394
 T_g , 157
 T_m , 163
 from tetramethylbisphenol-A, 297, 299, 302, 303, 395
 torsional creep data, 243
 WLF shift factor, 444
polychloroprene, 3, 366, 367, 368, 369
polychlorotrifluoroethylene, 403, 404
poly(dichlorophosphazene), 65, 66, 415
poly(diethyleneglycol adipate), 375
poly(dimethylene cyclohexane terephthalate), 401
poly(2,6-dimethyl-1,4-phenylene oxide), 396
 blend, 302, 303, 305, 396
 classification, 24
 craze, 185
 critical strain, 184, 271
 density, 166
 dual-mode parameters, 504
 Mark-Houwink parameters, 140
 membrane, 513
 permeability, 494
 properties, 283, 390
 solubility parameter, 271
 T_g , 157
polydimethylsiloxane
 in controlled release, 520
 critical molecular weight, 155
 Flory EOS parameters, 106
 Fox-Flory parameters, 180
 M_e , 155
 Mark-Houwink paramters, 140
 nanocomposite, 317
 permeability, 487
 T_g , 19, 157, 174
 thermal expansion coefficient, 174

- polydispersity, 47, 145
polydispersity index, 15
polyelectrolyte, 411
polyene, 267
polyester
 aromatic, 24, 269
 blend, 397
 classification, 24
 composite, 312
 engineering-grade, 401
 fiber, 3, 340, 344, 347
 glass-reinforced composite, 313, 319
 hydrolysis, 271
 hydroxyl-terminated, 375
 liquid crystalline, 365, 418
 T_m , 178
 thermoplastic, 364
 unsaturated, 3, 308, 317, 318, 319, 379, 380, 380, 382, 430
polyesterification, 24, 25
polyether, 375
polyetheretherketone (*see* PEEK)
polyetherimide, 406, 408, 492
polyether-polyurethane, 277
polyethersulfone, 398, 399
poly(ethyl acrylate), 306, 307
polyethylene
 blends, 280
 blow molded, 435
 branching, 356, 357
 carbon black-filled, 522
 ceiling temperature, 267
 chain conformation, 92, 93
 chlorinated, 294, 305
 conductivity, 522
 die swell, 450
 encapsulants, 526
 enthalpy of fusion, 163
 entropy of fusion, 163
 film, 486
 γ -relaxation, 158
 heat-distortion temperature, 177
 high-density, 358
 history, 49, 355
 impact strength, 199
 linear low density, 358, 453
 low-density, 355
 mechanical properties, 194
 medium-density, 358
 membrane, 513
 molecular-weight distribution, 17
 permeability, 487, 494
 Poisson's ratio, 188
 production figures, 3, 354
 properties, 355
 sharkskin, 453
 T_g , 161, 179
 T_m , 161, 163
 UHMW, 289, 313 358, 414
 very-low-density, 358
 viscosity, 468
 WAXS, 167
poly(ethylene glycol), 521
poly(ethylene naphthalate), 402
poly(ethylene oxide), 453, 524
poly(ethylene pyromellitimide), 7
poly(ethylene terephthalate), 364
 applications, 366, 486
 blends, 402
 commercial market, 366
 crystallization kinetics, 164
 density, 166
 DSC thermogram, 175
 enthalpy of fusion, 163
 entropy of fusion, 163
 magnetic tape, 437
 permeability, 494
 Poisson's ratio, 188
 properties, 344, 401, 418
 recycling, 275
 synthesis, 24, 25
 T_g , 161
 T_m , 161, 163
 track-etched, 511
 WLF parameters, 244
poly(ethylene-*co*-vinyl acetate), 520
poly(ethyl methacrylate), 179, 244, 301, 302, 303
polyformaldehyde, 397
polyfuran, 58
poly(α , L-glutamic acid), 71
poly(hexamethylene adipamide), 345

- polyhydroxyalkanoate, 277, 277
polyhydroxybutyrate, 277
poly(2-hydroxyethyl methacrylate) (*see* PHEMA)
polyimidazopyrrolones, 410
polyimides, 404
classification, 24
composites, 309
dielectric, 525
encapsulant, 526
6F, 527
properties, 406
rigid-rod, 527
synthesis, 405
thermoset, 407
polyimines, 9
polyisobutylene, 372
critical molecular weight, 155
as drag reducer, 453
Flory EOS parameters, 106
 M_e , 155
osmotic pressure, 131
permeability, 487
solubility parameter, 115
solution properties, 123, 124
standards, 133
synthesis, 47, 48
WLF parameters, 244
cis-1,4-polyisoprene, 155, 161, 339, 369
trans-polyisoprene, 161
polyisoprene, 338, 369
as elastomer, 366
ozonolysis, 270
photooxidation, 270
structure, 368
polyisothianaphthalene, 523, 524
poly(lactic acid), 278
poly(lactide-*co*-glycolide), 279, 520
polymer electrolyte, 522, 524
polymeric plasticizer, 285, 288
polymerization
anionic, 46
atom transfer radical, 69
cationic, 47
chain-growth, 23, 29
coordination, 50
emulsion, 55
gas-phase, 57
Gibbs free energy, 38
group-transfer, 67
ionic, 45
living, 17, 46, 47
metallocene, 51, 357, 360
oxidative coupling, 26
plasma, 58
rate, 34
solid-state, 57
solution, 54
steady state, 35
step-growth, 23, 28
suspension, 55
yield, 27
polymethacrylamide, 272
polymethacrylates, 179
polymethacrylonitrile, 486, 487
poly(methyl methacrylate), 362
applications, 363
blend, 301, 302, 303
ceiling temperature, 267
critical molecular weight, 155
critical strain, 184
dual-mode parameters, 504
Fox-Flory parameters, 180
heat capacity, 54
IPN, 306
 M_e , 155
Mark-Houwink parameters, 140
mechanical properties, 194
membrane, 511
NMR spectrum, 78
Poisson's ratio, 188
solubility parameter, 115, 116
structure, 6
 T_g , 157, 174, 178, 179
tacticity, 77, 178, 218, 219
thermal conductivity, 54
thermal-expansion coefficient, 174
torsional-braid analysis, 218, 219
viscosity, 468
poly(4-methylpentene-1) (*see* PMP)
poly(α -methylstyrene), 155, 180, 267
poly(*p*-methylstyrene), 361

- poly(methyl vinyl ether), 302, 303
polynorbornene, 369
polynucleotides, 329
polyoctenamer, 369
poly[3-(4-octylphenyl)-2,2'-bithiophene], 528
polyolefins, 355
blends, 397
chlorinated, 517
specialty, 414
polyols, 381
poly(organophosphazene), 65, 404, 415
polyoxyethylene, 159
polyoxymethylene
 enthalpy of fusion, 163
 entropy of fusion, 163
 synthesis, 5, 58, 397
 T_g , 161
 T_m 161, 163
polypentenamer, 66, 67
poly(*p*-phenylene), 269, 420, 522, 523, 528
poly[2,2'-(*m*-phenylene)-5,5'-bibenzimidazole] (*see* PBI)
poly(*p*-phenylene-benzobisthiazole), 526
poly(*m*-phenylene isophthalamide), 392
poly(*p*-phenylene sulfide), 166, 390, 400
poly(*p*-phenylene terephthalamide), 392
poly(*p*-phenylene vinylene), 523, 526
polyphenylsulfone, 398
polyphosphazene, 75, 498, 524
poly(phosphoric acid), 421
polypropylene
 amorphous, 50
 atactic, 358
 blends, 306, 377
 ceiling temperature, 267
 enthalpy of fusion, 163
 entropy of fusion, 163
 fiber, 347
 film, 486
 heat-distortion temperature, 177
 helix, 159
 history, 2, 358
 impact strength, 199
 isotactic, 358, 359
 market data, 3
 mechanical properties, 194
 medical applications, 518
 membrane, 510, 513
 nanocomposite, 315
 permeability, 487
 power-law parameters, 449
 production numbers, 354
 properties, 277, 355
 spherulites, 160
 syndiotactic, 51, 358
 T_g , 179
 T_m , 163
 thermooxidative degradation, 359
 viscosity, 468
poly(propylene glycol), 375
poly(propyl methacrylate), 179
polypyromellitimide, 405
polypyrrolane, 492
polypyrrole, 269, 420, 421, 522, 523, 524
polyquinoline, 527
polysaccharide, 334, 335, 337
poly(*N,N'*-sebacoyl piperazine), 173
polysilane, 415
polysilastyrene, 415, 416
polysiloxane, 8, 24
polysiloxane-block-polycarbonate, 492
polystyrene
 applications, 360
 blends, 297, 299, 302, 303, 377
 ceiling temperature, 266, 267
 chloromethylation, 61, 62
 critical molecular weight, 155
 critical strain, 184
 crosslinked, 61, 361
 dispersity, 18
 dual-mode parameters, 504
 early production, 2
 encapsulants, 526
 expandable, 275, 294, 295, 359
 Flory EOS parameters, 106
 Fox-Florey parameters, 180
 general purpose, 359
 GPC chromatogram, 143
 heat capacity, 54
 heat-distortion temperature, 177

- high-impact, 10, 200, 283, 294, 304, 306, 360, 396
history, 3, 359
impact strength, 199, 199
IPN, 306, 307
isotactic, 360
 M_e , 155
Mark–Houwink parameters, 140
mechanical properties, 194
medical applications, 518
membrane, 513
molecular weight, 2
permeability, 494
photooxidation, 270, 360
Poisson's ratio, 188
power-law parameters, 449
production figures, 354
properties, 359
secondary relaxations, 158
solubility parameter, 115
solution, 446
solution viscosity, 447
standards, 133, 144
stereospecific, 360
syndiotactic, 12, 51, 52, 360, 519
 T_g , 157, 174, 179
thermal conductivity, 54
thermal expansion coefficient, 174
TMDSC, 241
toughening, 304
viscosity, 442, 444, 468
WLF parameters, 244
poly(styrene-*co*-acrylonitrile) (*see* SAN)
polystyrene-block-polybutadiene-block-polystyrene, 378
polysulfide, 370, 370, 371, 371
polysulfone, 398, 503
applications, 399
classification, 24
composites, 309
critical strain, 184, 271
dual-mode parameters, 504
dynamic mechanical data, 219, 220
heat-distortion temperature, 177
impact strength, 199
membrane, 490, 492
nanocomposite, 317
permeability, 494
properties, 390, 398
solubility parameter, 115, 271
structure, 219, 398
sulfonated, 517
synthesis, 399
 T_g , 157
polysulfurnitride, 521
polytetrafluoroethylene, 402
ceiling temperature, 267
conductivity, 522
degradation, 266
dielectric constant, 525
electrical insulator, 521
film, 510
nomenclature, 14
processing, 403
structure, 404
thermal degradation, 292
poly(tetrafluoroethylene-*co*-perfluoro(methyl vinyl ether)], 373
poly(tetrafluoroethylene-*co*-propylene), 373
polytetrahydrofuran, 374
polytetramethylene ether glycol, 378
polythioether, 9
polythiophene, 58, 420, 522, 522, 523, 526, 528
poly(thio-1,4-phenylene), 400
polytriazole, 492
poly(trimethylene terephthalate), 344
poly[1-(trimethylsilyl)-1-propyne], 492, 493, 494
polyurea, 9
polyurethane, 373
biodegradation, 277
classification, 24
elastomer, 371, 375
encapsulants, 526
foam, 292, 294, 373
IPN, 306
polyester-based, 375
polyether-based, 375
RIM, 293, 434, 435

- segmented, 518
synthesis, 26, 376
WLF parameters, 244
- poly(urethane-urea), 518
- poly(vinyl acetate), 363
critical molecular weight, 155
hydrolysis, 363
 M_e , 155
Mark–Houwink parameters, 140
permeability, 487
as precursor, 64
solubility parameter, 115
structure, 6
thermal expansion coefficient, 174
 T_g , 157, 174
WLF parameters, 244
- poly(vinyl alcohol)
biodegradation, 280
fiber, 349, 350
as gas barrier, 486
hydrogen bonding, 161
membrane, 490, 496
permeability, 487
as precursor, 61, 363
in suspension polymerizations, 55
synthesis, 54, 61, 64
 T_g , 161
 T_m , 161
thermal degradation, 267
- poly(vinyl amides), 271
- poly(vinyl butyral), 61, 64, 363
- poly(*N*-vinylcarbazole), 421
- poly(vinyl carboxylic acid), 271, 272
- poly(vinyl chloride)
blends, 302, 303
calendering, 437
chlorinated, 362
chlorination, 61
dehydrochlorination, 267, 268, 362
density, 166
dry blend resin, 361
dual-mode parameters, 504
encapsulants, 526
extrusion grade, 55
fiber, 350
flexible-grade, 283, 361
- Fox–Flory parameters, 180
FTIR spectroscopy, 74
heat capacity, 54
heat-distortion temperature, 177, 395
impact modified, 305
impact strength, 199
incineration, 277
injection-molding grade, 55
market data, 3
Mark–Houwink parameters, 140
mechanical properties, 194
medical applications, 518
membrane, 492
paste, 442
permeability, 487
for pipe applications, 290
Poisson's ratio, 188
production figures, 354
properties, 362
property modification, 362
rigid grade, 361
solubility parameter, 115
 T_g , 174
tacticity, 12, 161
thermal conductivity, 54
thermal-expansion coefficient, 174
thermal stabilizers, 267
toughening, 362
WLF parameters, 244
- poly(vinyl esters), 271
- poly(vinyl fluoride), 403, 404
- poly(vinylidene chloride), 6, 486, 487
- poly(vinylidene chloride-*co*-vinyl chloride), 55
- poly(vinylidene fluoride)
blends, 303
copolymer, 403
structure, 404
synthesis, 54
 T_g , 161
 T_m , 161
- poly(vinylidene fluoride-*co*-chlorotrifluoroethylene), 373
- poly(vinylidene fluoride-*co*-hexafluoropropylene), 373

poly(vinylidene fluoride-*co*-hexafluoropropylene-*co*-tetrafluoroelastomer), 373
poly(vinylidene fluoride-*co*-propylene), 373
poly(vinylidene fluoride-*co*-tetrafluoroethylene-*co*-perfluoro(methyl vinyl ether)], 373
poly(α -vinyl naphthalene), 179
poly(*N*-vinyl-2-pyrrolidinone), 54, 363, 514
poly(vinyltoluene-*co*- α -methylstyrene), 347
porous media, 500
porphyrin, 329
potassium persulfate, 364
power consumption
 in dynamic deformation, 213
 in extrusion, 472
power-law fluid, 454, 457, 458, 459, 460, 463, 474, 475, 477
power-law index, 448, 458, 474, 477
power-law model, 448
power-law parameters, 448
Prausnitz, 123
preform molding, 317
pressure drop, 471
Price, 42
primary amine silane coupling agent, 312
processing additives, 291, 293
proline, 328
propagation rate constants, 35
propagation step, 31
proportional limit, 189
propylene
 ceiling temperature, 40
 heat of polymerization, 40
 polymerization, 51
propylene carbonate, 524
protein
 adsorption, 518
 conformation, 326
 fibrous, 328, 329
 globular, 328
 primary structure, 328

quaternary, 328
secondary structure, 328
synthesis, 61, 329, 333
tertiary structure, 328
Protein Data Bank, 329
proteomics, 329
Pseudomonas oleovorans, 277
puffup, 452
pultrusion, 309, 319
purine, 330
purine base, 331
pyridine base, 331, 333
pyrimidine, 330
pyromellitic anhydride, 405
pyrrole polymerization, 421

Q

Q-e scheme, 42
quinone derivative, 25, 27

R

radial distribution function, 89
radiation-sterilizable, 518
radiolysis, 273
radius of gyration, 135
Raman spectroscopy, 74
Raoult's law, 95
rate-of-deformation tensor, 450, 454
Rayleigh ratio, 134
rayon, 3, 63, 289, 337, 339, 341, 342, 343, 350
reaction-injection molding (*see* RIM)
reactive compatibilizer, 295
reactivity ratio, 41, 43
Rebok, 403
reciprocity relationship, 250
recycling, 274
redox initiator, 55
reduced viscosity, 140
refractive index, 134
reinforced reaction injection molding (*see* RRIM)
reinforcement, 284
relative viscosity increment, 139, 140
relaxational time, 235

relaxation spectra, 228
relaxation time, 222
relaxation-time distribution, 229
repeating unit, 1
reptation, 155, 156
resite, 383
resole, 383, 383
resorcinol, 382
retardation spectrum, 228, 230
retentate, 495
reverse osmosis, 488, 489, 490, 491, 511, 516
rheology, 439
rheometry, 461
ribosome, 328, 333
RIM, 293, 373, 434, 435
RNA, 329, 333
roll coating, 437, 438
rotational molding, 436
rotomolding, 436
Rouget, 337
roving, 319
RRIM, 435
rubber
 crosslinking, 370
 market data, 3
 production, 367
rubber elasticity, 249
rubbery plateau, 190, 245, 285
rule of mixtures, 181
runners, 433

S

Salame, 486
SAN, 55, 301, 302, 354
Sanchez, 103
Saran, 362, 486
SBR, 3, 13, 360, 366, 367, 368, 369, 377
SBS, 10, 48
Scatchard–Hildebrand equation, 117
Schatzki crankshaft motion, 157
Schering bridge, 238
Schiff base, 61
Schonbein, 2
Schrager equation, 311
Schultz, 16

Scott, 298
screw characteristic, 458, 472
secant modulus, 189
secondary relaxation, 19, 154, 157, 220
second law of thermodynamics, 249
second normal stress difference, 451, 452
second-order transition, 168, 170
second virial coefficient, 112, 130, 138
segment fractions, 106
segment volume fraction, 119
self-condensation, 24, 25
separation factor, 496
serine, 328
serum albumin, 329
S-glass, 290, 318
sharkskin, 452
shear banding, 183, 185
shear compliance, 191
shear flow, 439
shear-induced degradation, 441
shear modulus, 191, 253
shear storage modulus, 230
shear strain, 439
shear strain rate, 439
shear stress, 439
shear-stress tensor, 456
shear thickening, 442
shear thinning, 441, 445
sheet-molding compound, 317, 318
shellac, 428
shift factor, 242, 244
Shirakawa, 522
siemen, 521
silanol group, 312
silicon carbide, 416
silicon dioxide, 525
silicone rubber, 316, 366, 371, 492, 492, 494, 502, 514, 526
silk, 71, 339, 340
Silly Putty, 207
silver, 522
Simha, 103, 173
simple flow, 439, 454, 468
simple shear flow, 454
SIMS, 59
Sinn, 51, 357

- site fraction, 107
size exclusion, 499
size-exclusion chromatography, 128, 142
slit die rheometer, 452
slit flow, 472
slit rheometer, 461, 467
slush molding, 436
Small, 113
smectic, 417
SMC (*see* sheet-molding compound)
Smith-Ewart, 57
sodium cellulose, 337
sodium naphthalenide, 48, 49
sodium thiocyanate, 350
solubility parameter, 113, 118, 271
solution
 critical concentration, 445
 rheometry, 467
 viscoelastic properties, 230
 viscosity, 445
solution-diffusion model, 499
solution-diffusion transport, 501
solution-of-functional groups, 118
solvent cracking, 271
solvent crazing, 271
Sourirajan, 511
Spandex, 350, 366, 371
specific heat, 169, 174
specific heat increment, 172, 176
specific refractive increment, 134
specific retention volume, 112
specific volume, 129
spherulite, 153
spherulitic growth, 164
spinneret, 347, 349, 350
spinning, 428
spinodal curve, 110, 296, 300, 301
spinodal decomposition, 513
sprue, 433
Staphylococcus, 488
starch, 278, 280, 334, 335
star polymers, 69
static testing, 186
statistical theory of rubber elasticity, 255
Staudinger, 252
steady-shear flow, 231
steady-shear viscosity, 231
stearic acid, 370
steel, 290
step growth, 8
stereoregularity, 368
Stirling approximation, 96
storage compliance, 211
storage modulus, 211, 215, 248
strain softening, 192
stress-at-break, 192
stress relaxation, 186, 195, 198, 223
stress-relaxation modulus, 198, 245, 248
stress-strain curve, 192, 193
stress tensor, 450, 455
structure-property relationships, 177
styrene
 biodegradation, 280
 ceiling temperature, 40
 copolymer, 360
 copolymerization, 41, 44
 graft copolymerization, 361
 heat of polymerization, 40
 initiation, 46
 polymerization, 31, 69, 70, 359
 $Q\text{-}e$ values, 43
 rate constants, 35
 reactivity ratios, 43
 styrene-acrylonitrile copolymer, 184, 294,
 361, 393
 styrene-butadiene rubber (*see* SBR)
 styrene-butadiene-styrene triblock
 copolymer, 377
 styrene-maleic anhydride copolymer, 305,
 397
 styrenic elastomers, 367
 styrenic polymers, 3, 354
sulfate anion, 55
sulfolane, 513
sulfonyl chloride, 399
sulfonyl fluoride, 412, 509
sulfur bridges, 370
sulfuric acid, 522
sulfur vulcanization, 339
supercritical fluids, 60
supramolecular structure, 329
surface area, 107, 119

surfactant, 55

Surlyn, 411

suspension, 447

suture, 518

syndiotactic, 10

T

Takayanagi model, 313

talc, 401

N-tallowdiethanolamine, 513

$\tan \delta$, 211

Tedlar, 403

Teflon (*see* polytetrafluoroethylene)

temperature-modulated DSC, 176, 240

tenacity, 340

tensor, 450

terephthalic acid, 344

termination, 32

terpolymer, 10

terpolymerization, 40

3,5,3',5'-tetramethyldiphenoxquinone, 396

texturing, 348

thermal conductivity, 54

thermal degradation, 264, 264

thermal-expansion coefficient, 105, 117, 170, 173, 444, 478

thermally induced phase separation, 510, 512

thermally-stable polymers, 268

thermally stimulated current analysis, 239

thermal-pressure coefficient, 105

Thermid, 407

thermoelastic behavior, 252

thermoforming, 435

thermoplastic, 4, 354

thermoplastic elastomers, 366, 367, 377

thermoset, 4, 378, 431

θ conditions, 130, 154

θ temperature, 94, 102

third virial coefficient, 130

thiuram disulfides, 370

thixotropic, 445

Thomson formula, 166

threonine, 328

threshold stress, 449

thymine, 331

time lag, 507

time-temperature superposition, 197, 198, 242

tires, 276, 369

titanate coupling agent, 312

titanium dioxide, 294, 397

titanium tetrachloride, 356

toluene-2,4-diisocyanate, 374, 375

Torlon, 406, 408

torque, 466

torsional-braid analysis, 214, 217

torsion pendulum, 214, 215, 217

tortoise shells, 435

toughened plastics, 304

tow, 319

transesterification, 395

transfer molding, 430, 430, 431

transfer pot, 430

transform space, 247

transient testing, 195

Treloar, 94

trialkyl phosphate, 288

trialkyl trimellitates, 288

triazine structure, 404

tributyltin oxide, 293

tricresyl phosphate, 288

trioctyl trimellitate, 286, 288

trioxane polymerization, 5, 58, 397

Tripodi, 514

Trommsdorff effect, 53

Trotton viscosity, 440

true stain, 187

true stress, 187

tryptophan, 328

tyrosine, 328

U

Ubbelohde viscometer, 141

Udel, 400

Ultim, 406, 408

ultimate stress, 192

ultrafilter, 489

ultrafiltration, 489, 490, 491, 516

UNIFAC, 118

UNIFAC-FV, 118, 123, 124

Unipol process, 52, 57, 58, 358

UNIQUAC, 118, 120
unity tensor, 456
universal calibration curve, 144
unperturbed dimensions, 93, 93, 94, 154
upper critical solution temperature, 110, 296, 297, 513
uracil, 331
urea-formaldehyde resin, 378, 384, 385
urea linkage, 375
urea resins, 3, 379
urethane groups, 376
urethane-polyolefin formulation, 293
UV
 absorbers, 292
 coating, 438
 irradiation, 30, 363
 stability, 269

V

vacuum forming, 435
valine, 328
van der Waals surface area, 119
van't Hoff equation, 129
van Krevelen, 113
vapor-liquid equilibria, 118
vapor-pressure osmometry, 132
Vectra, 417
velocity profile, 455, 457, 458, 459, 460
vibrational spectroscopy, 72
vibration damping, 308
Vicor glass, 510
Victrex, 412
vinyl acetate
 Q-e values, 43
 rate constants, 35
vinyl chloride
 copolymer, 361
 copolymerization, 362
 polymerization, 361
 Q-e values, 43
 rate constants, 35
 reactivity ratios, 43
vinyl chloride-vinylidene chloride copolymer, 362
vinyl ester copolymerization, 355
vinyl ether copolymerization, 355

vinylidene chloride
 Q-e values, 43
 rate constants, 35
vinylidene fluoride copolymer, 403, 404
vinylmethylsilanol, 372
vinyl polymerization, 45
N-vinyl pyrrolidone, 43
vinyl silane coupling agent, 312
viscoelastic, 207
viscometric flow, 459
viscose, 343
viscose process, 63, 342, 350
viscosity
 coefficient, 439
 dynamic, 467
 molecular weight dependence, 442
 number, 140
 pressure dependence, 444
 shear-rate dependence, 449
 temperature dependence, 443
 time dependence, 445
viscous flow, 190, 500, 501
viscous fluid, 196
viscous heating, 427, 465
Viton, 366, 371, 373
Voigt element, 221, 225
Voigt-Kelvin model, 228, 229
volume change of mixing, 101
volume fraction, 99, 129
volumetric flow, 461, 469
volumetric flow rate, 458, 460, 463
vulcanization, 48, 366, 369, 370

W

water-soluble polymer, 61, 453, 514, 518
Watson, 331
weak-link degradation, 265
weathering, 264
web, 437
wet spinning, 349, 350
Wheatstone bridge, 238
whiskers, 289
Wilkins, 331
Williams-Landel-Ferry (*see* WLF)
wire coating, 428, 475
WLF equation, 243, 443

WLF parameters, 254, 444, 477, 478
wood, 335
Wood equation, 285
wood flour, 383
wood pulp, 342, 490
wool, 339, 340
work in dynamic deformation, 213
Wurtz reaction, 415

X

Xanthamonas, 453
xanthan, 453
xanthate process, 337
x-ray scattering
 small-angle (SAXS), 166
 wide-angle (WAXS), 166
Xydar, 417
2,6-xylenol polymerization, 27

Y

yarn, 340
yield behavior, 448
yield strength, 194
yield stress, 192, 449
Young's modulus, 189, 245, 253, 310

Z

zero-shear viscosity, 441, 442
Ziegler, 2, 50
Ziegler catalyst, 66, 356, 358
Ziegler–Natta catalyst, 358, 368, 376
Ziegler–Natta polymerization, 50, 52
Zimm method, 136
Zimm plot, 137, 137
zinc oxide, 370, 371
zinc stearate. 317