J2eeTutorial.book Page 475 Tuesday, March 5, 2002 11:14 AM

Index

A

abstract schemas, 53
  defined, 166
  deployment descriptors, 53
  `deploytool`, 134
  EJB QL, 165
  hidden from clients, 58
  names, 166
  naming conventions, 63
  types, 166
access methods
  examples, 132, 138
  local interfaces, 127
  persistent fields, 54, 123
  primary keys, 152
  relationship fields, 55, 124
`ant`
  downloading, xxiii
  examples, 26
  running, xxiii
  See also `ANT_HOME`
  version, xxiii
`ANT_HOME`, xxiii, 23
Apache Software Foundation, xxiii
  Jakarta project, xxiii
`APPCPATH`, 37
applet containers, 10
applets, 4, 6
Application Deployment Tool
  See `deploytool`
audience of this tutorial, xxi
authentication, 335, 359, 367
  J2EE application clients
    configuring, 347
  Web resources, 338
    authentication, 338
    client-certificate, 339
    configuring, 339
    Duke's Bank, 414
    form-based, 338
    HTTP basic, 338
    setting up
      client-certificate, 350
    SSL protection, 339
authorization, 335, 367

B

bean-managed persistence
  database connections, 357
  defined, 52
  examples, 84, 104, 112
  isolation levels, 329
  relationships, 53
bean-managed transactions
  See transactions, bean-managed

J2eeTutorial.book Page 476 Tuesday, March 5, 2002 11:14 AM

BufferedReader, 223
business logic, 48, 92
business methods, 30, 32, 58
  client calls, 73
  database connections, 358
  examples, 91, 125
  exceptions, 74
  local interfaces, 127
  message-driven beans, 158
  requirements, 74
  transactions, 319–320, 322, 326, 329
business objects, 51, 83

C

cascade delete, 133
CCI
  See J2EE Connector technology, CCI
cleanup, 431
  when to use, 45
Cloudscape database
  container-managed persistence, 136
  interactive SQL tool, 432
  JNDI name, 354
  method aliases, 387
  resource adapters, 371–372
  starting, 97, 432
  stopping, 97, 432
commit, 323–324, 326–327
commits
  See transactions, commits
Common Client Interface
  See J2EE Connector technology, CCI
concurrent access, 315
Connection, 323–325, 328, 331, 354, 357, 371, 376
connection factories
  databases, 355
  defined, 354
  queues, 157
  resource adapters, 368
  See also DataSource
ConnectionFactory, 375
connectors
  See J2EE Connector technology
container-managed persistence, 53
  database connections, 357–358
  EJB QL, 53, 165
  examples, 119
  isolation levels, 329
  relationships, 53
container-managed relationships
  bidirectional, 55
  defined, 53
  deploytool, 131
  direction, 59, 120, 133
  EJB QL, 56
  examples, 120
  local access, 59
  many-to-many, 55
  many-to-one, 55
  multiplicity, 55, 120, 133
  one-to-many, 55, 167
  one-to-one, 55, 180
  unidirectional, 55
container-managed transactions
  See transactions, container-managed

J2eeTutorial.book Page 477 Tuesday, March 5, 2002 11:14 AM

containers, 8
See also
applet containers
EJB containers
J2EE application clients, containers
Web containers
services, 8
`Context`, 29
context roots, 199
specifying, 37, 200
`create`, 320
bean-managed persistence, 85
compared to `ejbCreate`, 75
container-managed persistence, 136
examples, 29, 72, 106
life cycles, 63, 65
requirements, 75, 95, 126
custom tags, 268
attributes, 286
validation, 295
bodies, 287
cooperating, 288
defining, 289
examples, 304, 308
scripting variables
defining, 287
providing information about, 300, 302
Struts tag library, 281
tag handlers, 289
defining scripting variables, 298
methods, 289
simple tag, 293
with attributes, 294
with bodies, 296
tag library descriptors
See tag library descriptors
tutorial-template tag library, 281

D

data integrity, 315–316, 358
databases
bean-managed persistence, 83, 93
business methods, 91
clients, 4, 48, 58
Cloudscape
See Cloudscape database
connection factories, 355
connections, 57, 64, 74, 116, 326, 357
creating tables, 84, 97, 135
data recovery, 315
deleting rows, 87
Duke's Bank tables, 398
EIS tier, 3
entity beans and tables, 51
exceptions, 116
foreign keys, 55, 100
inserting rows, 85
isolation levels, 328
J2EE SDK, 15
JNDI names, 136, 354
message-driven beans, 57
multiple, 325, 329
persistent fields, 54
portable beans, 53
primary keys, 100, 113
read-only data, 51
referential constraints, 100

J2eeTutorial.book Page 478 Tuesday, March 5, 2002 11:14 AM

databases (*continued*)
relationships for bean-managed persistence, 99
resource references, 354
See also persistence
stored procedures, 376, 379
synchronizing with entity beans, 88
table relationships
many-to-many, 110
one-to-many, 103
one-to-one, 99
transactions
See transactions
`DataSource`, 354–355, 357, 371
deployer role, 14
deployment descriptors, 11
abstract schema, 53
container-managed persistence, 123
creating, 62
EJB QL, 165
enterprise bean, 62
viewing, 27
enterprise beans, 63
J2EE application client
viewing, 31
primary key class, 113
transaction attributes, 319
Web application, 194
viewing, 34
`deploytool`
bean-managed persistence, 99
container-managed persistence, 128, 148
database users and passwords, 358
message-driven beans, 160
online help, 23
options, 434
redeploy operation, 39
resource adapters, 368
resource references, 354
starting, 23
wizards, 19
`destroy`, 241
development roles, 11
`doAfterBody`, 297
`doEndTag`, 293
`doFilter`, 229, 233–234
`doGet`, 222
`doInitBody`, 297
`doPost`, 222
`doStartTag`, 293
downloading
J2EE SDK, xxii
J2SE, xxiii
tutorial, xxii
Duke's Bank, 391
building, 416
database tables, 398
deploying, 423
enterprise beans, 393–400
J2EE application client, 400–408
running, 424
JNDI names, 420, 422
packaging, 416
Web client, 408–415
component interaction, 413
running, 425

J2eeTutorial.book Page 479 Tuesday, March 5, 2002 11:14 AM

E
EAR files, 11
adding WAR file, 197
EJB JAR files, 62
examples, xxii
EIS, 8, 365, 370, 375–376
EJB components
See enterprise beans
EJB containers, 10
bean-managed persistence, 85
connection pools, 359
container-managed persistence, 52
container-managed transactions, 316
EJB QL, 53
generating primary keys, 153
instance contexts, 80
instantiating enterprise beans, 63, 72
`onMessage`, 158
persistence, 119
persistent fields, 123
relationships, 53, 119
services, 47–48
EJB JAR files
container-managed relationships, 60
contents, 11
EJB QL, 165, 178
examples, 26
portability, 62
EJB QL, 165
abstract schemas, 166, 178, 190
arithmetic functions, 187
boolean logic, 188
case sensitivity, 177
`cmp_field`, 180
`cmr_field`, 180
collection member declarations, 179
collections, 179, 186
comments, 191
compared to SQL, 165, 169, 177
conditional expressions, 182–183
delimiters, 180
deployment descriptors, 53
`deploytool`, 135, 149
domain of query, 165, 176, 178
examples, 167
finder methods, 53, 145
identification variables, 167, 176–177
input parameters, 183
multiple declarations, 178
navigation, 166, 169, 179, 181
navigation operator, 169, 180
null values, 186, 188
operators, 184
parameters, 168
path expressions, 166, 179
range variables, 178
relationship direction, 56
scope, 165
select methods, 124
string functions, 187
syntax diagram, 173
translated into SQL, 145
types, 181, 189–190
`ejbActivate`, 64–66, 358
`EJBContext`, 321, 323, 327

J2eeTutorial.book Page 480 Tuesday, March 5, 2002 11:14 AM

ejbCreate
bean-managed persistence, 85
compared to create, 75
container-managed persistence, 126
database connections, 358
examples, 72, 85, 105, 126, 137
life cycles, 63, 65, 67
message-driven beans, 159
primary keys, 66, 115, 152
requirements, 73
ejbFindByPrimaryKey, 89, 115
EJBHome, 74
ejbLoad, 88, 108, 111, 126, 322
EJBObject, 76
ejbPassivate, 64–65, 67, 358
ejbPostCreate, 65, 86, 126
ejbRemove
bean-managed persistence, 87, 112
container-managed persistence, 126
database connections, 358
examples, 87
life cycles, 64–65, 68
message-driven beans, 159
ejbStore, 88, 126
enterprise beans, 6, 24–25, 47
accessing, 58
business methods
See business methods, 25
compiling, 26
contents, 62
database connections, 357
defined, 48
deployment, 62
development role, 13
distribution, 60
Duke's Bank, 393–400
protecting, 400
entity beans
See entity beans
environment entries, 78
home interfaces
See home interfaces
interfaces, 58, 62
life cycles, 58, 63
local access, 59
local home interfaces
See local home interfaces
local interfaces
See local interfaces
lookups, 29
mapping references to JNDI names, 36
message-driven beans
See message-driven beans
method permissions
See method permissions
packaging, 26
performance, 60–62
persistence
See persistence
propagating security identity, 346
protecting, 340
references, 29, 32, 35
remote access, 58
remote interfaces
See remote interfaces
sending e-mail, 359
session beans
See session beans
state, 55
transactions, 327

J2eeTutorial.book Page 481 Tuesday, March 5, 2002 11:14 AM

types, 7, 49
unprotected, 342
URL connections, 362
Enterprise Information Systems
See EIS
Enterprise JavaBeans Query Language
See EJB QL
`EnterpriseBean`, 72
entity beans, 51
bean-managed persistence
See bean-managed persistence
collections, 179
container-managed persistence
See container-managed persistence, 53
container-managed
versus bean-managed, 122
database connections, 358
Duke's Bank, 397
equality, 80
finder methods, 59
garbage collection, 67
isolation levels, 329
persistent state, 56
primary keys
See primary keys
transactions, 320, 322–323, 327
`EntityBean`, 85
`EntityContext`, 80, 87
environment entries, 78
environment variables, xxiii, 23
examples
classpath, 26
downloading, xxii
location, xxii, 22
troubleshooting, 40, 215
exceptions
business methods, 74
`create`, 75, 95
`ejbCreate`, 73, 86
`ejbFindByPrimaryKey`, 90
`ejbRemove`, 87
enterprise beans, 116
`javax.ejb`, 117
mail server exceptions, 362
mapping to Web resources, 201
rolling back transactions, 117, 321, 325–326
SQL, 321
transactions, 318–319
Web components, 201

F

`Filter`, 229
filter chains, 229, 233
filters, 227
defining, 229
mapping to Web components, 232
mapping to Web resources, 232–234
overriding request methods, 231
overriding response methods, 231
response wrapper, 231
`findByPrimaryKey`, 110, 138, 141
finder methods
bean-managed persistence, 89

J2eeTutorial.book Page 482 Tuesday, March 5, 2002 11:14 AM

finder methods (*continued*)
compared to select methods, 124
container-managed persistence, 122
deploytool, 135
EJB QL, 167
examples, 89, 101, 144, 190
home interfaces, 95
local home interfaces, 127
returning collections, 106
transactions, 320
forward, 236

G
garbage collection, 67–68
GenericServlet, 210
getCallerPrincipal, 341
getEJBObject, 87
getObject, 80
getParameter, 223
getPrimaryKey, 87, 116
getRemoteUser, 340
getRequestDispatcher, 234
getServletContext, 237
getSession, 238
getters
See access methods
getUserPrincipal, 340

H
helper classes, 62, 76, 103
Duke's Bank, 397
home interfaces, 74, 94
defined, 58
examples, 25, 75, 94
home methods, 93
locating, 28, 33
home methods, 92, 96
HTTP protocol, 427
HTTP requests, 223, 428
methods, 428
query strings, 224
See also requests
URLs, 223
HTTP responses, 226, 428
See also responses
status codes, 201, 428
mapping to Web resources, 201
HttpServlet, 210
HttpServletRequest, 223
HttpServletResponse, 226
HttpSession, 238

I
identification, 335
include, 235, 263
init, 222
installation, 23
internationalization
J2EE application clients
Duke's Bank, 414
Web clients
Duke's Bank, 414
invalidate, 239
isCallerInRole, 341
isIdentical, 80
isolation levels, 328
isThreadSafe, 259
isUserInRole, 340
isValid, 295

J2eeTutorial.book Page 483 Tuesday, March 5, 2002 11:14 AM

J

`j2ee`
  options, 435
  See also J2EE server
J2EE application clients, 5, 28
  containers, 10
  Duke's Bank, 400–408
    classes, 401
    running, 424
  examples, 30, 157, 403
  JAR files, 11, 28
  packaging, 31
  See also `runclient`
J2EE applications, 3
  assembler role, 13
  components, 11
  deploying, 37
  design guidelines, xxv
  iterative development, 39
  See also Duke's Bank, 391
  tiers, 2
J2EE clients, 4
  application clients, 5
    See also J2EE application clients
  Web clients, 4
    See also Web clients
  Web clients versus J2EE application clients, 5
J2EE components
  defined, 3
  more information, xxiv
  types, 3
J2EE Connector technology, 365
  architecture version, 18
  CCI, 375
  more information, xxv
  resource adapters
    See resource adapters
J2EE group, 335, 348
J2EE platform, 1–2
J2EE SDK, 14
  databases, 15
  downloading, xxii, 15
  installing, 23
  tools, 19
J2EE security architecture, 334
J2EE server, 10
  restarting, 45
  starting and stopping, 23
J2EE specifications, xxi
`J2EE_HOME`, xxiii, 23
`j2eeadmin`, 159, 368, 371, 430
J2SE
  downloading, xxiii
  required version, xxiii
JAAS, 18
JAF, 17
JAR files
  `j2ee.jar`, 26
  See also
    EJB JAR files
    J2EE application clients, JAR files
Java API for XML Processing
  See JAXP
Java Authentication and Authorization Service
  See JAAS
Java BluePrints, xxv
Java Message Service
  See JMS
Java Naming and Directory Interface
  See JNDI

J2eeTutorial.book Page 484 Tuesday, March 5, 2002 11:14 AM

Java Servlet technology, 16
See also servlets
Java Transaction API
See JTA
JAVA_HOME, xxiii, 23
JavaBeans Activation Framework
See JAF
JavaBeans components, 5
benefits of using, 271
creating in JSP pages, 272
design conventions, 270
Duke's Bank, 409
in WAR files, 196
methods, 270
properties, 270
retrieving in JSP pages, 275
setting in JSP pages, 273
using in JSP pages, 272
JavaMail API, 17
more information, xxv
JavaServer Pages (JSP)
technology, 16
See also JSP pages
javax.resource, 377
javax.servlet, 210
javax.servlet.http, 210
javax.servlet.jsp.tagext, 289
JAXP, 17
more information, xxv
tutorial, xxiv
JDBC API, 16
more information, xxv
transactions
See transactions, JDBC
versus J2EE Connector technology, 365
JMS, 16
examples, 155
message listeners, 56
message-driven beans
See message-driven beans
more information, xxv
tutorial, xxiv, 8, 155
JNDI, 16, 29
deploytool, 36, 129, 150, 355
JMS destination, 161
lookup, 29, 354, 357, 360, 378
mail sessions, 360
more information, xxv
names, 354
Duke's Bank, 420, 422
naming context, 29
resource adapters, 368, 371
resource references, 354
tutorial, xxiv
URL connections, 362
JSP declarations, 260
JSP expressions, 262
JSP pages, 246
compilation, 253
errors, 254
compiling, 34
creating and using objects, 259
creating dynamic content, 257
creating static content, 257
custom tags
See custom tags
declarations
See JSP declarations
Duke's Bank, 408
eliminating scripting, 268
error page, 255
examples, 32, 196, 248–249, 281
execution, 254

J2eeTutorial.book Page 485 Tuesday, March 5, 2002 11:14 AM

JSP pages (*continued*)
expressions
See JSP expressions
finalization, 256
forwarding to an error page, 255
forwarding to other Web components, 265
implicit objects, 258
importing classes and packages, 260
importing tag libraries, 285
including applets or JavaBeans components, 265
including other Web resources, 263
initialization, 256
JavaBeans components
creating, 272
retrieving properties, 275
setting properties, 273
from constants, 273
from request parameters, 273
from runtime expressions, 274
using, 272
life cycle, 253
scripting elements
See JSP scripting elements
scriptlets
See JSP scriptlets
setting buffer size, 255
shared objects, 259
specifying scripting language, 260
translation, 253
enforcing constraints for custom tag attributes, 295
errors, 254
URLs for running, 38
JSP scripting elements, 260
JSP scriptlets, 261
drawbacks, 267
JSP tag libraries, 268
`jsp:fallback`, 266
`jsp:forward`, 265
`jsp:getProperty`, 275
`jsp:include`, 264
`jsp:param`, 265–266
`jsp:plugin`, 265
`jsp:setProperty`, 273
`jspDestroy`, 256
`jspInit`, 256
JTA, 17
See also
transactions, JTA
JTS API, 325

K

`keytool`, 435

L

listener classes, 216
defining, 216
Duke's Bank, 410
examples, 217
specifying, 218
listener interfaces, 216
local home interfaces, 126
defined, 59

J2eeTutorial.book Page 486 Tuesday, March 5, 2002 11:14 AM

local home interfaces (*continued*)
examples, 136
local interfaces, 127
defined, 59
examples, 127–128, 138
requirements, 97
lookup
See JNDI, lookup

M

mail sessions, 359
message-driven beans, 56
accessing, 57
defined, 56
garbage collection, 68
onMessage method, 57
requirements, 157
transactions, 316, 320, 323–324, 328
messages, 155
method permissions
Duke's Bank, 400
specifying, 341

O

onMessage, 158

P

packager, 436
application client JAR files, 437
EAR files, 438
EJB JAR files, 436
RAR files, 439
setting runtime deployment descriptor, 438
WAR files, 437
PATH, xxiii, 23
persistence
bean-managed
See bean-managed persistence
container-managed
See container-managed persistence
entity beans, 51
session beans, 50
types, 52
persistent fields, 54
deploytool, 134
EJB QL, 166, 180
examples, 124
physical schemas, 53
prerequisites, xxii
primary keys
automatically generating, 153
bean-managed persistence, 113
composite, 113, 151
container-managed persistence, 151
defined, 52
examples, 113, 151
methods for setting, 66
returned by create, 85
See also ejbFindByPrimaryKey
printing the tutorial, xxv
PrintWriter, 225

Q

queues, 156, 158

J2eeTutorial.book Page 487 Tuesday, March 5, 2002 11:14 AM

R
RAR files, 366, 370
realms, 348
  certificate, 348
  default, 348
    Duke's Bank
      adding groups and users, 416
    managing users and groups, 349
`realmtool`, 440
reference implementation
  See J2EE SDK
relationship fields
  defined, 55
  `deploytool`, 132
  direction, 55
  EJB QL, 166, 180
  examples, 124
  modifying by local clients, 142
relationships
  bean-managed persistence, 53
  container-managed
    See container-managed relationships
  multiplicities, 55
`release`, 297
remote interfaces
  defined, 58
  example, 24
  examples, 76, 96
  requirements, 76
`remove`
  bean-managed persistence, 87
  life cycles, 64–65
  transactions, 320
`RequestDispatcher`, 234
requests, 223
  appending parameters, 265
  customizing, 230
  getting information from, 223
  retrieving a locale, 206
  See also HTTP requests
required software, xxii
resource adapters, 366
  archive files
    See RAR files
  black box testing, 369
  CCI, 375
  deploying, 368
  examples, 372, 376
  properties, 370
  security, 345
resource bundles, 206
resource connections, 353
resource references, 354, 374
responses, 225
  buffering output, 225
  customizing, 230
  See also HTTP responses
  setting headers, 223
roles
  development
    See development roles
  security
    See security roles
`rollback`, 316, 323–324, 326–327
rollbacks
  See transactions, rollbacks
`runclient`
  examples, 38
  options, 441

J2eeTutorial.book Page 488 Tuesday, March 5, 2002 11:14 AM

S
security
application client tier, 342
callback handlers, 342
application client tier login modules, 342
specifying a callback handler, 343
authentication
See authentication
declarative, 334
EIS tier, 343
component-managed sign-on, 344
configuring sign-on, 344
container-managed sign-on, 344
sign-on, 343
EJB tier
method permissions
See method permissions
programmatic, 341
login example, 38
programmatic, 334
resource adapter, 345
Web tier, 337
programmatic, 340
security constraints
specifying, 338
security identity, 346
caller identity, 346
configuring propagation, 346
propagating to enterprise beans, 346
specific identity, 346
security role references, 335
mapping to security roles, 336
security roles, 335
creating, 335
Duke's Bank, 400
mapping to groups, 423
mapping to J2EE users and groups, 337
select methods, 124, 135, 146
EJB QL, 172, 190
`Servlet`, 210
`ServletContext`, 237
`ServletInputStream`, 223
`ServletOutputStream`, 225
`ServletRequest`, 223
`ServletResponse`, 225
servlets, 210
binary data
reading, 223
writing, 225
character data
reading, 223
writing, 225
Duke's Bank, 411
examples, 196
finalization, 241
initialization, 222
failure, 222
life cycle, 216
life cycle events
handling, 216
service methods, 222
notifying, 242
programming long running, 243
tracking service requests, 242
session beans, 49
activation, 64
clients, 49
compared to entity beans, 52

J2eeTutorial.book Page 489 Tuesday, March 5, 2002 11:14 AM

database connections, 357–358
databases, 322
Duke's Bank, 394–397
equality, 80
examples, 25, 69, 79
isolation levels, 329
passivation, 64
requirements, 70
stateful, 50–51
stateless, 50–51, 57
transactions, 320, 322, 324, 326–327, 331
SessionBean, 72
SessionContext, 80
sessions, 238
associating attributes, 238
associating with user, 240
invalidating, 239
notifying objects associated with, 239
setEntityContext, 65, 106, 108, 358
setMessageDrivenContext, 67
setSessionContext, 63, 81, 377
setters
See access methods
SingleThreadModel, 220
SQL, xxii, 15–16, 53, 84–88, 94, 135, 145, 149, 169, 177, 322, 324–325, 379
SQL92, 165, 188

T

tag handlers
life cycle, 313
tag library descriptors, 290
attribute, 294
body-content, 293, 298
filenames, 285
listener, 291
mapping name to location, 286
tag, 292
taglib, 291
variable, 300
TagExtraInfo, 295
taglib, 285
timeouts, 328
transactions, 315, 324
attributes, 317
bean-managed, 316, 323, 327–328, 331
boundaries, 52, 316, 323
business methods
See business methods, transactions
commits, 316, 322, 324–327, 329
container-managed, 316, 323, 327–328
database connections, 358
defined, 316
entity beans
See entity beans, transactions
examples, 321–323, 325–326, 329
exceptions
See exceptions, transactions
JDBC, 324, 327, 329
JTA, 324–325, 327–328
levels for resource adapters, 369
managers, 319, 324–325, 329–330

J2eeTutorial.book Page 490 Tuesday, March 5, 2002 11:14 AM

transactions (*continued*)
message-driven beans, 57
See message-driven beans, transactions
nested, 317, 325
resource adapters, 367
rollbacks, 316, 321–322, 324, 326–328
scope, 317
session beans
See session beans, transactions
shared data, 52
tips, 327
Web components, 221, 331
XA, 367, 371
troubleshooting, 40, 362

U

`UnavailableException`, 222
`unsetEntityContext`, 66, 358
URL, 353, 362
`UserTransaction`, 323, 326–328, 331
utility classes, 62, 84

V

`verifier`
options, 443
running, 45

W

WAR files, 194
adding component files, 198
adding to EAR files, 197
adding Web component files, 34
contents, 11
creating, 197
directory structure, 196
JavaBeans components in, 196
specifying error pages, 218
Web application archives
See WAR files
Web clients, 4, 193
configuring, 194, 199
deploying, 203
Duke's Bank, 408–415
custom tags, 410
initialization, 410
JavaBeans components, 409
JSP template, 410
request processing, 411
running, 425
examples, 32
internationalizing, 206
J2EE Blueprints, 207
maintaining state across requests, 238
packaging, 196
running, 203
updating, 204
Web components, 6, 193
accessing databases from, 221
adding to WAR files, 198
applets, 6
concurrent access to shared resources, 220
connecting to resources, 353
development role, 13
enterprise bean references, 35

J2eeTutorial.book Page 491 Tuesday, March 5, 2002 11:14 AM

forwarding to other Web components, 236
including other Web resources, 234
invoking other Web resources, 234
JSP pages
See JSP pages, 193
mapping filters to, 232
packaging, 34
runtime environment, 194
scope objects, 219
servlets
See servlets
sharing information, 218
transactions, 221, 331
types, 6, 193
utility classes, 6
Web context, 237
Web containers, 10, 194
loading and initializing servlets, 216
Web resources, 196
Duke's Bank
protecting, 414
mapping filters to, 232–234
protecting, 337
unprotected, 340
work flows, 51

X

XML, 17