INDEX

Symbols

? (question mark), context-sensitive help, 70, 76

Numerics

100 Mbps Ethernet, 43
10Base2 Ethernet, 15
10Base5 Ethernet, 15
10BaseT Ethernet, 15
    connectivity recommendations in hierarchical model, 44
    router interfaces, 467
2500 series routers, 477
700 series routers, 469–470
    10BaseT Ethernet interface, 467
    commands, 465–468
    configuration, 466, 469–470
    configuring ISDN switches that interface with, 467
    ISDN interfaces, 468
    naming, 467
    profiles, 464–465
        creating, 468
        displaying configuration for, 466
        moving between, 466
    reloading with default configuration, 466
    service support, 463–464
    static routes, establishing, 468

A

AARP (AppleTalk Address Resolution Protocol), 440
access layer (hierarchical model for network design), 8
access lists
    applying to router interfaces, 305
    applying to multiple router interfaces, 303
    blocking FTP traffic from a specific subnet, 319–320
    blocking Telnet traffic from a specific subnet, 320–321
    blocking traffic from a specific host, 313
    blocking traffic from a specific subnet, 313–314
    blocking traffic from external networks, 311–312
    condition tests, 302–303, 305
    configuration
        commands for, 304–306
        guidelines, 322–324
    creating before applying to router interfaces, 304
    defaults, 304
    displaying contents of, 324
    extended, 300
        IP, 305, 317–321
        IPX, 305
    functionality of, 299
    guidelines for implementing, 303–304
    inbound, 300–301
    IP, 298
        displaying contents, 324
        extended, numbers for, 300
        extended, configuration, 317–321
    IPX, 350–353
        displaying contents, 360–361
        extended, 305, 352, 355
        linking to router interfaces, 353
        SAP filters, 352, 356–360
        standard, 351, 353–355
        test conditions, 350
        verifying, 360–361
    justification for, 298–300
    mechanics of, 300–302
    monitoring, 324–325
    named
        IP, 305, 321–322
        IPX, 305
    numbers
        for IP/IPX access lists, 305
        guidelines for using, 303
    outbound, 300–302, 312
    removing from router interfaces, 311
    standard, 300
        IP, 305, 310–314
        IPX, 305
    statements
        adding, 304
        deny, 302, 305
        implicit deny any, 303

matching, 302
numbering, 311
order, 302
organization for efficiency, 304
permit, 302, 304–305
traffic filtering capabilities, 304
verifying, 324–325
access-class command, 315–316, 325
access-group command, 305, 307, 355
access-list command, 304, 307, 310, 318, 325, 353, 355, 362
ACLs (Access Control Lists). *See* access lists
address mapping
Frame Relay connections, 414–418
Address Resolution Protocol. *See* ARP
address violation command, 176
addresses
AppleTalk, 438–439
dynamic assignment, 440–441
extended, 439–440
BIA, 20
dynamic MAC addresses (switch ports), 170
IP addresses, 237
assigning host names to, 238–239
assigning to router interfaces, 237
broadcast addresses, 231–232
calculating address space, 233
classes, 222–224
components, 25
configuration, 237–241
configuring for switches, 167
denying router interface access with access lists, 308
displaying for hosts, 240–241
dotted decimal format, 26
format, 221
Frame Relay VCs, mapping, 414
host addresses, 224–226
host number, 221
identifying, 233–235
mapping to MAC sublayer addresses with ARP, 218
network number, 221
network schemes, 221
permitting access to router interfaces with access lists, 308
subnet addresses, 226–227
subnet masks, 227–231
verifying for switches, 168
wildcard masking, 307–310
IPX addresses, 332–333
logical addresses, 24–26
MAC addresses, 19
in IPX addresses, 333
MAC address table storage on Catalyst 1900 series switch, 171
permanent MAC addresses (switch ports), 171–172
static MAC addresses (switch ports), 172–173
switches, learning, 146–148
addressing. *See also* addresses
700 series routers
10BaseT Ethernet interfaces, 467
ISDN interfaces, 468
end stations, 18
IP addressing (switches), 83
address-violation command, 174
administrative distance (routes), 256–259
advertisements (VTP), 191
all subnets broadcasts, 232
American Registry of Internetwork Numbers (ARIN), 222
AND operation (Boolean), 230
any keyword (access lists), 309
AppleTalk
addresses, 438–439
dynamic assignment, 440–441
extended, 439–440
client/server environment, 438
configuration, 443–453
discovery mode, 447–450
functionality, 438
protocol stack versus OSI reference model, 437–438
router global configuration parameters, displaying, 452–453
router interfaces, displaying information for, 451
routing, enabling, 444
routing table content displays, 451–452
services, 441–443
versions, 438

zone table information displays, 452
zones, 441–443
AppleTalk Address Resolution Protocol, 440
appletalk cable-range command, 445–447, 454
appletalk discovery command, 448, 454
appletalk protocol command, 444, 454
appletalk routing command, 444, 454
appletalk zone command, 445, 454
application layer (OSI reference model Layer 7), 11
ARIN (American Registry of Internetwork Numbers), 222
ARP (Address Resolution Protocol), 215, 218
ASICs (application-specific integrated circuits), 21
ATM (Asynchronous Transfer Mode), 373
AUI (attachment unit interface), 16
authentication
CHAP, 380–383
PAP, 379–383
Autoinstall utility, 131
autonomous systems, 256
AUX ports, 65

B

b command, 476
b flash command, 476
backbone layer, 9
backup IOS images, 137–139
Backward Explicit Congestion Notification, 414
balanced hybrid routing protocols, 276
bandwidth, 26, 55, 105
bandwidth command, 105, 420
banner motd command, 102
Basic Rate Interface. *See* BRI
BECN (Backward Explicit Congestion Notification), 414
BGP (Border Gateway Protocol), 249
BIA (burned-in-address), 20
blocking state (Spanning Tree), 160
Boolean operations, 230
boot field, 130, 476
Boot ROM mode (router initialization), 84
boot sequence (routers), 124–125, 128
boot system command, 127
boot system flash command, 127, 479
boot system rom command, 127
boot system tftp command, 127
booting router configuration register from Flash memory, 477, 479
bootstrap code (routers), 126–128
Border Gateway Protocol, see BGP
BPDU (Bridge Protocol Data Unit), 156–158
branch offices, 5
BRI (Basic Rate Interface), ISDN, 387
call processing, 391–392
components of, 390
enabling, 395–397
bridge IDs (Spanning Tree), 157
bridge loops, 150
Bridge Protocol Data Unit, 249
bridged/switched networks. *See also* VLANs
characteristics of, 22, 24
bridges, 30. *See also* devices, switches
criteria for selecting, 32, 34
filtering, 22
flooding, 22
forwarding tables, 22
operation at the data link layer, 21–24
source-route bridging, 22
translational bridging, 22
versus switches, 162
bridging
definition of, 145
disabling over 700 series router ISDN interfaces, 468
broadcasts. *See also* VLANs
addresses (IP), 231–232
domains, 16, 18
routers, 181
switches, 181
frames, 150
SAP broadcasts, 338
storms (frames), eliminating, 151–152
burned-in-address, 20

C

cabling
console ports, 64
crossover cable, 51–52
DCE, 372
DTE, 372
Ethernet, 45–46
LANs, 41
connection types, 46
Ethernet implementations, 44–45
Ethernet media/connector requirement considerations, 45
implementations, 43
requirements based on media, 52–53
UTP implementation, 47–52
rollover cables, 64
standards, 15–16
straight-through cable, 48–50
variety in a network environment, 52
WANs, 53, 55
call command, 470
carrier sense multiple access collision detection, 17
Catalyst switches. *See* switches
Category 5 wiring, 53
cd command, 466
CDP (Cisco Discovery Protocol), 113
disabling on a device, 116
displaying detailed CDP information about neighboring devices, 118–119
displaying general CDP information about neighboring devices, 116–117
displaying device CDP information, 115–116
functionality, 113–115
network device support, 114
packets, 116
preventing other devices from obtaining information, 116
re-enabling on a device, 116
startup, 114
cdp command, 120
cdp enable command, 116
CHAP (Challenge Handshake Authentication Protocol), 377, 380–383
CIR (committed information rate), Frame Relay, 414
circuit switching (WANs), 369
Cisco Discovery Protocol. *See* CDP
Class A IP addresses, 222–224
Class B IP addresses, 222–224
Class C IP addresses, 222–224
Class D IP addresses, 222–224
Class E IP addresses, 222–224
clear frame-relay-inarp command, 423
clear line command, 123
CLI (command-line interface), IOS, 67
client mode (VTP), 189–190
clock rate command, 105
collision domains, 16, 18
collisions, 16–18
command history buffer
routers, 93–94
switches, 77–78
command modes
IOS, 69–70
switches, changing between, 75
command scripts (router configuration), 88
command-line interface, 67
command-line mode (switch logon), 75
commands
abbreviating, 77, 92
access-class, 315–316, 325
access-group, 305, 307, 355
access-list, 304, 307, 310, 318, 325, 353, 355, 362
address-violation, 174, 176
appletalk cable-range, 445, 447, 454
appletalk discovery, 448, 454
appletalk protocol, 444, 454
appletalk routing, 444, 454
appletalk zone, 445, 454
b, 476
b flash, 476
bandwidth, 105, 420
banner motd, 102
boot system, 127
boot system flash, 127, 479
boot system rom, 127
boot system tftp, 127

call, 470
cd, 466
cdp, 120
cdp enable, 116
clear frame-relay-inarp, 423
clear line, 123
clock rate, 105
config-register, 129–130, 474
configure terminal, 100, 134, 474, 479
connect, 120
context-sensitive help, 70
copy flash tftp, 138
copy nvram tftp, 175, 177
copy running-config tftp, 134
copy running-configuration startup-configuration, 101, 133
copy running-configuration tftp, 133
copy startup-configuration running-configuration, 133
copy tftp, 176
copy tftp flash, 139–140
copy tftp nvram, 175
copy tftp running-config, 134
debug apple routing, 454
debug dialer, 406–407
debug frame-relay lmi, 424, 432
debug ip igrp events, 289, 294
debug ip igrp transactions, 288, 294
debug ip rip, 282, 294
debug ipx routing, 345
debug ipx routing activity, 348–349, 362
debug ipx sap activity, 345, 349–350, 362
debug isdn q391, 406
debug isdn q921, 406–407
debug isdn q931, 407
debug ppp authentication, 384
delete nvram, 176–177
delete vtp, 191, 195, 200
dialer idle-timeout, 406
dialer list, 406
dialer map, 403
dialer map id, 406
dialer-group, 402, 404, 406
dialer-list, 401
disconnect, 123
duplex, 169
enable, 474
enable password, 103
enable secret, 103, 482
encapsulation frame-relay, 431
encapsulation hdlc, 374, 384
encapsulation isl, 243, 245
encapsulation ppp, 381, 384
erase startup-configuration, 134
exec-timeout 0 0, 104
finding with context-sensitive help, 76
frame-relay inverse-arp, 431
frame-relay lmi-type, 431
frame-relay map, 421, 431
global commands (routers), 100
hostname, 381
initialize, 481
interface, 104, 200, 342
interface serial, 428, 432
ip access-group, 304–305, 311, 319, 325
ip access-list, 325
ip address, 167, 176, 237, 245
ip classless, 293–294
ip default-gateway, 168, 176, 237, 245
ip directed-broadcast, 232
ip domain-lookup, 240
ip host, 239, 245
ip name-server, 239, 245
ip netmask-format, 245
ip route, 252, 294, 401
ipx access-group, 353, 355, 362
ipx input-sap-filter, 362
ipx maximum-paths, 341
ipx network, 336, 341–342, 361
ipx output-sap-filter, 362
ipx routing, 332, 340, 361
isdn spid1, 397, 406
isdn spid2, 397, 406
isdn switch-type, 396
isdn switch-type basic, 406
line, 316
line console 0, 102
line vty, 325
line vty 0 4, 103
logging synchronous, 104
mac-address-table permanent, 171, 176
mac-address-table restricted static, 172, 176
major commands, 100
maximum-paths, 278

net boot, 127
network, 277, 279, 285, 294
no access-list, 311
no address-violation, 174
no appletalk discovery, 450
no cdp enable, 116
no cdp run, 116
no debug all, 294
no ip access-group, 311
no ip default-gateway, 168
no ip domain-lookup, 240, 245
no mac-address-table permanent, 171
no mac-address-table restricted static, 172
no port secure, 173
no shutdown, 107, 407, 482
options, displaying, 76
ping, 124, 405, 470
ping ipx, 345, 350
port secure, 173, 176
ppp authentication, 382
ppp authentication chap, 384
ppp authentication pap, 384
privileged EXEC mode,
    displaying, 91
    listing availability, 70
reboot, 470
recalling, 77, 93–95
reload, 474
resume, 123
router, 277, 294
router igrp, 285
router rip, 279
service password-encryption, 103, 381
set 1 spid, 467
set bridging off, 468
set default, 466
set ip address, 467–468
set ip netmask, 467–468
set ip route destination 0.0.0.0/0 gateway 0.0.0.0, 468
set ip routing on, 467–468
set switch, 467
set systemname, 467
set user, 468
show, displaying options for, 76
show access-lists, 324
show appletalk globals, 452–454
show appletalk interface, 454
show appletalk route, 451, 454
show appletalk zone, 452, 454
show cdp, 115–116
show cdp interface, 120
show cdp neighbors, 116–117
show cdp neighbors detail, 118–119, 334
show cdp traffic, 119
show config, 466
show dialer, 405, 407
show flash, 131, 137
show frame-relay lmi, 422, 432
show frame-relay map, 423, 432
show frame-relay pvc, 422–423, 432
show history, 94
show hosts, 240
show interface, 106, 169, 383–384, 421
show interfaces, 80–81, 107–110, 169, 176
show ip, 82, 168, 176
show ip access-lists, 324–325
show ip interface, 324–325
show ip protocols, 279, 281, 287, 294
show ip route, 280, 288, 294, 406–407
show ipx access-list, 360, 362
show ipx interface, 345–346, 360–361
show ipx route, 345–347, 362
show ipx servers, 345, 347–348
show ipx traffic, 345, 348
show isdn active, 405, 407
show isdn status, 406–407
show mac-address-table, 170, 172–173, 176
show mac-address-table security, 174
show run, 166
show running-config
show running-configuration, 79–80, 98–99, 132, 281
show sessions, 121
show spantree, 167, 199–200
show startup-configuration, 98–99, 132, 482
show trunk, 196, 200
show user, 122
show version, 78–79, 98, 128, 175–176, 473
show vlan, 197, 200
show vlan-membership, 167, 199–200
show vtp, 191, 195, 200
shutdown, 107, 406–407
telnet, 120, 405

term ip netmask-format, 238, 245
terminal editing, 96
terminal history size, 94
trace, 124
traffic-share, 286, 294
trunk, 196
upload, 466
user EXEC mode
displaying, 90
listing availability, 70
username, 381, 384
variance, 294
vlan, 197, 200
vlan-membership, 198
vtp, 195
vtp domain, 200
where (UNIX), 122
who (UNIX), 122
write, 101
write memory, 101
committed information rate, 414
condition testing (access lists), 302–305
config-register command, 129–130, 474
configuration, 469–470
access lists
commands for, 304–306
guidelines, 322–324
AppleTalk, 443–453
CHAP, 382–383
DDR over ISDN, 400–406
default routes, 254
dynamic routing, 276–277
extended IP access lists, 317–321
Frame Relay subinterfaces, 425, 428–431
Frame Relay multipoint subinterfaces, 430–431
Frame Relay point-to-point subinterfaces, 429–430
gateways for switches, 167
HDLC encapsulation in WANs, 374
IGRP, 285–286
inter-VLAN routing, 243
IP addresses, 167, 237–241
IPX routing, 339–344
named IP access lists, 321–322
PAP, 382–383
PPP encapsulation
in WANs, 379–383
verifying, 383–384
RIP, 279
routers
active, 132
backup, 132
CLI configuration method, 99–110
command script, 88
console passwords, 102
copying into RAM, 133
copying RAM configuration to TFTP server, 133
copying running configuration to NVRAM, 133
copying saved NVRAM configuration to RAM, 133
deleting NVRAM files, 134
displaying current, 99
displaying current configuration running in RAM, 132
displaying current configuration saved in NVRAM, 132
displaying saved configuration, 99
displaying system information, 98
downloading from TFTP server, 134
Frame Relay, 418–424
global parameters, 85
initial configuration, 84–89
initial protocol settings, 87
IPX, 334
interfaces, 104–110
loading, 131–132
loading parameters into RAM, 131
message-of-the-day banner, 101
modifying, 89–91
moving between routers/router components, 132
moving configuration/system files, 136
permissable access locations, 68–69
ports on modular cards, 60
remote terminal/console configuration method, 134
running, 131–132
saving to NVRAM, 101
setup mode, 84

system configuration, 85
uploading to TFTP server, 134
vty passwords, 103
Spanning Tree, displaying status of, 199–200
standard IP access lists, 310–314
static Frame Relay maps, 420–421
static routes, 252
subnet masks for switches, 167
switches, 165
CLI configuration method, 82–83
default, 68, 165–167
displaying active configuration files, 79–80
downloading from TFTP server, 175
global configuration mode, 82
interface configuration mode, 82
interfaces (duplex mode), 168–170
IP configuration, displaying current, 82
permissable access locations, 68–69
port security, 173–174
resetting to factory defaults, 176
trunk ports, 196–197
uploading to TFTP server, 175
trunks, 196–197
VLANs
default requirements, 194
guidelines, 194
overwriting, 192
prerequisite steps, 194
VTP, 195–197
configuration modes (switches), 167–168
configuration register (routers), 126
bit meanings, 475
boot field, 476
boot field settings, 130
booting from Flash memory, 477, 479
contents, setting, 474
default settings, changing, 129
displaying, 128, 473, 481
factory defaults, 473
listing setting for, 129
settings, changing, 473–479
values, 127
configuration revision number (switches), resetting, 191–192
configure terminal command, 100, 134, 474, 479
connect command, 120
connectionless protocols, 29, 207
connection-oriented protocols, 29, 207
connections (TCP), establishing, 211–213
connectivity
devices, verifying, 124
WAN options, 368–369
connectors
Ethernet specifications, ??–4545
jacks, 48
RJ-45 connector, 46, 48
wiring standards, 48
console connections (network devices), setup, 64–65
console error messages
routers, 92–93
switches, 77
console password (routers), configuring, 102
console ports (routers), 64
context-sensitive help (commands), 70
routers, 92, 94–96
switches, 76–77
controller configuration mode (routers), 100
convergence (Spanning Tree), 161–162
copy flash tftp command, 138
copy nvram tftp command, 175, 177
copy running-config tftp command, 134
copy running-configuration startup-configuration command, 101, 133
copy running-configuration tftp command, 133
copy startup-configuration running-configuration command, 133
copy tftp command, 176
copy tftp flash command, 139–140
copy tftp nvram command, 175
copy tftp running-config command, 134
core layer (hierarchical model for network design), 9
corporate networks. *See* internetworks, LANs, WANs
counting to infinity (routing loops), 266
CPE (customer premises equipment), ISDN, 370, 392–394
crossover cable, 51–52
CSMA/CD (carrier sense multiple access collision detection), 17
cut-through mode switching, 162

D

data circuit-terminating equipment, 57, 371-372
Data Delivery Protocol, 438
data encapsulation. *See* encapsulation
data link layer (OSI reference model Layer 2), 18, 437
  devices, 21–24, 30
  functionality of, 18–19
  functions of, 18–19
  LLC sublayer, 19–21
  MAC sublayer, 19–20
data terminal equipment, *See* DTE
data-link connection identifiers, *See* DLCIs
DB-60 connectors (routers), 371
DCE, (data circuit-terminating equipment), 57, 371–372
DDP (Datagram Delivery Protocol), 438
DDR (dial-on-demand routing), 299, 387
  identifying interesting traffic with access lists, 299
  ISDN
    characteristics of, 397–400
    configuration, 400–406
    connections, 398
    dialer information configuration for router interfaces, 402–403
    operation, 399–400
    specifying interesting traffic, 401–402
    troubleshooting, 406
    verifying configuration/operation, 405–406
  setup, 397
debug apple routing command, 454
debug dialer command, 406–407
debug frame-relay lmi command, 424, 432
debug ip igrp events command, 289, 294
debug ip igrp transactions command, 288, 294
debug ip rip command, 282, 294
debug ipx routing activity command, 345, 348–349, 362
debug ipx sap activity command, 345, 349–350, 362
debug isdn q921 command, 406–407
debug isdn q931 command, 406–407
debug ppp authentication command, 384
de-encapsulation, 14
default routes, configuration, 254
delay, 26
delete nvram command, 176–177
delete vtp command, 191, 195, 200
demarcation (WANs), 370
deny statement (access lists), 302, 305
designated port (Spanning Tree), 156
desktop layer, 8
devices. *See also* bridges, hubs, routers, switches
  accessing via console port, 458–461
  AUX ports, 65
  CDP, re-enabling, 116
  CDP information
    displaying, 115–116
    preventing other devices from obtaining, 116
  console connections, setup, 64–65
  criteria for selecting, 32, 34
  data link layer devices, 21–24, 30
  determining IP address components with subnet masks, 227–231
  figure icons for, xx
  HyperTerminal terminal emulation session
    components for enabling, 457
    creating, 458–461
    disconnecting, 461
    reconnecting, 461
  interfaces
    displaying configuration about, 120
    displaying status information about, 120
  IP addresses, 224
  ISL configuration, 186
  latency, 163
  neighboring
    communication between, 115
    displaying detailed CDP information about, 118–119
    displaying general CDP information about, 116–117
    displaying general information about, 115
  network connectivity, verifying, 124
  network layer devices, 31
  NT1 devices, 62
  physical layer devices, 30
  PPP connections, establishing, 378–379

remote (Telnet sessions), 120–123
routes, displaying, 124
Telnet sessions, ending, 123
traffic, displaying information about, 119
URL prefixes, 135
DHCP (Dynamic Host Configuration Protocol), 215, 219-220
dialer idle-timeout command, 406
dialer map command, 403
dialer map ip command, 406
dialer-group command, 402–406
dialer-list command, 401, 406
dial-on-demand routing, 299, 387
directed broadcasts, 232
disabling router interfaces, 107
disconnect command, 123
distance vector routing protocols
characteristics of, 260
routes, 261–263
distribution layer (hierarchical model for network design), 9
DLCIs (data-link connection identifiers), 414
DNS (Domain Name System), 239
Domain Name System, 239
domains
adding switches to, 195
broadcast, 16–18
broadcast domains, 179–181
collision, 16–18
segmentation by routers, 27
VTP domains, 188
dotted decimal notation (IP addresses), 26, 221
DTE (data terminal equipment), 57, 371–372
duplex command, 169
dynamic AppleTalk address assignment, 440–441
Dynamic Host Configuration Protocol (DHCP), 215, 219-220
dynamic MAC addresses (switch ports), 170
dynamic membership mode (VLANs), 184–185
dynamic routes, 251
dynamic routing
configuration, 276–277
protocols for, 254–276

E

EGP (Exterior Gateway Protocol), 256
EIGRP (Enhanced Interior Gateway Routing Protocol), 249, 258, 276
enable command, 474
enable password (routers), 86
enable password command, 103
enable secret command, 103, 482
enable secret password (routers), 86
encapsulation, 13–14
HDLC, configuration in WANs, 374
IPX packets, 334–337
ISLs, 187–188
Layer 2 (WANs), 372–374
PPP (WANs)
characteristics of, 375–379
configuration, 379–383
verifying configuration, 383–384
SAP encapsulation, 337
encapsulation frame-relay command, 431
encapsulation hdlc command, 374, 384
encapsulation isl command, 243, 245
encapsulation ppp command, 381, 384
encryption (MD5), 86
end stations
communication between at the transport layer, 29
physical addressing, 18
Enhanced Interior Gateway Routing Protocol, 249, 258, 276
enterprise services, 9
erase startup-configuration command, 134
error messages
routers, 92–93
switches, 77
Ethernet
100 Mbps Ethernet, 43
10Base2 Ethernet, 15
10Base5 Ethernet, 15
10BaseT Ethernet, 15
connectivity recommendations in hierarchical model, 44
router interfaces, 467
cabling, connector types, 46
connector/cabling specifications, 45–46
considerations for LAN cabling, 44–45

Ethernet (DIX), 43
Fast Ethernet, 43–45
full-duplex, 163–165
Gigabit Ethernet, 43
half-duplex, 163–165
IEEE 802.3, 43
interfaces (routers), media type settings, 106
media, considerations for LAN cabling, 45
switches, 145
upgrading, 44
Ethernet_802.2 encapsulation type (IPX packet encapsulation), 335
Ethernet_802.3 encapsulation type (IPX packet encapsulation), 335
Ethernet_II encapsulation type (IPX packet encapsulation), 335
Ethernet_SNAP encapsulation type (IPX packet encapsulation), 335
EXEC mode (switch logon), 75
EXEC sessions (routers), preventing timeouts, 104
exec-timeout 0 0 command, 104
extended access lists, 300
extended AppleTalk addressing, 439–440
extended IP access lists, 306
configuration, 317–321
numbers for, 305
extended IPX access lists, 305, 352, 355
Exterior Gateway Protocols, 256
external networks (traffic), blocking with access lists, 311–312

F

Fast Ethernet, 43
benefits in a campus LANs, 44–45
connectivity recommendations in hierarchical model, 44
FastHub hub series, 34
FCS (frame check sequence), 12
FECN (Forward Explicit Congestion Notification), 414
filtering
bridging, 22
frames to switch ports, 148–150
packets with access lists, 298
finding commands with context-sensitive help, 76
fixed ports (routers), 58
Flash memory, 126, 131
Flooded broadcasts, 232
flooding
bridging, 22
frames, 146
flow control
Frame Relay, 414
TCP, 213–214
UDP, 213–214
forward delay (Spanning Tree), 160
Forward Delay timer (Spanning Tree), 160
Forward Explicit Congestion Notification, 414
forwarding
frames to switch ports, 148–150
VLAN information, 183
forwarding state (Spanning Tree), 160
forwarding tables, 22
fragment-free mode switching, 163
frame check sequence, 12
Frame Relay, 373
BECN, 414
CIR, 414
Cisco router serial connection support, 412
components, 412–414
configuration on routers, 418–424
connections
address mapping, 414–418
displaying map entry information, 423
displaying statistics, 422–423
displaying status/information, 421–422
LMI signaling, 414–418
troubleshooting, 424
verifying, 424
definition of, 411–412
DLCIs, 414
DTE, 411
FECN, 414
flow control, 414
Inverse ARP, 414
LMI, 414–415
types, 416
traffic, displaying statistics, 422
local access rate, 413
maps, clearing, 423

multipoint subinterfaces, 428–431
NBMA reachability, 426–429
OSI functions, 412
point-to-point subinterfaces, 428
configuration, 429–430
PVCs, 413
static mapping, configuration, 420–421
subinterfaces, configuration, 425, 428–431
SVCs, 413
terminology, 412–414
traffic, displaying statistics, 422–423
VCs, 411, 413
design considerations, 427
IP addresses, 414
states, 416
frame-relay inverse-arp command, 431
frame-relay lmi-type command, 431
frame-relay map command, 421, 431
frames, 13
broadcast, 150
broadcast storms, eliminating, 151–152
database instability, eliminating, 153–154
duplicate nonbroadcast transmissions, eliminating, 152–153
filtering, 148–150
flooding, 146
forwarding, 148–150
HDLC, format, 374
LLC sublayer, 20–21
MAC sublayer, 19–20
multicast, 150
switching, 162–163
FTP traffic, blocking from a specific subnet with access lists, 319–320
full-duplex transmission (switches), 163–165
full-mesh topology (Frame Relay), 426

G-H

gateways (switches)
assigning defaults, 237
default configuration, 167
verifying, 168
Get Nearest Server. *See* GNS
Gigabit Ethernet, 43
global commands (routers), 100
global configuration mode
routers, 99
switches, 82, 167
global services, 9
GNS (Get Nearest Server), 331
SAP queries, 339

half-duplex transmission (switches), 163–165
HDLC (High-Level Data Link Control), 55, 373
encapsulation, configuration in WANs, 374
frames, format, 374
hdlc keyword, 336
headers, 12, 21
Hello Time timer (Spanning Tree), 160
help (context-sensitive help)
routers, 92, 94–96
switches, 76–77
hierarchical model (network subdivision), 7, 10, 44
High-Level Data Link Control. *See* HDLC
holddown timers
pairing with triggered updates for route maintenance, 271–274
route maintenance with, 269–270
hops, 26
host addresses (IP), 224–226
host names
assigning to IP addresses, 238–239
routers, assigning, 381
workstations, displaying, 240–241
host name-to-address mapping, 238–239
hostname command, 381
hosts
determining number of in a given network, 225
IPX, testing reachability, 350
traffic, blocking with access lists, 313
hubs, 30. *See also* devices
Cisco product line, 34–35
criteria for selecting, 32, 34–35
FastHub series, 34
functionality of, 17
Micro Hub series, 34
typical topology, 17
hybrid routing protocols, 274–276

HyperTerminal terminal emulation sessions, 457
components for enabling, 457
creating, 458–461
disconnecting, 461
reconnecting, 461

I

ICMP (Internet Control Message Protocol), 215, 217–218
IEEE 802.3 Ethernet, 43
IFS (IOS File System), 135
IGP (Interior Gateway Protocols), 256
IGRP (Interior Gateway Routing Protocol), 249
administrative distance default, 258
characteristics of, 282
configuration, 285–286
IP routing tables, displaying, 288
load balancing/sharing, 286
metrics, 283–284
routes, assigning to unknown subnet of a directly attached network, 293
routing information
displaying summaries for, 289–290
verifying, 287–288
routing process, 285–286
routing transaction information displaying, 288–289
routing updates, 290–293
unequal-cost load balancing, 284–285
images (IOS)
backup, 137–139
displaying information about, 137
loading from Flash into RAM, 130
loading from network server, 139–140
specifying source to load, 127
implicit deny any statement (access lists), 303
implicit deny statement (access lists), 302
inbound access lists, 300–301
initial sequence numbers (ISNs), 211
initialization (routers)
Boot ROM mode, 84
setup mode, 84
user mode, 84
initialize command, 481
Integrated Services Digital Network. *See* ISDN
interface command, 104, 200, 342
interface configuration mode, 167
routers, 100
switches, 82
interface serial command, 428, 432
interfaces
routers, 26, 126
access lists, activating, 304
access lists, removing, 311
AppleTalk, specifying a network number range, 445
AppleTalk information, displaying, 451
AppleTalk routing, configuring, 443–453
assigning to AppleTalk zones, 445
bandwidth settings, 105
clock rate settings, 105
configuration, 104–110
configuring a description, 102
configuring dialer information for DDR over ISDN BRI, 402–403
disabling, 107
displaying configuration information about, 120
displaying statistics for, 107–110
displaying status of, 120
IP addresses, assigning, 237
IPX encapsulation types, 336
IPX encapsulation types, selecting, 341–343
IPX network numbers, assigning, 341–343
IPX routing, enabling, 341–343
IPX, displaying status/parameters, 345–346
ISDN, 394
linking IPX access lists to, 353
media type settings, 106
re-enabling, 107
serial
connectors, 370
IPX node addresses, 340
slot/port adapter schemes, 105
slot/port number schemes, 105
subinterfaces, 242
traffic, displaying information about, 119
type/number schemes, 104
verifying configuration, 106

switches
displaying configuration information about, 120
displaying statistics for, 80–81
displaying status of, 120
duplex mode configuration, 168–170
Interior Gateway Protocols, 256
Interior Gateway Routing Protocol. *See* IGRP
Internal profile (700 series routers), 465
Internet Control Message Protocol, 215, 217-218
Internet Protocol. *See* IP
internetwork operating system. *See* IOS
Internetwork Packet Exchange. *See* IPX
internetworks
organization by user type, 5–6
remote access connections, 5–6
subdividing based on business/user needs, 6–10
traffic patterns, 7–8
Inter-Switch Links. *See* ISLs
Inverse ARP, 414–415, 418
inverted subnet mask, see wildcard masking
IOS (internetwork operating system), 67
CLI, accessing, 67
command modes, 69–70
images
backup, 137–139
displaying information about, 137
loading from Flash into RAM, 130
loading from network server, 139–140
specifying source to load, 127
network service support, 67
privileged EXEC mode, 89
switches, displaying information about, 174–175
user EXEC mode, 89–90
IOS File System, 135
IP (Internet Protocol), 215. *See also* IP addresses
access lists, 298
activing on router interfaces, 304
displaying contents, 324
extended, 300, 306, 317–321
named, configuration, 321–322
numbers for, 305
standard, 300, 306
applying to vty ports, 315
configuration, 310–314
header format, 215–217
packets, access list testing, 306
ip access-group command, 304–305, 311, 319, 325
ip access-list command, 325
ip address command, 167, 176, 237, 245
IP addresses
assigning to switches, 237
assigning host names to, 238–239
assigning to router interfaces, 237
broadcast addresses, 231–232
calculating address space, 233
classes, 222–224
components, 25
configuration, 237–241
denying router interface access with access lists, 308
dotted decimal format, 26
format, 221
Frame Relay VCs, mapping, 414
host addresses, 224–226
host number, 221
identifying, 233–235
mapping to MAC sublayer addresses with ARP, 218
network number, 221
network schemes, 221
permitting access to router interfaces with access lists, 308
subnet addresses, 226–227
subnet masks, 227–231
subnets, filtering traffic from with access lists, 309–310
switches, 83
configuration, 167
verifying, 168
wildcard masking, 307–310
workstations
discovering with RARP, 219–220
displaying, 240–241
ip classless command, 293–294
IP configuration mode (switch logon), 75
ip default-gateway command, 168, 176, 237, 245
ip directed-broadcast command, 232
ip domain-lookup command, 240
ip host command, 239, 245
ip name-server command, 239, 245
ip netmask-format command, 245

IP RIP routing
700 series router 10BaseT Ethernet interfaces, enabling, 467
700 series router ISDN interfaces, enabling, 468
ip route command, 252, 294, 401
IPX
access lists, 350–353
displaying, 360–361
extended, 352, 355
linking to router interfaces, 353
SAP filters, 352, 356–360
standard, 351, 353–355
test conditions, 350
verifying, 360–361
addresses, 332–333
characteristics of, 331
configuration on Cisco routers, 334
hosts, testing reachability, 350
networks
addresses in, 332
assigning multiple logical networks to the same physical wire, 341
Cisco router features, 329–330
connectivity, testing, 350
load sharing, enabling, 341
nondefault encapsulation types, specifying, 336
overhead, 352
packets, encapsulation, 334–337
protocol stack, 330–332
RIP, 331, 337
RIP updates, displaying information about, 348–349
router interfaces, displaying status/parameters, 345–346
routing
configuration, 339–344
enabling, 340
monitoring, 345–350
verifying, 345–350
routing tables, displaying contents, 346–347
SAP updates, displaying information about, 349–350
servers, displaying information for, 347–348
traffic, displaying volume/type information, 348
ipx access-group command, 353, 355, 362
ipx input-sap-filter command, 362
ipx maximum-paths command, 341
ipx network command, 336, 341–342, 361
ipx output-sap-filter command, 362
ipx routing command, 332, 340, 361
IPX/SPX (Internet Packet Exchange/Sequenced Packet Exchange), 330–332
IPX-router configuration mode (routers), 100
ISDN (Integrated Services Digital Network), 387
benefits of, 387–388
BRI, 387
call processing, 391–392
components of, 390
connections, cabling routers for, 62–63
enabling, 395–397
DDR
characteristics of, 397–400
configuration, 400–406
connections, 398
dialer information configuration for router interfaces, 402–403
operation, 399–400
setup, 397
specifying interesting traffic, 401–402
troubleshooting, 406
verifying configuration/operation, 405–406
equipment, 392–394
port types, 63
PRI, 390
protocols, 389
reference points, 392–394
router interfaces, 394
addressing, 468
disabling bridging over, 468
IP RIP routing, enabling, 468
subnet masks, specifying, 468
services, components, 390–397
SPIDs, 395, 397
standards, 388
switches, 389
configuring for use with 700 series routers, 467
types, 395
isdn spid1 command, 397, 406
isdn spid2 command, 397, 406
isdn switch-type basic command, 406

isdn switch-type command, 396
ISLs (Inter-Switch Links), 185–188
encapsulation, 187–188
router support, 242
tagging, 186–187
ISNs (initial sequence numbers), 211

J-K

jacks (connectors), 48

keywords
any (access lists), 309
hdlc, 336
novell-ether, 335–336
snap, 336

L

LAN profile (700 series routers), 465, 467
LAPB (Link Access Procedure, Balanced), 373
latency (switches), 163
Layer 1. *See* physical layer
Layer 2 encapsulation (WANs), 372–374
Layer 2. *See* data link layer
Layer 3. *See* network layer
Layer 4. *See* transport layer
Layer 5. *See* session layer
Layer 6. *See* presentation layer
Layer 7. *See* application layer
LCP (Link Control Protocol), PPP sublayer, 376–378
leaf node, 251
learning state (Spanning Tree), 160
leased lines (WANs), 368
LEDs (light-emitting diodes), Catalyst 1900 series switches, 70–74
line command, 316
line configuration mode (routers), 100
line console 0 command, 102
line vty 0 4 command, 103
line vty command, 325
link-state routing protocols, 274–276
listening state (Spanning Tree), 160
LLC sublayer (Logical Link Control), data link layer, 19
frames, 20–21
header components, 21
LMI (Local Management Interface), Frame Relay, 414–416
LMI signaling (Frame Relay connections), 414–418
load balancing/sharing
IGRP, 286
IPX networks, 341
RIP, 278
local access rate (Frame Relay), 413
local loop (WANs), 370
Local Management Interface, 414–418
logging synchronous command, 104
logical addresses, 24–26
logical AND operation, 230
logon (switches)
after setup, 74–75
EXEC mode, 75
loop avoidance (switches), 150–155
loops. *See also* routing loops
bridge loops, 150
multiple in switched networks, 154
switched networks, eliminating with Spanning Tree, 155–161

M

MAC (Media Access Control), 12
MAC addresses, 19
dynamic MAC addresses (switch ports), 170
in IPX addressses, 333
MAC address table storage on Catalyst 1900 series switch, 171
permanent MAC addresses (switch ports), 171–172
static MAC addresses (switch ports), 172–173
switches, learning, 146–148
MAC sublayer (data link layer), 19–20
mac-address-table permanent command, 171, 176

mac-address-table restricted static command, 172, 176
major commands, 100
Max Age timer (Spanning Tree), 160
maximum transmission units, 15
maximum-paths command, 278
MD5 (Message Digest 5) encryption, 86
Media Access Control, 12
memory
    Flash, 126, 131
    NVRAM, 126
    RAM, 125
    ROM, 125
    routers, displaying information about, 137
Menu Console Logon Screen (switches), 74
Menu mode (switch logon), 75
message-of-the-day banner (routers), configuration, 101
metrics
    IGRP networks, 283–284
    networks, 26
Micro Hub hub series, 34
mobile user connections, 6
modular serial ports (routers), 58
MTUs (maximum transmission units), 15
multicast addresses, 222-224
multicast frames, 150
multipoint subinterfaces (Frame Relay), 428–431

N

Name Binding Protocol, 438
name servers (IP networks), defining, 239–240
named IP access lists
    configuration, 321–322
    numbers for, 305
named IPX access lists, 305
naming
    700 series routers, 467
    routers, 86, 101
    switches, 83
NBP (Name Binding Protocol), 438
NCP (NetWare Core Protocol), 331, 376–378
neighboring devices
    communication between, 115
    displaying detailed CDP information about, 118–119
    displaying general CDP information about, 116–117
    displaying general information about, 115
net boot command, 127
NetWare, features of, 331–332
NetWare Core Protocol, 331, 376–378
NetWare Link Services Protocol, 331
network command, 277, 279, 285, 294
network layer (OSI reference model Layer 3), 24
    devices, 31
    functions of, 24
    router operations, 26–28
network layer addresses, 24–26
network numbers (IPX), 333–334
networks
    autonomous systems, 256
    bridged/switched, characteristics of, 22–24
    broadcasts, 231–232
    communication across, 12–14
    connections, figure icons for, xxi
    domains
        broadcast domains, 16, 18
        collision domains, 16, 18
    external, blocking traffic from with access lists, 311–312
    figure icons for, xxi
    hierarchical model for subdividing, 7, 10
    hosts, determining number of, 225
    IPX networks
        addresses in, 332
        assigning multiple logical networks to the same physical wire, 341
        Cisco router features in, 329–330
        connectivity, testing, 350
        load sharing, enabling, 341
        nondefault encapsulation types, specifying, 336
        overhead, 352
    metrics, 26
    name servers, defining, 239–240
    segmenting with subnet addresses, 226–227
    segmenting with subnet masks, 234
    stub networks, 251

subnet masks, format, specifying, 238
subnets
planning, 235–236
traffic, blocking with access lists, 313–314
switched networks
multiple loops, 154
redundancy in, 150
toll networks (WANs), 370
traffic. *See also* internetworks, WANs
filtering, *See* access lists
identifying interesting traffic with access lists, 299
separating into queues with access lists, 299
user connections at the access layer, 8
NICs (network interface cards), Novell file servers, 333
NLSP (NetWare Link Services Protocol), 331
no access-list command, 311
no address-violation command, 174
no appletalk discovery command, 450
no cdp enable command, 116
no cdp run command, 116
no debug all command, 294
no ip access-group command, 311
no ip default-gateway command, 168
no ip domain-lookup command, 240, 245
no mac-address-table permanent command, 171
no mac-address-table restricted static command, 172
no port secure command, 173
no shutdown command, 107, 407, 482
nonvolatile random-access memory. *See* NVRAM
Novell file servers, 333
Novell Internetwork Packet Exchange. *See* IPX
novell-ether keyword, 335–336
NT1 (Network Termination 1), ISDN, 392
NT1 devices, 62
NT2 (Network Termination 2), ISDN, 392
numbering SPIDs, 467
NVRAM (nonvolatile random-access memory), 84, 126

O

octets, 25, 221
ODI (Open Data-Link Interface), 331
Organizationally Unique Identifier, see OUI
OSI (Open Systems Interface) reference model, 10–12
advantages of, 10
application layer, 11
communication between layers, 12–14
data link layer, 18
functions of, 10
lower layers, 11–12
network layer, 24
physical layer, 14–18
presentation layer, 11
session layer, 11
transport layer, 28
upper layers, 10–11
OSPF (Open Shortest Path First), 249, 258, 275
OUI (Organizationally Unique Identifier), 20
outbound access lists, 300–312

P

packet switching (WANs), 369–372
packets, 13
CDP, 116
denying from router interfaces, 298
filtering with access lists, 298
IP, access list testing, 306
IPX
displaying volume/type information, 348
encapsulation, 334–337
permitting to router interfaces, 298
routing. required information for, 250
VLAN information, forwarding, 183
PAP (Password Authentication Protocol), 377–383
partial-mesh topology (Frame Relay), 426
passwords (routers)
changing, 482
defining, 381
disabling, 103
enable, 86
enable secret, 86
recovering, 479–485

path cost (Spanning Tree), 158–159
PCs, serial communications ports, 459
PDUs (protocol data units), 12
peer layers, 13
permanent MAC addresses (switch ports), 171–172
permanent virtual circuit, 413
permit statement (access lists), 302, 304–305
physical layer (OSI reference model Layer 1), 14, 17–18, 437
    devices, 30
    functions of, 14–15
    wiring standards, 15–16
ping command, 124, 405, 470
ping ipx command, 345, 350
Point-to-Point Protocol. *See* PPP
point-to-point subinterfaces (Frame Relay), 428–430
poison reverse (routing loop prevention), 269
port numbers, 29, 209–211
port secure command, 173, 176
ports
    ISDN port types, 63
    PCs, 459
    routers
        console ports, 64
        vty ports, filtering Telnet traffic, 298
    switches
        address violations, 174
        assigning to VLANs, 198–199
        designated ports, 156
        displaying VLAN assignments for, 199
        dynamic MAC addresses, 170
        MAC address table, displaying, 170
        permanent MAC addresses, 171–172
        port states (Spanning Tree), 157–158
        root ports, 156
        security configuration, 173–174
        static MAC addresses, 172–173
        trunk line configuration, 196–197
        trunk ports, 184
        VLAN assignments, 181
        VLAN membership, 194
        VLAN support, 187
POST (power-on self test), 68
    result displays, 74
    router booting sequence, 125
    routers, 84
    switch port LED associations, 73
PPP (Point-to-Point Protocol), 55, 373
    benefits of, 377
    connections, establishing, 378–379
    encapsulation
        characteristics of, 375–379
        compatible interfaces, 375
        configuration in WANs, 379–383
        verifying configuration in WANs, 383–384
    LCP sublayer, 376–378
    NCP sublayer, 376–378
    services, 376
ppp authentication chap command, 384
ppp authentication command, 382
ppp authentication pap command, 384
presentation layer (OSI reference model Layer 6), 11
PRI (Primary Rate Interface), ISDN
        components of, 390
privileged EXEC mode (IOS), 69
    changing to, 70
    commands
        displaying, 91
        listing availability, 70
    restricting access to, 103
profiles (700 series routers), 464–465, 468
protocol data units, 12
protocol stacks, 12
protocols
    AARP, 440
    AppleTalk, 438
    ARP, 215
    BGP, 249
    CDP, 113–120
    connectionless, 29, 207
    connection-oriented, 29, 207
    EIGRP, 249
    HDLC, 373
    ICMP, 215
    IGRP, 249
    initial router settings, 87
    IP, 215
    IPX, 330–332
    IPX RIP, 337
    ISDN, 389

OSPF, 249
PPP, 373
RARP, 215
RIP, 249
SAP, 337–339
Spanning-Tree Protocol, 155
transport layer protocols, 28
VTP, 188
pruning (VTP), 192–193
PVCs (permanent virtual circuits), 413

R

R reference point (ISDN networks), 393
RAM (random-access memory), 125
RARP (Reverse Address Resolution Protocol), 215, 219–220
read-only memory, 126
reboot command, 470
recovering router passwords, 479–485
redundancy (switched networks), 150
reference points (ISDN), 392–394
reload command, 474
reloading 700 series routers with default configuration, 466
remote access connections
branch offices, 5
mobile users, 6
telecommuters, 5
remote devices (Telnet sessions)
displaying, 121–122
ending, 123
establishing, 120–121
re-establishing, 122
suspending, 122
verifying, 121–122
resume command, 123
Reverse Address Resolution Protocol (RARP), 215, 219–220
RIP (Routing Information Protocol), 249
administrative distance default, 258
characteristics of, 278
configuration, 279
IP routing table information, displaying, 280–281
IPX, 331, 337
load balancing,enabling, 278
routing information, verifying, 279–280
routing updates, displaying, 282
selecting as a routing protocol, 279
RIP-1 (RIP version 1), 278
RIP-2 (RIP version 2), 278
RIT (Route Information Table), IPX, 333
RJ-45 connectors, 45–46, 48
rollover cables, 64
ROM (read-only memory), 126
ROM microcode (routers), 126–131
ROM monitor mode (routers), 129
root bridge (Spanning Tree), electing, 156–157
root port (Spanning Tree), 156
Route Information Table, 333
route maps, 299
route poisoning, 268–269
routed protocols versus routing protocols, 255
router command, 277, 294
router configuration mode, 100
router igrp command, 285
router rip command, 279
routers, 31
2500 series, default boot filenames, 477
700 series
addressing 10BaseT Ethernet interface for, 467
commands, 465–468
configuration, 469–470
configuring ISDN switches that interface with, 467
displaying configuration for, 466
displaying profile configuration, 466
enabling IP RIP routing for 10BaseT Ethernet interfacesr, 467
ISDN interfaces, disabling bridging, 468
ISDN interfacs, enabling IP RIP routing for, 468
ISDN interfaces, IP addressing, 468
ISDN interfaces, specifying subnet mask for, 468
moving between profiles, 466
naming, 467
profiles, 464–465, 468
reloading with default configuration, 466

service support, 463–464
static routes, establishing, 468
subnet masks, specifying for 10BaseT Ethernet interface for, 467
AppleTalk global configuration parameters, displaying, 452–453
boot sequence, 128
booting sequence, 124–125
bootstrap code, 125–128
cabling for WAN ISDN BRI connections, 62–63
cabling for WAN serial connections, 57–62
Cisco product line, 36, 38
command history buffer, 93–94
configuration
active, 132
backup, 132
CHAP, 382–383
command script, 88
copying into RAM, 133
copying RAM configuration to TFTP server, 133
copying running configuration to NVRAM, 133
copying saved NVRAM configuration to RAM, 133
deleting NVRAM files, 134
displaying current, 99
displaying current configuration running in RAM, 132
displaying current configuration saved in NVRAM, 132
displaying saved configuration, 99
displaying system information, 98
downloading from TFTP server, 134
Frame Relay, 418–424
from CLI, 99–110
from remote terminal/console, 134
HDLC encapsulation, 374
initial configuration, 84–89
initial global parameters, 85
initial protocol configurations, 87
IPX, 334
loading, 131–132
loading parameters into RAM, 131
modifying, 89–91
moving between routers/router components, 132
moving configuration/system files, 136
PAP, 382–383
permissable access locations, 68–69
running, 131–132
saving to NVRAM, 101
setup mode, 84
system configuration dialog, 85
uploading to TFTP server, 134
configuration register, 126
bit meanings, 475
boot field, 476
boot field settings, 130
booting from Flash memory, 477–479
contents, setting, 474
default settings, changing, 129
displaying, 128, 473, 481
factory defaults, 473
listing setting for, 129
settings, changing, 473–479
values, 127
console error messages, 92–93
console input, redisplaying interrupted, 104
console password, configuring, 102
context-sensitive help, 92, 94–96
controller configuration mode, 100
criteria for selecting, 32–38
DB-60 connectors, 371
enhanced editing mode (terminal editing), 96–98
EXEC sessions, preventing timeouts, 104
fixed ports, 58
Frame Relay subinterfaces, configuration, 428
functions of, 27–28
global configuration mode, 99
host names, assigning, 381
IFS, 135
IGRP transaction information, displaying, 288–289
initialization
Boot ROM mode, 84
setup mode, 84
user mode, 84

initializing, 481
interface configuration mode, 100
interfaces, 26, 126
  access lists, activating, 304
  access lists, removing, 311
  AppleTalk information, displaying, 451
  AppleTalk routing, configuring, 443–453
  assigning IP addresses to, 237
  assigning to AppleTalk zones, 445
  bandwidth settings, 105
  clock rate settings, 105
  configuration, 104–110
  configuring a description, 102
  configuring dialer information for DDR over ISDN BRI, 402–403
  disabling, 107
  displaying configuration information about, 120
  displaying statistics for, 107–110
  displaying status of, 120
  IPX encapsulation types, 336, 341–343
  IPX network numbers, assigning, 341–343
  IPX routing, enabling, 341–343
  IPX, displaying status/parameters, 345–346
  ISDN, 394
  linking IPX access lists to, 353
  media type settings, 106
  re-enabling, 107
  serial
    connectors, 370
    IPX node addresses, 340
  slot/port adapter schemes, 105
  slot/port number schemes, 105
  specifying a network number range in AppleTalk, 445
  subinterfaces, 242
  traffic, displaying information about, 119
  type/number schemes, 104
  verifying configuration, 106
inter-VLAN routing, 241–244
IPX networks, 329–330
IPX-router configuration mode, 100
ISL configuration, 186
ISL trunking support, 242
line configuration mode, 100
memory, displaying information about, 137
  message-of-the-day banner, configuration, 101
  modular serial ports, 58
  multiple broadcast domains, 181
  naming, 86, 101
  neighboring devices, displaying CDP information about, 116–117
  operation at the network layer, 26–28
  passwords
    changing, 482
    defining, 381
    disabling, 103
    enable, 86
    enable secret, 86
    recovering, 479–485
  ports
    configuration on modular cards, 60
    console ports, 64
  POST, 84
  required information for routing packets, 250
  ROM microcode, 126–131
  ROM monitor mode, 129
  router configuration mode, 100
  RTMP routine output, displaying, 453
  seed routers (AppleTalk), 447–450
  setup, 68
  startup, 68, 83–84
  static maps (Frame Relay),configuration, 4, 20–421
  subinterface configuration mode, 100
  subnet addressing, 228
  usernames, defining, 381
  vty interfaces, controlling access to with access lists, 314–316
  vty passwords, configuring, 103
  vty ports, filtering Telnet traffic, 298
  WANs, routing across, 244
routes
  administrative distance, 256–259
  default, configuration, 254
  devices, displaying, 124
  discovering with distance vector routing protocols, 261–263
  dynamic, 251
    configuration, 276–277
    routing protocols for, 254–276
  IGRP, assigning to unknown subnet of a directly attached network, 293

load sharing in IGRP, 286
maintenance
with both holddown timers and triggered updates, 271–274
with distance vector routing protocols, 261–263
with holddown timers, 269–270
with triggered updates, 270–271
multiple path support in IGRP, 284–285
selecting with distance vector routing protocols, 261–263
static, 251
configuration, 252
defining for DDR over ISDN BRI, 400–401
enabling, 251–254
establishing for 700 series routers, 468
routing
IGRP process, 285–286
IP RIP routing
enabling for 700 series router 10BaseT Ethernet interfaces, 467
enabling for 700 series router ISDN interfaces, 468
IPX
configuration, 339–344
enabling, 340
monitoring, 345–350
RIP updates, displaying information about, 348–349
SAP updates, displaying information about, 349–350
verifying, 345–350
packets, required information for, 250
process overview, 249–251
Routing Information Protocol. *See* RIP
routing loops
causes, 263–266
troubleshooting
with maximum metric settings, 266–267
with route poisoning, 268–269
with split horizon, 267–268
routing protocols. *See also* distance vector routing protocols, link-state routing protocols, hybrid routing protocols
characteristics of, 255
classes, 259
EGP, 256
IGP, 256
versus routed protocols, 255
Routing Table Maintenance Protocol, 438
routing tables, 250
components, 26
displaying for RIP networks, 280–281
IGRP networks, displaying, 288
IPX, displaying contents of, 346–347
populating, 251
routing updates
IGRP, 290–293
RIP, displaying, 282
RPS LED (Catalyst 1900 series switch), 71
RTMP (Routing Table Maintenance Protocol), 438

S

S reference point (ISDN networks), 393
SAP (Service Advertisement Protocol), 331, 337–339
broadcasts, 338
encapsulation, 337
filters (IPX access lists), 305, 352, 356–360
LLC frame type, 20
services, enabling, 340
types, 338
security
switch ports, configuration, 173–174
VLANs, 179
seed routers (AppleTalk), 447–450
segments, 13
Sequenced Packet Exchange, 331
serial communications ports (PCs), 459
serial connections (WANs), 55–62
serial interfaces (routers)
connectors, 370
IPX node addresses, 340
Serial Line Internet Protocol, 373
serial lines (WANs), standards, 370–372
server mode (VTP), 189–190
servers
IPX, displaying information for, 347–348
Novell file servers, NICs, 333

TFTP
downloading router configuration from, 134
downloading configuration files to switches, 175
uploading router configuration to, 134
uploading switch running configuration, 175
service access point identifier, 19
Service Advertisement Protocol. *See* SAP
Service Information Table, 333
service password-encryption command, 103, 381
service provider IDs. *See* SPIDs
services
AppleTalk, 441–443
SAP, enabling, 340
session layer (OSI reference model Layer 5), 11
set 1 spid command, 467
set bridging off command, 468
set default command, 466
set ip address command, 467–468
set ip netmask command, 467–468
set ip route destination 0.0.0.0/0 gateway 0.0.0.0 command, 468
set ip routing on command, 467–468
set switch command, 467
set systemname command, 467
set user command, 468
setup, routers, 68
setup mode (router initialization), 84
Setup utility, 132
show access-lists command, 324
show appletalk globals command, 452, 454
show appletalk interface command, 454
show appletalk route command, 451, 454
show appletalk zone command, 452, 454
show cdp command, 115–116
show cdp interface command, 120
show cdp neighbors command, 116–117
show cdp neighbors detail command, 118–119, 334
show cdp traffic command, 119
show command, displaying options for, 76
show config command, 466
show dialer command, 405, 407
show flash command, 131, 137
show frame-relay lmi command, 422, 432
show frame-relay map command, 423, 432
show frame-relay pvc command, 422–423, 432
show history command, 94
show hosts command, 240
show interface command, 106, 169, 383–384, 421
show interfaces command, 80–81, 107–110, 169, 176
show ip access-lists command, 324–325
show ip command, 82, 168, 176
show ip interface command, 324–325
show ip protocols command, 279, 281, 287, 294
show ip route command, 280, 288, 294, 406–407
show ipx access-list command, 360, 362
show ipx interface command, 345–346, 360–361
show ipx route command, 345–347, 362
show ipx servers command, 345, 347–348
show ipx traffic command, 345, 348
show isdn active command, 405, 407
show isdn status command, 406–407
show mac-address-table command, 170–173, 176
show mac-address-table security command, 174
show run command, 166
show running-configuration command, 79–80, 98–99, 132, 281
show sessions command, 121
show spantree command, 167, 199–200
show startup-configuration command, 98–99, 132, 482
show trunk command, 196, 200
show user command, 122
show version command, 78–79, 98, 128, 175–176, 473
show vlan command, 197, 200
show vlan-membership command, 167, 199–200
show vtp command, 191, 195, 200
shutdown command, 107, 406–407
SIT (Service Information Table), IPX, 333
SLIP (Serial Line Internet Protocol), 373
SNAP (Subnetwork Access Protocol), 20, 336
SONET (Synchronous Optical Network), 373
source-route bridging, 22
Spanning Tree
BPDUs, 156–158
bridge IDs, 157

configuration, displaying status of, 199–200
convergence, 161–162
designated port, 156
forward delay, 160
functionality of, 155
operations, 156
path cost, 158–159
port states, 157–158
recalculation, 161
root bridge, electing, 156–157
root ports, 156
Spanning-Tree Protocol, 155
states, 159–160
timers, 160
SPF (shortest path first) algorithms, 275
SPIDs (service provider IDs), ISDN, 395
numbering, 467
specifying, 397
split horizon (Frame Relay), 267–268, 427
SPX (Sequenced Packet Exchange), 331
SS7 (Signaling System 7), ISDN BRI call processing, 391
standard access lists, 300
standard IP access lists, 306
applying to vty ports, 315
configuration, 310–314
numbers for, 305
standard IPX access lists, 305, 351, 353–355
Standard profile (700 series routers), 465
star topology (Frame Relay), 425
startup
CDP, 114
routers, 68, 83–84
switches
operations, 68
prerequisite checklist, 70
procedures for, 70
static MAC addresses (switch ports), 172–173
static mapping (Frame Relay), configuration, 420–421
static membership mode(VLANs), 184–185
static routes, 251
700 series routers, establishing, 468
configuration, 252
defining for DDR over ISDN BRI, 400–401
enabling, 251–254
store-and-forward mode switching, 162
straight-through cable, 48–50
stub networks, 251
subinterface configuration mode (routers), 100
subinterfaces
inter-VLAN routers, 242
Frame Relay, configuration, 428
subnet addresses, 226–227
subnet masks, 25, 227–231
700 series routers, specifying for ISDN interfaces, 468
defaults, 230
extending, 231
format, specifying, 238
patterns, 229
specifying for 700 series router 10BaseT Ethernet interfaces, 467
switches
configuration, 167
verifying, 168
subnets
filtering traffic from with access lists, 309–310
planning, 235–236
traffic, blocking with access lists, 313–314
Subnetwork Access Protocol, 20, 336
SVCs (switched virtual circuits), 413
switched networks
loops
eliminating with Spanning Tree, 155–161
multiple, 154
redundancy, 150
switches (Catalyst 1900 series), 30, 70, 167
adding to VTP domains, 195
bridge IDs, 157
bridging/switching between in VLANs, 183
broadcast storms, eliminating, 151
CDP information, displaying, 115–116
Cisco product line, 35–36
CO switch (WANs), 370
command history buffer, 77–78
command modes, changing between, 75
communication with other network devices, 163–165
configuration, 165
default, 68
default settings, 165–167

displaying active configuration files, 79–80
downloading from TFTP server, 175
from CLI, 82–83
global configuration mode, 82
interface configuration mode, 82
IP configuration, displaying current, 82
permissable access locations, 68–69
resetting to factory defaults, 176
uploading to TFTP server, 175
configuration modes, 167–168
configuration revision numbern resetting, 191–192
console error messages, 77
context-sensitive help, 76–77
criteria for selecting, 32, 34–36
cut-through mode, 162
database instability from redundant frame transmissions, eliminating, 153–154
duplicate nonbroadcast frame transmissions, eliminating, 152–153
enterprise software, 79
Ethernet switches, 145
flooding, 146
fragment-free mode, 163
frame transmission, 162–163
full-duplex transmission, 163–165
functionality of, 145
gateways
assigning defaults, 237
default configuration, 167
verifying, 168
global configuration mode, 167
half-duplex transmission, 163–165
interface configuration mode, 167
interfaces
displaying configuration information about, 120
displaying statistics for, 80–81
displaying status of, 120
duplex mode configuration, 168–170
IOS, displaying information about, 174–175
IP addresses, 83
assigning, 237
configuration, 167
verifying, 168
ISDN, 389
configuring for use with 700 series routers, 467
types, 395
ISLs (Inter-Switch Links), 185–188
latency, 163
LEDs, 71–74
logon
after setup, 74–75
EXEC mode, 75
loop avoidance, 150–155
MAC addresses, learning, 146–148
Menu Console Logon Screen, 74
multiple broadcast domains, 181
naming, 83
operation at Layer 3 and 4, 22
operation at the data link layer, 21–24
path cost (Spanning Tree), 158–159
ports
address violations, 174
assigning to VLANs, 198–199
designated ports, 156
displaying VLAN assignments for, 199
dynamic MAC addresses, 170
MAC address table, displaying, 170
permanent MAC addresses, 171–172
root ports, 156
security configuration, 173–174
static MAC addresses, 172–173
trunk line configuration, 196–197
trunk ports, 184
VLAN assignments, 181
VLAN membership, 194
VLAN support, 187
root bridge, electing, 156–157
Spanning Tree
configuration status, displaying, 199–200
convergence, 161–162
recalculation, 161
standard software, 79
startup
initial configuration, 68
operations, 68
prerequisite checklist, 70
procedures for, 70
store-and-forward mode, 162
subnet masks. *See also* devices
configuration, 167
verifying, 168
system information displays, 78–79
versus bridges, 162
VLAN information

communicating with ISLs, 185–188
communication with VTP, 188–193
VLANs
adding, 197
adding to bridged/switched networks, 189
configuration, 193–200
defaults, 194
membership modes, 184–185
operation, 183–184
parameters, modifying/verifying, 198
renaming, 198
spanning multiple switches on a single link, 194
support limitations, 187
VTP, 188
configuration, 195–197
membership modes, 194
modes, 189–190
operations, 191–192
overwriting VLAN configurations, 192
pruning, 192–193
setup precautions, 190
VTP domains, 188
Synchronous Optical Network. *See* SONET
System LED (Catalyst 1900 series switch), 71
System profile (700 series routers), 466–467

T

T reference point (ISDN networks), 393
TA (Terminal Adapter), ISDN, 393
TCP (Transmission Control Protocol), 206
connections, establishing, 211–213
flow control, 213–214
header format, 207–208
port numbers, 209–211
window size, 214
TCP/IP (Transmission Control Protocol/Internet Protocol), 205
access lists, 306–310
application layer, 206
development, 205
Internet layer, 215–220
protocol stack, 205
transport layer, 206–214
TE1 (Terminal Endpoint 1), ISDN, 392
TE2 (Terminal Endpoint 2), ISDN, 393
telecommuters, 5
Telnet
sessions
displaying, 121–122
ending, 123
establishing to remote devices, 120–121
re-establishing, 122
suspending, 122
verifying, 121–122
traffic, blocking from a specific subnet with access lists, 320–321
telnet command, 120, 405
term ip netmask-format command, 238, 245
terminal editing command, 96
terminal history size command, 94
TFTP (Trivial File Transfer Protcol) servers
downloading router configuration from, 134
downloading to switches, 175
uploading router configuration to, 134
uploading switch running configuration to, 175
Thicknet, 15
Thinnet, 15
three-way handshake (communciation between network end stations), 29, 211–213
timers (Spanning Tree), 160
toll networks (WANs), 370
trace command, 124
traffic
devices, displaying information about, 119
filtering. *See* access lists
Frame Relay, displaying statistics, 422–423
FTP, blocking from a specific subnet with access lists, 319–320
impact on internetwork design, 7–8
interesting, identifying with access lists, 299
IPX, displaying volume/type information, 348
separating into queues with access lists, 299
Telnet, blocking from a specific subnet with access lists, 320–321

VLANs
multiplexing on a single physical path, 186
VTP pruning, 192
traffic-share command, 286, 294
trailers, 12
translational bridging, 22
Transmission Control Protocol. *See* TCP
Transmission Control Protocol/Internet Protocol. *See* TCP/IP
transparent bridging, 22
transparent mode (VTP), 189–190
transport layer (OSI reference model Layer 4), 28–30
triggered updates
pairing with holddown timers for route maintenance, 271–274
route maintenance with, 270–271
troubleshooting
DDR over ISDN BRI, 406
Frame Relay connections, 424
routing loops
with maximum metric settings, 266–267
with route poisoning, 268–269
with split horizon, 267–268
trunk command, 196
trunking (VLANs), 183–184, 196–197

U

U reference point (ISDN networks), 393
UDP (User Datagram Protocol), 206
flow control, 213–214
header format, 208–209
port numbers, 209–211
unequal-cost load balancing (IGRP), 284–285
unshielded twisted pair, 47
upgrading Ethernet, 44
upload command, 466
URL prefixes (Cisco network devices), 135
user EXEC mode (IOS), 69–70, 89–90
user mode (router initialization), 84
User profile (700 series routers), 468
username command, 381, 384
usernames (routers), defining, 381
users, grouping in broadcast domains, 179
UTP (unshielded twisted pair), 47
LAN implementations, 47–52
wiring standards, 47–48

V

variance command, 294
VCs (virtual circuits), 413
design considerations, 427
IP addresses, mapping, 414
states, 416
virtual terminal lines. *See* vty
Visual Switch Manager, 194
vlan command, 197, 200
VLAN Trunking Protocol. *See* VTP
vlan-membership command, 198
VLANs (virtual LANs), 179
adding, 197
to bridged/switched networks, 189
assigning switch ports to, 198–199
benefits of, 179
broadcast domains, functionality of, 181
characteristics, 183
configuration
default requirements, 194
guidelines, 194
overwriting, 192
prerequisite steps, 194
defaults, 194
definition, 181
functionality of, 182
information
communicating with ISLs, 185–188
communicating with VTP, 188–193
forwarding, 183
inter-VLAN routing, 241–244
membership modes, 184–185
operation, 183–184
parameters
modifying, 198
verifying, 198
parameters in bridged/switched networks, 182
port switch assignments, 181
renaming, 198
switches
bridging/switching between, 183
port membership, 194

spanning on a single link, 194
support limitations, 187
traffic
multiplexing on a single physical path, 186
VTP pruning, 192
trunking, 183
trunks, 184
VSM (Visual Switch Manager), 194
VTP (VLAN Trunking Protocol), 188
advertisements, 191
configuration, 195–197
defaults for Catalyst 1900 switches, 195
domains, 188
membership modes, 194
modes, 189–190
operations, 191–192
overwriting VLAN configurations, 192
pruning, 192–193
setup precautions, 190
vtp command, 195
vtp domain command, 200
vty (virtual terminal lines), routers, 103
controlling access to with access lists, 314–316
filtering Telnet traffic, 298

W

WANs (wide-area networks)
cabling, 53, 55
characteristics of, 367–368
circuit switching, 369
CO switch, 370
connectivity options, 368–369
CPE, 370
DCE, 371
demarcation, 370
devices, criteria for selecting, 33–34
DTE, 371
encapsulation
HDLC, configuration in WANs, 374
Layer 2, 372–374
PPP
characteristics of, 375–379
configuration, 379–383
verifying configuration, 383–384
ISDN BRI connections, cabling routers for, 62–63
leased lines, 368
local loop, 370
packet switching, connection standards, 370–372
PPP connections, establishing, 378–379
routing across, 244
serial connections, 55
cabling routers for, 57–62
differentiating between, 55–57
standards, 370–372
services, 367
terminology, 369–370
toll networks, 370
versus LANs, 367
where command (UNIX), 122
who command (UNIX), 122
wide-area networks. *See* WANs
wildcard masking (IP addresses), 307–310
window size (TCP), 214
wiring
Category 5 wiring, 53
EIA/TIA 568A/568B, 48
standards, 15–16
UTP standards, 47–48
workgroup layer, 9
workstations
host names, displaying, 240–241
IP addresses
discovering with RARP, 219–220
displaying, 240–241
write command, 101
write memory command, 101

X-Z

X.25/LAPB (Link Access Procedure, Balanced), 373

ZIP (Zone Information Protocol), 438
zones (AppleTalk), 441–443