
Index

Symbols

“Project Angel”, 6, 7

Numerics

1x evolution data optimized (1x EV-DO), 14,
213, 275, 369, 387, 398, 410

3G cellular systems, 14

A

access control, 247

access service network (ASN), 337, 357

access service network gateway (ASN-GW),
57, 338

See also WiMAX Forum Network
Working Group (NWG)

active set, 53

adaptive modulation and coding (AMC), 37,
43, 206, 208, 289, 290, 299, 323,
371, 377, 378, 394, 398

additive white Gaussian noise (AWGN), 25,
105, 107, 140, 141, 153, 155, 164,
187, 210, 365, 370, 409

adjacent subcarrier permutation, 217

admission control, 225–226

advanced antenna systems (AAS), 38, 55,
287, 323

Advanced Encryption Standard (AES), 38,
241–246

advanced wireless services (AWS), 21

advertised specifications (ADSpec), 229

advertised window, 260

aggregate handling, 227

AK Transfer Protocol, 349

amplitude modulation/amplitude modulation
(AM/AM), 131

amplitude modulation/phase modulation
(AM/PM), 131

analog-to-digital convertor (ADC), 68, 132
See also digital-to-analog convertor
(DAC)

anchor

base stations (BS), 53, 330, 331

data path function, 354

PC, 361

See also base station (BS)

angle of departure (AoD), 100

angular spread (AS), 90, 100, 103

antenna grouping, 297

antenna selection, 297

application

function (AF), 351, 352

programming interfaces (API), 234

service providers (ASP), 337

array, 150

array response vector, 170

association levels, 328

assured forwarding (AF), 230

asymmetric key, 242, 245

AT&T, 7

authentication, 247, 346–348

key, 348

relay protocol, 349

server, 247

authorization module, 319

automatic repeat requests (ARQ), 312, 323, 330, 355, 366, 385, 409

automatic retransmissions requests (ARQ), 38, 208, 209, 254, 262, 263, 272, 277, 307, 308

B

backoff window, 317

back-of-the-envelope, 373

bandwidth, 313

base station, 57, 338

 controller (BSC), 58, 339

 transceiver (BST), 58

See also WiMAX Forum Network Working Group (NWG)

basic capabilities, 322

beamforming, 55, 149, 166, 169–172, 189, 190, 292, 368, 387, 389, 407–410, 419–422

 direction of arrival (DOA), 169, 170

 eigenbeamforming, 169–173

Bell Labs layered space/time (BLAST), 178

best-effort service (BE), 228, 318

binding update, 256

bit error probability (BEP), 140, 152–157, 164

bit error rate (BER), 191, 279, 366, 383, 389

block error rate (BLER), 105, 373

breakout gateway control function (BGCF), 239

broadband fading, 104

broadband radio services (BRS), 19

burst profile, 206, 217, 283

burst time division multiplexing (TDM), 8
 See also time division multiplexing

C

cable modem technology, 3

call drop, 330

call session control functions (CSCF), 239

call-processing language (CPL), 234

care-of address (CoA), 255

 colocated CoA (CCoA), 358

carrier sense multiple access (CSMA), 15, 201, 204

cell, 25, 56, 78, 183, 185, 329, 369, 401–413, 421

cellular architecture, 25, 78

certification profile, 34

challenge handshake authentication protocol (CHAP), 248

channel

 coherence bandwidth, 115

 coherence time, 70

 estimation, 187

 quality feedback (CQI), 303

 quality indicator channel (CQICH), 45, 368, 376, 381

 reciprocity, 189

 sounding, 189, 297

 state information (CSI), 287

chase combining, 56, 278

cipher-block chaining message-authentication code (CBC-MAC), 245

ciphertext, 242

circular convolution, 117

client context, 355

client-based mobile (CMIP), 259

clipping, 135, 136

closed loop, 158

closed loop-transmit diversity, 164

See also transmit diversity

cochannel-reuse ratio, 79

code division multiple access (CDMA), 5, 8, 108, 185, 199–201, 330, 375

codebook based feedback, 297

codecs, 239
coherence
 bandwidth, 86, 114, 167, 285–287, 296, 376, 377
 distance, 90
 time, 87, 119, 166, 167, 210, 303, 381
colocated foreign agent, 255
coloring matrix, 406
common gateway interface (CGI), 234
congestion window, 261
congestion-avoidance, 261
conjugate transpose, 168
connection identifier (CID), 48, 309, 315–321, 345
 secondary CIDs, 316
connectivity service network (CSN), 57, 337
 See also WiMAX Forum Network Working Group (NWG)
controlled load services, 228
conventional transpose, 168
correspondent node (CN), 255
COST-231-Hata model, 402, 424
counter mode, 244
customer premise equipment (CPE), 10, 60, 61
cyclic prefix, 118–121, 187, 217, 276, 281, 301, 332, 371

D

data, 108
 path function (DPF), 354
 region, 44, 283, 290, 312, 385
 subcarriers, 282
decision-feedback equalizers, 109
decryption, 242
delay spread (DS), 70, 86, 103, 113, 117, 121, 142, 285, 376, 383
deployment modularity, 336

differentiated services (DiffServ), 229
digital audio radio services (DARS), 20
digital subscriber line (DSL), 3, 39, 199, 210, 336
digital-enhanced cordless telephony (DECT), 5
digital-to-analog convertor (DAC), 68, 131, 132
 See also analog-to-digital convertor
discrete Fourier transform (DFT), 40, 117–118, 136, 187, 383
dispersion, 97
distortion, 189
distributed coordination function (DCF), 201
distributed subcarrier permutation, 217
distribution systems, 6
diversity, 105, 150, 422
 order, 152
 precoding, 167
 set, 53, 330
domain name system (DNS), 239
Doppler power spectrum, 87
Doppler spread, 25, 40, 43, 71, 87–89, 188, 287, 303, 368, 381
double space/time transmit diversity (DSTTD), 161
 See also transmit diversity
downlink channel descriptor (DCD), 291
dropping probability, 251
dynamic subcarrier allocation, 202

E

edge effect, 405
effective code rate map (ECRM), 408
effective isotropic radiated power (EIRP), 20
eigenbeamforming, 169–173
eigenchannel, 171

- Electronics and Telecommunications Research Institute (ETRI), 13
 - empirical path loss formula, 72
 - encryption key, 242
 - equal gain combining (EGC), 157
 - Erceg model, 402, 424
 - Ethernet convergence sublayer (ETH-CS), 342
 - European Telecommunications Standards Institute (ETSI), 8, 33
 - expedited forwarding (EF), 230
 - exponentially effective SINR map (EESM), 408
 - See also* signal-to-interface-plus noise ratio (SINR)
 - extended real-time polling service (ertPS), 318
 - See also* polling
 - extensible authentication protocol (EAP), 39, 248, 249, 345, 346, 353
 - See also* authentication
 - extensible authentication protocol (EAP) method, 249
- F**
- fading, 84, 110, 114, 151–154, 159–163, 202, 289, 320
 - See also* multipoint fading
 - fast base station switching (FBSS), 53, 254, 353
 - fast Fourier transform (FFT), 37, 100, 117, 119–122, 128, 142, 185–186, 272, 285
 - fast recovery, 261
 - fast retransmit, 261
 - Federal Communications Commission (FCC), 6, 109
 - fiber-to-the-home (FTTH) system, 4
 - final sleep window size, 326
 - first-generation broadband systems, 6
 - fixed broadband wireless applications, 4
 - consumer and small-business broadband, 10
 - T1 emulation for business, 11
 - Wi-Fi hotspots, 12
 - fixed WiMAX, 271
 - flash-OFDM, 13
 - See also* orthogonal frequency division multiplexing
 - flow context, 264
 - FlowSpec, 228
 - foreign agent (FA), 255
 - forking, 237
 - forward equivalence class (FEC), 231
 - forward error correction (FEC), 37, 272, 293, 330, 370–373, 385, 409
 - forward information base (FIB), 232
 - frame control header (FCH), 44, 291, 301, 319, 410
 - frame error rate (FER), 105
 - free-space, 422
 - pathloss formula, 70
 - frequency
 - diversity, 107, 149
 - division duplexing (FDD), 8, 36, 38, 44
 - division multiple access (FDMA), 200–202
 - equalization, 122
 - hopping diversity code (FHDC), 295
 - planning, 78
 - reuse, 25, 55, 56, 78–82, 183, 287, 401, 413, 419, 421
 - synchronization, 124
 - full-buffer traffic model, 412
 - function context, 355
 - functional decomposition, 336

G

generic MAC header (GMH), 48
See also media access control

generic routing encapsulation (GRE), 342

global system for mobile communications (GSM), 14, 58, 108, 109, 339

guaranteed services, 228

H

handoff (HO) function, 355

handoff management, 250

handoff rate, 251

hard handover, 53

hashed message authentication code, 322

Hermitian transpose, 168

high speed downlink packet access (HSDPA), 14, 60, 108, 202, 213, 275, 369, 387, 398, 410

high-definition TV (HDTV), 4

high-performance metropolitan area network (HIPERMAN), 8, 33

high-power amplifier (HPA), 131

home
 address (HoA), 255
 agent (HA), 255
 subscriber server (HSS), 239

hybrid-ARQ, 56, 278
See also automatic retransmissions requests

Hypertext transfer protocol (HTTP), 233

I

i-Burst technology, 13

idle mode, 52

incremental redundancy, 56, 278

initial ranging, 320, 321

initial sleep window size, 326

input backoff (IBO), 132

Institute of Electrical and Electronics Engineers (IEEE)
 Globecom, 146

Institute of Electrical and Electronics Engineers (IEEE) standards, 8

802.11, 67, 271

802.15.3, 121

802.16, 33, 34, 37, 68, 223, 309, 318, 338, 342, 360

802.16 group, 8, 33, 34, 67

802.16-2004, 8, 34, 41, 271, 335

802.16-2005, 9, 34–38, 50, 52, 57, 137, 254, 271, 272, 290, 292, 324, 335, 348, 365, 392, 401

802.16a amendment, 8

802.20, 17

802.22, 17

802.3, 313

integrated services (IntServ), 227

intercarrier interference (ICI), 281

interference limited, 73

Internet group management protocol (IGMP), 339

Internet Protocol television (IP-TV), 13

intersymbol interference (ISI), 24, 39, 40, 89, 107, 109, 113, 117, 142, 281

inverse fast Fourier transform (IFFT), 40, 117, 119, 142, 204, 282, 300
See also fast Fourier transform

IP convergence sublayer (IP-CS), 342

K

key
 distributor, 348
 encryption key (KEK), 339, 349
 receiver, 348

L

label switching routers (LSR), 232
 label-edge router (LER), 231
 lightweight directory access protocol (LDAP), 225
 linear equalizer, 109
 linear minimum mean square error, 383
 link-level simulations, 404
 local multipoint distribution systems (LMDS), 6
 local policy function (LPF), 352
 location

- management, 249
- register (LR), 250, 361
- server, 235
- update, 250

 lognormal shadowing, 110

M

MAC service data units (MSDUs), 356
 macro diversity handover (MOHO), 53, 353
 master session key (MSK), 348
 Matlab function, 100
 maximal ratio combining (MRC), 154, 156
 maximum

- backoff window, 317
- Doppler, 88
- likelihood detection, 109, 366, 396
- sum rate (MSR) algorithm, 210

 MCI WorldCom, 6
 mean instantaneous capacity (MIC), 408
 mean square error (MSE), 299, 394
 media access control (MAC), 8, 33, 36, 38, 47, 48, 53, 201, 223, 271, 307, 335, 344, 360, 366, 410

- managements messages, 302
- protocol data units (MPDUs), 47
- service data units (MSDUs), 47

media gateway (MG), 239
 media gateway control function (MGCF), 239
 median pathloss models, 402

- COST-231-Hata model, 402, 424
- Erceg model, 402, 424
- Okumura-Hata model, 402, 422
- Walfisch-Ikegami model, 402, 426

 message digest, 246
 minimum signal level (MSL), 251
 mobile broadband, 4

- mobility, 4
- nomadicity, 4
- wireless applications, 12, 13
- See also* fixed broadband wireless

 mobile node (MN), 255
 mobile stations, 45, 80, 150, 223, 259, 358, 401, 422
 mobile WiMAX, 272

- See also* WiMAX

 mobility, 4, 28, 33, 39, 52, 89, 98, 199, 249, 254, 259, 320, 324, 327, 335, 352–358, 424

- handoff, 28
- management, 28, 250
- proxy agent (MPA), 259
- roaming, 28

 mode of operation, 244
 modulus, 247
 multiantenna processing, 8
 multicarrier concept, 110
 multicarrier modulation, 39, 114, 149
 multicast and broadcast services (MBS), 54
 multichannel multipoint distribution services (MMDS), 6
 multipath fading, 24, 84, 104, 108, 368, 374, 403

- See also* fading

 multipath intensity profile

power-delay profile, 86
multiple input/multiple output (MIMO), 149,
366, 368, 374, 383, 387, 389, 392–
398, 401, 406, 410, 419, 422
multiple input/single output (MISO), 149
multiplexing, 150, 366, 387, 392
multiprotocol label switching (MPLS), 231,
355
multiuser, 199

N

Nakagami-m fading, 95
narrowband (flat) fading, 104, 105
See also fading
narrowband wireless local-loop system, 5
network
access provider (NAP), 337
address translation (NAT), 256
entry, 319
reference model (NRM), 337
service provider (NSP), 337
timing protocol (NTP), 240
non-line-of-sight (NLOS) system, 113, 374,
422
nonlinear equalizer, 109
non-real-time polling services (nrtPS), 318
See also polling
nonrepudiation, 246
null subcarriers, 282
null-steering beamformer, 171
Nyquist sampling, 134

O

Okumura-Hata model, 402, 422
open loop transmit-diversity, 158
ordered successive interference cancellation,
366, 396
orthogonal communication, 200

orthogonal frequency division multiple access
(OFDMA), 8, 34–41, 60, 199, 209,
214, 216
orthogonal frequency division multiplexing
(OFDM), 8, 34–39, 60, 89, 97, 98,
109, 113, 117, 128, 159, 168, 182,
184, 199, 203, 271, 368, 375, 383,
384, 416
history, 9
OFDM symbol, 117

P

packet data unit (PDU), 48
packet error rate (PER), 105
packet header suppression (PHS), 309
paging, 250
agent (PA), 361
controller (PC), 361
group (PG), 327, 361
group update, 327
pairwise master key (PMK), 348
partial usage of subcarriers (PUSC), 43, 285,
286, 290, 298, 323, 371, 376, 398,
416
password authentication protocol (PAP), 248
pathloss, 24, 61, 69–73, 84, 93, 110, 154,
211, 406, 422, 424
peak-to-average ratio (PAR), 131–134, 140,
302
peak-to-average-power ratio (PAPR), 131, 204
per hop behavior (PHB), 230
per-flow handling, 226, 228
periodic ranging, 320
personal communications services (PCS), 6,
424
personal mobility, 238
PHY-layer data rate, 46
pilot subcarriers, 282

pilot symbol, 130
 plaintext, 242
 point-of-attachment (PoA), 344
 point-to-multipoint applications, 10, 11, 35
 point-to-point applications, 10
 policy decision points (PDP), 225
 policy enforcement points (PEP), 225, 339
 polling, 48, 316
 portability, 29, 52, 104, 336, 360
 power-saving class, 326
 precoding codebook, 189
 primary, 316
 private key, 247
 Privacy Key Management Version 2
 (PKMv2), 345, 348
 probability density function (PDF), 205
 propagation models, 422
 proportional fairness (PF) scheduler, 213, 416
 proportional rate constraints (PRC) algorithm,
 212
 protocol data unit, 307
 provisioned QoS parameter set, 319
 See also quality of service (QoS)
 proxy mobile IP (PMIP), 259
 proxy server, 235
 public exponent, 247
 public key infrastructure (PKI), 245, 247
 public switched telephone network (PSTN),
 58, 239
 pull model, 346

Q

quality of service (QoS), 26, 27, 38, 39, 44,
 48, 57, 204, 223–225, 258, 265,
 290, 307, 335, 346, 349
 active parameter set, 319
 policy management, 225
 quantized channel feedback, 297

R

radio
 frequency (RF), 68, 117, 131, 287
 resource agent, 359
 resource controller (RRC), 339, 359
 resource management (RRM), 338, 358,
 359
 rake receivers, 108
 random-access, 201
 ranging, 217
 Rayleigh
 distribution, 94
 fading, 91, 93, 104, 132, 155, 164, 205,
 206, 365, 403
 real time
 control protocol (RTCP), 240
 polling service (rtPS), 318
 transport (RTP), 227
 receive diversity, 163
 See also diversity
 received signal strength indicator (RSSI), 303
 receiver, 366
 redirect server, 235
 Reed Solomon (RS), 275
 reference points, 58, 336
 registrar server, 235
 relaying context function, 355
 relaying data path function, 355
 See also data path
 relaying HO function, 355
 remote access dial-in user service (RADIUS),
 242, 247
 request for comments (RFC), 230, 345–349,
 356, 358
 resource reservation protocol (RSVP), 226,
 228, 339
 resource-retain timer, 329
 reverse tunneling, 256

Ricean

- distribution, 93, 94, 95
- fading, 95, 403

robust header compression (ROHC), 264

round robin (RR) scheduler, 202, 416

route optimization, 256

S

samples, 95

scanning intervals, 53

scheduling service, 317

second-generation broadband wireless systems, 8

See also wireless broadband

sectoring, 82

security, 29, 33, 39, 53, 223, 235, 241, 247, 335, 345–349

segmentation, 287

selection combining (SC), 154, 155

selection diversity, 107

See also diversity

selectivity, 97

semempirical channel model, 103

server context, 355

service flow, 309, 315, 318, 339, 345, 348, 350, 361

authorization (SFA), 339, 351

classes, 319

identifier (SFID), 318, 324

management (SFM), 351

service level agreements (SLA), 226, 230, 340

service mobility, 238

Service Provider Working Group (SPWG), 335

serving data path function, 354

See also data path

serving HO function, 355

See also handoff function

session, 233

description protocol (SDP), 234

initiation protocol (SIP), 233, 265

mobility, 238

shadowing, 24, 69, 74, 84, 92, 93, 103, 110, 402, 424

signaling, 225

signal-mapping techniques, 142

signal-to-interface-plus-noise ratio (SINR), 44, 55, 73, 74, 80, 81, 105, 153, 157, 172, 173, 183, 206, 209–218, 251, 300, 302, 328, 407, 408

signal-to-interference-plus-noise ratio (SINR), 26, 303

signal-to-noise-plus-distortion ratio (SNDR), 140

single input/multiple output (SIMO), 149, 387

singular-value decomposition (SVD), 179, 180

sleep mode, 51

slot, 44, 107, 290, 312, 408

slow-start threshold, 261

space/time block codes (STBC), 158, 160, 167

spatial diversity, 106, 149, 150

See also diversity

spatial multiplexing (SM), 55, 161, 167, 174, 175, 292

See also automatic retransmissions requests

See also multiplexing

spectral regrowth, 136

spread spectrum, 108

Sprint, 6

standards

See also Institute of Electrical and Electronics Engineers (IEEE)

statistical channel model, 91
 stop and wait ARQ, 56
 stream control transport protocol (SCTP), 234
 See also transport control protocol
 subcarrier permutation, 160, 273, 283
 subchannelization, 43, 217, 273, 275
 subpacket identity (SPID), 279
 subscriber stations, 23, 43, 45, 51, 54
 supplicant, 247
 symmetric key, 242
 synchronization, 126, 127, 130, 185, 200,
 217, 240, 253, 280, 290, 300, 309,
 319, 329, 355, 368
 system identity information advertisement
 (SII-ADV), 344
 system profile, 34
 system-level simulations, 404

T

tap-delay line (TDL), 69
 target data path function, 355
 target HO function, 355
 terminal mobility, 238
 Third-generation Partnership Project (3GPP),
 14, 58, 101, 102, 239, 335, 369
 tile usage of subcarriers (TUSC), 287
 time division
 duplexing (TDD), 8, 16, 36–38, 44, 55,
 158, 189, 287, 296, 323, 413
 multiple access (TDMA), 192, 200, 201,
 375
 multiplexing, 33, 35
 synchronous CDMA (TD-SCDMA), 14
 time/frequency uncertainty principle, 88
 timing synchronization, 124
 traffic
 encryption key (TEK), 339, 348
 engineering (TE), 232

 specifications (TSPEC), 228
 transmission, 108, 366
 transmit
 diversity, 55, 160, 163
 selection diversity (TSD), 165, 167
 spatial diversity, 157
 See also diversity
 transport control protocol (TCP), 227, 260,
 278
 transport-layer security (TLS), 234
 triangular routing, 255
 two-ray approximation, 70
 type of service (TOS), 229

U

ultra high frequency (UHF), 21
 See also frequency
 unicast, 316
 See also polling
 universal mobile telephone system (UMTS),
 14
 unlicensed national information infrastructure
 (U-NII), 20
 unsolicited grant services (UGS), 316, 326
 uplink channel descriptor (UCD), 291
 user agents (UA), 234
 user datagram protocol (UDP), 234

V

very high data rate digital subscriber loop
 (VDSL) system, 4
 video on demand (VoD), 4
 virtual local area networking (VLAN), 343
 virtual path identifier/virtual circuit identifier
 (VPI/VCI), 232
 voice telephony, 5, 223, 230
 voice-over-internet protocol (VoIP)
 technology, 4, 39, 44, 50, 199, 251,
 259, 307, 309, 401

W

Walfisch-Ikegami model, 402, 426

Wi-Fi Alliance, 9

Wi-Fi based-systems, 15

See also fixed broadband wireless applications

WiMAX

adaptive modulation and coding, 26

business challenges, 21, 22

efficient multiaccess techniques, 26

fixed, 271

Forum, 7, 9, 18

Internet Protocol (IP), 30

physical layer (PHY), 37, 39, 77, 223, 271, 307, 315, 320, 335, 360, 366, 410

spatial multiplexing, 26

spectrum scarcity, 25

technical challenges, 23–25, 31

versus 3G and Wi-Fi, 16

WiMAX Forum, 410

WiMAX Forum Network Working Group (NWG), 37, 57

wireless

broadband (WiBro), 7, 43, 282

channel modeling, 402

communications services (WCS), 7

local-loop (WLL) system, 5

metropolitan area network (wireless MAN), 8, 34, 271

regional area networks (WRAN), 17

wraparound, 405

Z

zero prefix, 121

zero-forcing detector, 176