

# ACME Library Database Technical Resource Kit

## Table Structures

In the following section, the “Type” column describes the format of the data stored in the field. Generic terms are used here. Each type can be mapped to its SQL Server equivalent as follows.

Generic Term	SQL Server Equivalent	Comments
Boolean	bit	True or False value. The bit data type supports NULL values, but in the library database, all Boolean fields are required.
Currency	money	Used for patron fines and other financial values.
Date	datetime	All date related values except for standalone years.
Integer	smallint	Used for most non-decimal values.
Long	bigint	Mainly used for primary keys values. Some primary key fields have a type of “Long - Auto,” which indicates that the ID value is autogenerated by SQL Server using the IDENTITY field property.
Memo	varchar(max)	Long, descriptive text and comments.
Number	decimal	All non-financial decimal values.
Text(x)	varchar(x)	All variable-length text values other than long comments.

**Activity** - This table defines the features of the application that can be secured using group rights. These activities are linked with security groups (from the *GroupName* table) to establish the rights for a particular group.

Field	Type	Description
ID	Long	Primary key. This key is not auto-generated; the value supplied matches internal values used within the Library application. Required.
FullName	Text(50)	Descriptive name of this activity. Required.

The following activities are defined at this time.

- 1 - Manage authors and names
- 2 - Manage author and name types
- 3 - Manage copy status codes
- 4 - Manage media types
- 5 - Manage series
- 6 - Manage security groups
- 7 - Manage library materials
- 8 - Manage patrons
- 9 - Manage publishers
- 10 - Manage system values
- 11 - Manage administrative users
- 12 - Process and accept fees
- 13 - Print reports
- 14 - Manage locations
- 15 - Check out library items
- 16 - Check in library items
- 17 - Access administrative features
- 18 - Perform daily processing
- 19 - Run system reports
- 20 - Access patrons without patron password
- 21 - Manage barcodes

- 22 - Manage holidays
- 23 - Manage patron groups
- 24 - View administrative patron messages

**Author** - Someone who writes, edits, illustrates, or in some other way contributes to a book or media item. In all cases, when the term “author” appears in this table, it refers to anyone who contributes to the item.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
LastName	Text(50)	Last name of this author. Required.
FirstName	Text(30)	First name of this author. Optional.
MiddleName	Text(30)	Middle name or initial of this author. Optional.
Suffix	Text(10)	Name suffix, such as “Jr.” Optional.
BirthYear	Integer	Year of birth. Use negative numbers for BC. Optional
DeathYear	Integer	Year of death. Use negative numbers for BC. Optional.
Comments	Text(250)	Miscellaneous comments about this author. Optional.

**BarcodeLabel** - Describes the template for a single label on a barcode sheet. There may be any number of labels on a single sheet, but they all have the same shape and format.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this label template. Required.
BarcodeSheet	Long	The sheet template on which this label template appears. Foreign reference to BarcodeSheet.ID. Required.
UnitType	Text(1)	Units used in the various measurements found in most fields in this record. Required. <ul style="list-style-type: none"> <li>• I = Inches</li> <li>• C = Centimeters</li> <li>• P = Points</li> <li>• T = Twips</li> </ul>

**BarcodeLabelItem** - Describes a single item as found on a barcode label. Items include static and generated text, lines, rectangles, and generated barcodes.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
Priority	Integer	Identifies the order in which items on the label are printed. Lower numbers are printed first. Required.
BarcodeLabel	Long	The label template on which this item appears. Foreign reference to BarcodeLabel.ID. Required.
ItemType	Text(1)	What type of item does this record represent? Required. <ul style="list-style-type: none"> <li>• T = Static text</li> <li>• B = Barcode</li> <li>• N = Barcode number</li> <li>• L = Line</li> <li>• R = Rectangle</li> </ul>
PosLeft	Number	Left edge of the item relative to the left edge of the label. Measured according to the related BarcodeLabel.UnitType field. Required.
PosTop	Number	Top edge of the item relative to the top edge of the label. Measured according to the related BarcodeLabel.UnitType field. Required.
PosWidth	Number	Width of the item, or of the box in which the item is drawn. For lines, this is the X-coordinate of the end point. Measured according to the related BarcodeLabel.UnitType field. Required.
PosHeight	Number	Height of the item, or of the box in which the item is drawn. For lines, this is the Y-coordinate of the end point. Measured according to the related BarcodeLabel.UnitType field. Required.

Field	Type	Description
Rotation	Integer	Rotation angle, in degrees, of the box in which the item is drawn. Zero (0) equals no angle, and increasing angles proceed clockwise. Ranges from 0 to 359. Only used when ItemType is T, B, N, or R. Optional.
FontName	Text(50)	The name of the font used to write the text. Valid only when ItemType is T or N. Optional.
FontSize	Number	The size of the font used to write the text. Valid only when ItemType is T, B, or N. Optional.
StaticText	Text(100)	The static text to display on the label. Valid only when ItemType is T. Optional.
FontStyle	Text(4)	The style of the font text. May be any combination of the following four codes. <ul style="list-style-type: none"> <li>• B = Bold</li> <li>• I = Italic</li> <li>• U = Underline</li> <li>• K = Strikeout</li> </ul> Leave this field NULL to use the normal style. Valid only when ItemType is T or N. Optional.
Color1	Long	The main color of the text, barcode, or line. When printing a rectangle, this is the border color. If NULL, black is used. A standard Windows 32-bit RGB color value. Optional.
Color2	Long	The fill color when printing a rectangle. If NULL, white is used. A standard Windows 32-bit RGB color value. Optional.
Alignment	Integer	The alignment of the text within the bounding box. Valid only when ItemType is T, B, or N. <ul style="list-style-type: none"> <li>• 1 = Align in top-left corner of box</li> <li>• 2 = Align in top-center area of box</li> <li>• 4 = Align in top-right corner of box</li> <li>• 16 = Align in middle-left area of box</li> <li>• 32 = Align in middle-center area of box</li> <li>• 64 = Align in middle-right area of box</li> <li>• 256 = Align in bottom-left corner of box</li> <li>• 512 = Align in bottom-center area of box</li> <li>• 1024 = Align in bottom-right corner of box</li> </ul>
PadDigits	Integer	The number of digits in which to pad the barcode number. Set to zero (0) to ignore padding. Ranges from 0 to 20. If the barcode length is less than the specified number of digits, it is padded on the left with zeros. Only applies to ItemTypes of B and N.

**BarcodeSheet** - Describes the template for a single page of barcode labels.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this sheet template. Required.
UnitType	Text(1)	Units used in the various measurements found in most fields in this record. Required. <ul style="list-style-type: none"> <li>• I = Inches</li> <li>• C = Centimeters</li> <li>• P = Points</li> <li>• T = Twips</li> </ul>
PageWidth	Number	Width of the entire page. Required.
PageHeight	Number	Height of the entire page. Required.
MarginLeft	Number	Left border, up to the edge of the printable label area. Required.
MarginRight	Number	Right border, up to the edge of the printable label area. Required.
MarginTop	Number	Top border, up to the edge of the printable label area. Required.

Field	Type	Description
MarginBottom	Number	Bottom border, up to the edge of the printable label area. Required.
IntraColumn	Number	The width of the blank area between label columns. Required.
IntraRow	Number	The height of the blank area between label rows. Required.
ColumnsCount	Integer	The number of label columns on this template. Required.
RowsCount	Integer	The number of label rows on this template. Required.

**CodeAuthorType** - In the Library program, the word “author” is a generic term used for authors, illustrators, editors, and any other similar contributor to an item in the library’s inventory. This table lets you define those roles.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this type of author or contributor. Required.

**CodeCopyStatus** - Copy status codes include things like “circulating,” “being repaired,” and any other primary status the library wishes to set. The checked-in or checked-out status is handled through other features, as is the flag that indicates whether an item is a reference item or not.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this status entry. Required.

**CodeLocation** - Physical locations where library items are stored. This could be separate sites, or rooms or areas within a common location.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this location. Required.
LastProcessing	Date	The date when Daily Processing was last done for this location. If NULL, processing has not yet been done. Optional.

**CodeMediaType** - Types of media, such as Book, Magazine, Video, CD, etc.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this media type. Required.
CheckoutDays	Integer	Number of days for which items in this type can be checked out, before renewal. Required.
RenewDays	Integer	Number of days to add to the original checkout period for a renewal of items within this type. Required.
RenewTimes	Integer	Maximum number of times the item can be renewed by a patron before it must be returned. Required.
DailyFine	Currency	Amount charged per day for an overdue item of this type. Required.

**CodePatronGroup** - Categories of groups into which patrons are placed. These are not security groups, but general groups for reporting purposes. This was added to support grouping of patrons by units within a company, or by class/grade within a school library setting.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this patron group. Required.

**CodeSeries** - Some items appear as part of a larger series or collection. This table defines the collection and series names.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this series or collection. Required.

**GroupActivity** - This table connects records in the *Activity* table to records in the *GroupName* table (a many-to-many relationship) to establish the activities a security group can perform.

Field	Type	Description
GroupID	Long	Primary key. The associated security group. Foreign reference to GroupName.ID. Required.
ActivityID	Long	Primary key. The activity that members of the associated security group can perform. Foreign reference to Activity.ID. Required.

**GroupName** - Each record in this table defines a single security group. Librarians and other administrators each belong to a single security group.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this group. Required.

**Holiday** - When checking an item out to a patron, the return date should not fall on holiday (or any day that the library is closed) since the patron might not have a way to return the book on the day it's due. This table defines one-time and recurring holidays.

Field	Type	Description								
ID	Long - Auto	Primary key, automatically assigned. Required.								
FullName	Text(50)	Name of this holiday. Not necessarily unique. Required.								
EntryType	Text(1)	The type of entry. Required. From the following list. <ul style="list-style-type: none"><li>• A = Annual (as in “every December 25”)</li><li>• E = Weekly (as in “every Sunday”)</li><li>• O = One-time (as in “2/16/2004 is President’s Day”)</li></ul>								
EntryDetail	Text(10)	Entry-type-specific detail. Required. Differs for each entry type. <table><tr><th>Entry Type</th><th>Detail Value</th></tr><tr><td>A</td><td>Month and Day in “mm/dd” format.</td></tr><tr><td>E</td><td>Single digit: 1=Sunday through 7=Saturday</td></tr><tr><td>O</td><td>Date in “yyyy/mm/dd” format.</td></tr></table>	Entry Type	Detail Value	A	Month and Day in “mm/dd” format.	E	Single digit: 1=Sunday through 7=Saturday	O	Date in “yyyy/mm/dd” format.
Entry Type	Detail Value									
A	Month and Day in “mm/dd” format.									
E	Single digit: 1=Sunday through 7=Saturday									
O	Date in “yyyy/mm/dd” format.									

**ItemAuthor** - An author, editor, and so on, for a specific named item. This table establishes a many-to-many relationship between the *NamedItem* and *Author* tables.

Field	Type	Description
ItemID	Long	Primary key. The associated named item. Foreign reference to NamedItem.ID. Required.
AuthorID	Long	Primary key. The author associated with the named item. Foreign reference to Author.ID. Required.
Sequence	Integer	Relative order of this author among the authors for this named item. Authors with smaller numbers appear first. Required.
AuthorType	Long	The specific type of contribution given by this author for this named item. Foreign reference to CodeAuthorType.ID. Required.

**ItemCopy** - A single copy of a named item. Separate copies of the same item will appear as separate records in this table.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
ItemID	Long	The related named item record. Foreign reference to NamedItem.ID. Required.
CopyNumber	Integer	Numbered position of this item within the set of copies for a named item. Required, and unique among items with the same ItemID field value.
Description	Memo	Comments specific to this copy of the item. Optional.
Available	Boolean	Is this copy available for checkout or circulation? 0 for False, 1 for True. Required.

Field	Type	Description
Missing	Boolean	Has this copy been reported missing? 0 for False, 1 for True. Required.
Reference	Boolean	Is this a reference copy? 0 for False, 1 for True. Required.
Condition	Text(30)	Any comments relevant to the condition of this copy. Optional.
Acquired	Date	Date this copy was acquired by the library. Optional.
Cost	Currency	Value of this item, either original or replacement value. Optional.
Status	Long	The general status of this copy. Foreign reference to CodeCopyStatus.ID. Required.
Barcode	Text(20)	Barcode found on the copy. At this time, only numeric barcodes are supported. Optional.
Location	Long	The site or room location of this item. Foreign reference to CodeLocation.ID. Optional.

**ItemKeyword** - Connects a keyword with a named item through a many-to-many relationship between the *NamedItem* and *Keyword* tables.

Field	Type	Description
ItemID	Long	Primary key. The associated named item. Foreign reference to NamedItem.ID. Required.
KeywordID	Long	Primary key. The keyword to associate with the named item. Foreign reference to Keyword.ID. Required.

**ItemSubject** - Connects a subject with a named item through a many-to-many relationship between the *NamedItem* and *Subject* tables.

Field	Type	Description
ItemID	Long	Primary key. The associated named item. Foreign reference to NamedItem.ID. Required.
SubjectID	Long	Primary key. The subject to associate with the named item. Foreign reference to Subject.ID. Required.

**Keyword** - Custom words that can be applied to named items to make searching easier.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this keyword. Required.

**NamedItem** - A library item, such as a book, CD, or magazine. This table represents a general item, and not the actual copy of the item.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
Title	Text(150)	Title of this item. Required.
Subtitle	Text(150)	Subtitle of this item. Optional.
Description	Memo	Full description of this item. Optional.
Edition	Text(10)	Edition number for this item. Optional.
Publisher	Long	This item's publisher. Foreign reference to Publisher.ID. Optional.
Dewey	Text(20)	Dewey decimal number. Use "/" for line breaks. Optional.
LC	Text(25)	Library of Congress number. Use "/" for line breaks. Optional.
ISxN	Text(20)	ISBN, ISSN, or other standardized number of this item. Optional.
LCCN	Text(12)	Library of Congress control number. Optional.
Copyright	Integer	Year of original copyright, or of believed original copyright. Optional.
Series	Long	The series or collection in which this item appears. Foreign reference to CodeSeries.ID. Optional.
MediaType	Long	The media classification of this item. Foreign reference to CodeMediaType.ID. Required.
OutOfPrint	Boolean	Is this title out of print? 0 for False, 1 for True. Required.

**Patron** - An identified library user. Patrons usually have check-out privileges.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
LastName	Text(30)	Last name of this patron. Required.
FirstName	Text(30)	First name of this patron. Required.
LastActivity	Date	Date of last checkout, renewal, or return. Optional.
Active	Boolean	Is this an active patron? 0 for False, 1 for True. Required.
Comments	Memo	Any comments associated with this patron. Optional.
AdminMessage	Memo	Comments that are displayed to administrative users when the patron's record is accessed. Optional.
Barcode	Text(20)	Barcode found on this patron's library card. At this time, only numeric barcodes are supported. Optional.
Password	Text(20)	Patron's password, in an encrypted format. Required.
Email	Text(100)	Patron's email address. Optional.
Phone	Text(20)	Patron's phone number. Optional.
Address	Text(50)	Patron's street address. Optional.
City	Text(20)	Patron's city. Optional.
State	Text(2)	Patron's state abbreviation. Optional.
Postal	Text(10)	Patron's postal code. Optional.
PatronGroup	Long	The group in which this patron appears. Foreign reference to CodePatronGroup.ID. Optional.

**PatronCopy** - This table manages item copies currently checked out by a patron, or item copies that have been previously checked out and have since been returned.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
Patron	Long	The associated patron. Foreign reference to Patron.ID. Required.
ItemCopy	Long	The item copy currently or previously checked out by the patron. Foreign reference to ItemCopy.ID. Required.
CheckOut	Date	The date when this item copy was initially checked out. Required.
Renewal	Integer	The number of times this item copy has been renewed. Set to 0 when the item copy is first checked out. Required.
DueDate	Date	Current due date for this item copy. Required.
CheckIn	Date	The date when this item copy was returned. Optional.
Returned	Boolean	Has the item copy been returned? 0 for False, 1 for True. Required.
Missing	Boolean	Is the item copy missing and considered lost? 0 for False, 1 for True. Required.
Fine	Currency	Total fine accumulated for this item copy. Defaults to 0.00. An administrator may reduce an accumulated fine. Required.
Paid	Currency	Total amount paid (in fees) for this item copy. Required.
ProcessDate	Date	When an item copy is processed for overdue fines, this field contains the last date for which processing was done. Optional.

**PatronPayment** - Fines, payments, and dismissals on a patron copy record. Overdue fines are not recorded in this table, but administrator-initiated fines due to charges for missing items are recorded here.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
PatronCopy	Long	The associated patron. Foreign reference to PatronCopy.ID. Required.
EntryDate	Date	Date and time when this entry was recorded. Required.
EntryType	Text(1)	The type of payment entry. Required. The possible values are: <ul style="list-style-type: none"> <li>• "P" - The patron made a payment.</li> <li>• "F" - A fine (other than a standard overdue fine) was imposed by</li> </ul>

Field	Type	Description
		an administrator. • “D” - A portion (or all) of the fine was dismissed. • “R” - A refund was given to the patron due to overpayment.
Amount	Currency	The amount associated with this entry. The value is always positive. Required.
Comment	Text(50)	A short comment about this entry. Optional.
UserID	Long	The user who added this payment event. Foreign reference to UserName.ID. Optional.

**Publisher** - An organization that publishes books or some other type of media.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(100)	Name of the publisher. Required.
WebSite	Text(255)	URL for this publisher’s web site. Optional.

**Subject** - Subject headings used to classify named items.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(150)	Name of this subject. Required.

**SystemValue** - This table stores miscellaneous enterprise-wide settings that apply to every workstation. Local workstation-specific settings are stored on each machine, not in the database.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
ValueName	Text(50)	Name of this value. Required.
ValueData	Text(100)	Information associated with this entry. Optional.

The following system values are defined at this time. The name of the code appears in the *ValueName* field. The corresponding value appears in the *ValueData* field.

- **BarcodeCode39** - Is the specified barcode in “code 39” or “code 3 of 9” format? If so, an asterisk will be placed before and after the barcode number before it is printed on a label. Use a value of 0 for False, or any non-zero value for True (-1 is preferred). If missing or NULL, False is assumed.
- **BarcodeFont** - The name of the font used to print barcodes. This font must be installed on any workstation that displays or prints barcodes. It is not needed to scan barcodes.
- **DatabaseVersion** - Which structural version of the database is currently in use? Right now it is set to “1,” and is reserved for future enhancement.
- **DefaultLocation** - CodeLocation.ID value for the location that is set as the default.
- **FineGrace** - Number of days that an item can be overdue without incurring a fine.
- **Licensee** - The name of the person or organization authorized to use this copy of the system.
- **LicenseCode** - An encrypted value that matches the license code.
- **NextBarcodeItem** - The next starting value to use when printing item barcodes.
- **NextBarcodeMisc** - The next starting value to use when printing miscellaneous barcodes.
- **NextBarcodePatron** - The next starting value to use when printing patron barcodes.
- **PatronCheckOut** - Indicates whether patrons can check out items without being logged in as an administrative user. Use a value of 0 (zero) to indicate no check out privileges, or any non-zero value to allow patron check out (-1 is preferred). If this value is missing or empty, patrons will not be allowed to check out items without administrator assistance.
- **SearchLimit** - Indicates the maximum number of results returned in any search or lookup. If this value is missing or invalid, a default of 250 is used. The allowed range is between 25 and 5000, inclusive.
- **TicketHeading** - Display text to be printed at the top of check-out tickets. All lines are centered on the ticket. Include the vertical bar character (“|”) to break the text into multiple lines.
- **TicketFooting** - Display text to be printed at the bottom of check-out tickets. All lines are centered on the ticket. Include the vertical bar character (“|”) to break the text into multiple lines.



- **UseLC** - Indicates whether books are categorized by Dewey or by Library of Congress (LC) call numbers. Use a value of 0 (zero) to indicate Dewey, or any non-zero value for LC (-1 is preferred). If this value is missing or empty, Dewey is assumed.

**UserName** - This table contains the actual records for each librarian or administrator. Each record includes the user's password and security group setting.

Field	Type	Description
ID	Long - Auto	Primary key, automatically assigned. Required.
FullName	Text(50)	Name of this user, administrator, or librarian. Required.
LoginID	Text(20)	User ID that gives this user access to the system. It is entered into the Library program's "login" form, along with the password, to gain access to enhanced features. Required.
Password	Text(20)	The password for this user, in an encrypted format. Optional.
Active	Boolean	Is this user allowed to access the system? 0 for False, 1 for True. Required.
GroupID	Long	To which security group does this user belong? Foreign reference to GroupName.ID. Required.