

# Index

- Accountability, 398–399
  - Acousto-optic switches, 18
  - Add-drop multiplexers (ADM), 14
  - Adjacencies, 166–171
    - control, 171
    - layer, 167–170
    - physical media, 170
  - Alarm indication signals (AIS), 79
  - Alarms, 407–408
    - notification types, table, 408
  - Alignment monitoring, 78
    - frame alignment and loss of frame (LOF), 78
    - loss of multiframe, 78
    - pointer processing and loss of pointer (LOP), 78
  - Amplifier spontaneous emission (ASE), 320
  - APS commands, 107
  - Arbitrary concatenation in SONET/SDH, 54–55
  - Area local flooding, 324
  - Assessing security, 399
  - Asynchronous transfer mode (ATM) networks, 158–163, 296
    - P-NNI protocols, 158–163
      - addressing and identification, 161–163
      - hierarchy, 158–160
  - Attenuation, 2–3
  - Autonomous system (AS) wide flooding, 324
  - Availability, 399
  - Available capacity, 319
  - Avalanche Photodiode (APD), 7
  
  - Bandwidth constraints, routing with, 352–355
  - Batch processing, 363–364
  - Bellman-Ford algorithm, 348–349
    - example, 349
  - Bidirectional line switched rings (BLSRs), 114–122
    - four fiber (4F-BLSRs), 115–118
      - operations, 120–122
      - service classes in, 119–120
    - two fiber (2F-BLSRs), 114
  - Bidirectional 1+1 protection, 277–278
  - Bit error rate (BER), 9, 43, 347
  - Broadband cross-connects, 13–14
  - Building integrated timing supply (BITS), 38
  
  - Cable (conduit) diversity, 316
  - Chromatic dispersion, 2, 3
  - Client/server layer networks, 136
  - Common management information protocol (CMIP), 414
  - Concatenation, 52–60
    - arbitrary, 54–55
    - standard signals, 53–54
    - virtual, 55–60
  - Confidentiality, 399
  - ConfigAck message, 192–193
  - Config message exchange, 191–192
  - Connectionless network protocol (CLNP), 309
  - Connection provisioning, signaling for, 203–266
    - GMPLS RSVP-TE, 243–259
      - connection deletion under, 255–258
      - connection establishment under, 252–255
      - notify message, 252
      - objects, 244–252
      - restart procedures, 258
      - signaling at the UNI and the NNI, 258–259
    - GMPLS signaling, 214–223
      - basic signaling model, 215–217
      - encoding of SONET/SDH connection parameters, 221–223
      - labels, 218–220
    - ITU-T G.7713 model, 209–214
      - architectural aspects, 209–214
        - defining the G.7713 model, 209
        - overview of, 204–209
      - P-NNI signaling adaptations for optical networks, 259–265
        - connection establishment/deletion, 262–265
        - designated transit list (DTL), 261–262
        - signaling protocol, 259–261
      - RSVP, 224–233
        - basic model, 224
        - deleting a reservation: PathTear and ResvTear, 231–232
        - establishing a reservation: path and resv, 228–230
          - messages and objects, 224–228
          - path and resv errors, and reservation confirmation, 232–233
          - refresh reduction, 243
          - soft state approach, 230–231
        - RSVP-TE, 233–243
          - establishing an LSP tunnel, 239–240
          - hello protocol, 242
          - objects, 233–239
          - removing an LSP tunnel, 242–243
          - soft state, 240–242
  - Control adjacency, 171
  - Control plane
    - architecture and functional model, 133–146
      - control plane functions, 144
      - data communications network (DCN), 145–146
        - network model and layering, 135–139
        - partitioning and control interfaces, 139–144
      - aspects in IP networks, 146–149
        - addressing, 147–148
        - discovery, 148–149
        - routing, 149
      - management systems relationship with, 415–419
        - accounting, performance, security management, 416
        - configuration management, 415–416
        - discovery and management, 416–417
        - fault management, 415
        - routing and management, 417–418
        - signaling and management, 418–419
        - optical, 423–430
    - CORBA based management, 414–415
  - Data communication channel (DCC) bytes, 185–186
    - neighbor discovery using, 185–186
  - Data communications network (DCN), 145–146
  - Data integrity, 399
  - Dense wavelength division multiplexing (DWDM), 4, 10–12
    - main functions, 12
    - systems, 10–12
  - Designated transit list (DTL), 261–262
  - Digital cross-connects and add/drop multiplexers, 13–14
  - Dijkstra's algorithm, 349–351
    - example, 351
  - Dispersion, 3
    - shifted fiber, 5–6
  - Distributed feedback (DFB) lasers, 7
  - Domain hierarchies, 379–386
    - diversity services and domain representation, 386–387
    - identification of components within a hierarchy, 383–386
      - BGP example, 384
      - operational issues arising from RA identifiers, 385–386
      - OSPF example, 383–384
    - relationship to signaling, 380
    - routing hierarchies, 380–382
- DS-1, 22–24
- 
- Electro-optic switches, 17–18
- End-to-end dedicated mesh protection, 277–281
  - bidirectional 1+1 protection, 277–278
    - functional description, 277–278
    - messages, 278–280
      - failure acknowledge, 279
      - failure indication, 279
      - switchover request, 279
      - switchover response, 279–280
    - signaling procedures, 280–281
      - failure indication and acknowledge, 280
      - provisioning the protection path, 280
      - switchover and response, 280–281
    - unidirectional 1+1 protection, 277
  - End-to-end shared mesh protection, 282–287
    - functional description, 282–284
    - messages, 284–285
      - reversion, 284–285
        - switchover request, 284
        - switchover response, 284
      - signaling procedures, 285–287
        - failure indication and acknowledge, 286
        - provisioning the protection path, 285–286
        - reversion, 287
        - switchover request and response, 286
- Erbium-Doped Fiber Amplifier (EDFA), 8
- Ethernet over SONET/SDH, payload mappings, 69
- Event dependent routing (EDR), 298
- Events and notifications, 407–410
  - alarms, 407–408
  - event logs, 410
  - event reporting control, 409–410
- Extended superframe (ESF), 24
- Exterior Network-Network Interface (E-NNI), 143
- 
- Fabry-Perot lasers, 7
- Fiber-switch capable interface, 318
- Four fiber bidirectional line switched ring (4F-BLSR), 115–118
- Four-wave mixing, 4
- 
- Generalized multi-protocol label switching (GMPLS), 155–158
  - encoding of SONET/SDH connection parameters, 221–223
  - labels carried in signaling messages, 218–220
    - port or wavelength, 218
    - sonet and SDH, 218–220
    - waveband, 218
  - link management, 156–157
  - overview, 155–156
  - routing, 157
  - RSVP-TE, 243–259
    - connection deletion under, 255–258
    - connection establishment under, 252–255
    - notify message, 252
    - restart procedures, 258
    - signaling at the UNI and the NNI, 258–259
  - RSVP-TE objects, 244–252
    - acceptable label set, 247
    - administrative status, 249
    - generalized label, 245
    - generalized label request, 244–245
    - interface identification, 249–252
    - label set, 246–247
    - notification request, 252
    - protection information, 248–249

- RSVP-TE objects (*cont'd*)
  - suggested label, 245–246
  - upstream label, 246
- signaling, 214–223
  - basic signaling model, 215–217
  - encoding of SONET/SDH connection parameters, 221–223
- Generic framing procedure (GFP), 65–69
  - frame structure, 67–68
    - core header, 67
    - payload area, 67–68
  - functions, 68–69
    - client/frame multiplexing, 68–69
    - client payload mapping, 69
    - frame delineation, 68
    - header/payload scrambling, 69
- Geographic route diversity, 317
- Global Positioning System (GPS), 39
- Hello protocol, 193, 242
- Higher-order virtual concatenation (HOVC), 56–58
- Higher-order virtual container layer, 45–46
- Information models, 401–411
  - events and notifications, 407–410
    - alarms, 407–408
    - event logs, 410
    - event reporting control, 409–410
  - managed objects, 401–406
    - containment, 402–404
    - inheritance, 404–406
    - relationships, 402
  - state, 406–407
- Interdomain control, 373–393
  - discovery processes and hierarchy, 392–393
    - interdomain discovery, 392–393
  - domain hierarchies, 379–386
    - diversity services and domain representation, 386–387
    - identification of components within a hierarchy, 383–386
      - relationship to signaling, 380
      - routing hierarchies, 380–382
  - interdomain routing, 387–392
    - information categorization, 387–390
    - routing within a hierarchy, 390–392
  - and management, 420
  - requirements, 375–379
    - administrative partitioning, 378
    - deployment and operations considerations, 378–379
    - intervendor interoperability, 376–377
    - scalability, 375–376
- Interdomain routing, 387–392
  - information categorization, 387–390
    - domain and node-related information, 390
    - topology and resource information, 388–389
  - routing within a hierarchy, 390–392
    - information flow down the hierarchy, 391–392
    - information flow up the hierarchy, 391
- Interface switching capabilities, 318
- Interior Network-Network Interface (I-NNI), 143
- International Telecommunications Union (ITU-T), 314, 427–428
  - G.7713 model, 209–214
    - architectural aspects, 209–214
    - call and connection control, 212–213
    - connection provisioning, 213–214
    - signaling interfaces and the control plane, 209–212
    - defining, 209
- Internet, routing in, 299–300
- Internet Engineering Task Force (IETF), 304, 314, 426–427
- Internet routing protocols, 305–311
  - interdomain, 310–311
    - BGP, 310–311
  - intradomain, 306–309
    - IS-IS, 309
    - OSPF, 306–309
    - RIP, 306
- Intervendor interoperability, 376–377
- Intradomain optical routing, 313–344
  - IP and optical routing, differences between, 314–316
    - link bundling, 321–322
    - optical intradomain routing, 323–330
      - routing in all-optical networks, 328–330
      - routing in a single area, 324–328
    - routing across multiple areas, 330–342
      - multiarea traffic engineering based on OSPF, 340–342
    - packet forwarding in IP networks, 330–333
    - provisioning in a multiarea network, 334–335
    - shared mesh protection in a multiarea network, 335–340
    - summarizing resource information, 333–334
  - routing with constraints, 317–320
    - link characteristics, 318–319
    - optical constraints, 319–320
  - routing with physical diversity, 316–317
  - source routing, 322
- IP and optical routing, differences between, 314–316
- IP routing protocols, 303–305
  - distance vector routing, 303–304
  - link state routing, 304–305
- JO-based neighbor discovery, 177–185
  - alternative usage of JO bytes, 182–183
    - with an out-of-band control channel, 179–181
  - multilayer, 184–185
    - without an out-of-band control channel, 181–182
- Label distribution protocol (LDP), 152–153
- Label switched paths (LSPs), 214
- Lambda-switch capable interface, 318
- Layer adjacency, 167–170
- Light-emitting diode (LED), 2, 6
- Linear 1:N protection, 100–101
  - group configuration, 101
  - intro to, 100
  - line parameters, 101
- Linear protection, 94–111
  - APS commands, 107
  - benefit of, 95–96
  - detecting failure, 96
  - extra traffic, 99
  - linear subnetwork connection protection, 107–110
    - reversion, 99
  - SDH/SONET linear 1:N protection, 100–101
  - SONET/SDH K1/K2 linear APS (LAPS) protocol, 101–106
  - SONET/SDH line protection, 100
  - theoretical underpinning of, 99–100
  - types of, and communication requirements, 96–98
- Linear subnetwork connection protection, 107–110
  - 1+1 protection, 108–109
  - virtual 1:N, 109–110
- Line layer performance parameters, 87
- Line terminating equipment (LTE), 47
- Link, 136, 318–319
  - bundling, 321–322
  - characteristics, 318–319, 325
    - encoding/switching/capability/and capacity availability, 318–319
    - protection capabilities, 319
    - of a single component link, 325
  - connection (LC), 136–137
  - diverse routing algorithms, 356–357
    - nonoptimal disjoint paths via pruning, 356–357
  - encoding, 318
  - local flooding, 323
    - protection constraints, routing with, 352
  - resource manager (LRM), 382
- Link capacity adjustment scheme (LCAS), 60–63
- Link management protocol (LMP), 187–201
  - control channels, 187–189
    - in-fiber over SONET/SDH DCC bytes, 188
    - out-of-fiber, 189
  - neighbor discovery examples, 193
  - usage with OEO cross-connects (OXCs), 189–195
    - basic LMP parameters, 190–191
    - link connectivity verification, 191
    - link property correlation, 194–195
  - usage with photonic cross-connects (PXCs), 195–201
    - complexity of complete link identification, 201
    - link connectivity verification, 196–197
    - link property correlation, 201
    - procedure, 197–200
- Link state advertisement (LSA), 304, 306–307
  - types of, 306–307
- Liquid crystal optical switches, 19–20
- Localization and signal maintenance, 79–81
- Loss of frame (LOF), 78
- Loss of pointer (LOP), 78
- Lower-order virtual concatenation (LOVC), 58–60
  - capabilities/limitations, 58
  - implementation, 58–60
- Mach-Zehnder interferometer, 18, 119
  - figure of, 119
- Magneto-optic switches, 19
- Management systems, 395–421
  - information models, 401–411
    - events and notifications, 407–410
    - managed objects, 401–406
    - state, 406–407
  - interdomain control and management, 420
  - protocols for systems management, 411–415
    - common management information protocol (CMIP), 414
    - CORBA based management, 414–415
    - simple network management protocol (SNMP), 413–414
    - transaction language 1 (TL1), 411–413
  - relationship with the control plane, 415–419
    - discovery and management, 416–417
    - FCAPS and the control plane, 415–416
    - routing and management, 417–418
    - signaling and management, 418–419
  - transport systems management, 396–400
    - functionality provided by management systems, 396–399
    - levels of system management, 400
- Material dispersion, 3
- Mesh protection, 277–287
  - end-to-end dedicated, 277–281
  - end-to-end shared, 282–287
- Mesh restoration, 126–129
  - bandwidth efficiency of, 126–128
  - end-to-end source rerouted, 128–129
- Micro-electro-mechanical systems (MEMS), 16–17
- Modern optical network control plane, 131–163
  - control of ATM networks: P-NNI protocols, 158–163
    - addressing and identification, 161–163
    - P-NNI hierarchy, 158–160
  - control of MPLS networks, 149–154
    - label distribution, 151–153
    - MPLS-TE routing, 154
    - MPLS traffic engineering (MPLS-TE), 153–154
    - overview of MPLS, 149–151
    - recovery in MPLS networks, 154

- control plane architecture and functional model, 133–146
  - control plane functions, 144
  - data communications network (DCN), 145–146
  - network model and layering, 135–139
  - partitioning and control interfaces, 139–144
- control plane aspects in IP networks, 146–149
  - addressing, 147–148
  - discovery, 148–149
  - routing, 149
- generalized MPLS (GMPLS), 155–158
  - link management, 156–157
  - overview, 155–156
  - routing, 157
  - signaling, 157–158
- Multiarea traffic engineering based on OSPF, 340–342
- Multicommodity flow: mathematical formulation, 365–366
- Multimode optical fiber, 5
- Multiplexing, grooming, and switching, 12–20
  - digital cross-connects and add/drop multiplexers, 13–14
  - OOO switch fabrics, 15–20
- Multiplex section layer, 45
- Multi-Protocol Label Switching (MPLS) networks, 149–154
  - control of, 149–154
  - label distribution, 151–153
  - overview of, 149–151
  - recovery in, 154
  - traffic engineering (MPLS-TE), 153–154
  - routing, 154
- Neighbor discovery, 165–202
  - adjacencies and discovery procedures, 166–176
    - control adjacency, 171
    - layer adjacency, 167–170
    - neighbor discovery procedures, 171–176
    - physical media adjacency, 170
  - defining, 166
  - LMP, 187–201
    - control channels, 187–189
    - usage with OEO cross-connects (OXCs), 189–195
    - usage with photonic cross-connects (PXC), 195–201
  - and management, 416
  - protocol mechanisms, 176–187
    - link property correlation, 186–187
    - neighbor discovery using the DCC bytes, 185–186
    - neighbor discovery using the JO byte, 177–185
- Network connection, 138
- Network optimization, 361–372
  - batch processing, 363–364
  - formulating and solving multicommodity optimizations, 366–372
  - multicommodity flow: mathematical formulation, 365–366
  - shortest path: mathematical formulation, 364
- Non-dispersion-shifted fiber, 5–6
- Nonlinear effects, 2, 4
- Non-zero dispersion-shifted fiber, 5–6
- On-off-keying (OOK), 9
- OOO (photonic) switch fabrics, 15–20
  - acousto-optic switches, 18
  - electro-optic switches, 17–18
  - liquid crystal optical switches, 19–20
  - magneto-optic switches, 19
  - opto-mechanical switches, 16–17
  - thermo-optic switches, 18–19
- Opaque optical switches (OEO), 12–13
- Open Shortest Path First (OSPF), 304, 340–342, 383–384
  - multiarea traffic engineering based on, 340–342
- Open system interconnection (OSI), 309
- Optical amplifiers (OAs), 8
- Optical carrier level 1 (OC-1) signal, 25
- Optical control plane internetworking, 423–430
  - business drivers and inhibitors, 424–425
  - deployment issues, 429–430
  - interoperability status, 428–429
  - standards, differences in, 425–428
    - International Telecommunication Union (ITU-T), 427–428
    - Internet Engineering Task Force (IETF), 426–427
    - Optical Internetworking Forum (OIF), 427
- Optical fiber, 4–6
  - multimode, 5
  - single-mode, 5
- Optical Internetworking Forum (OIF), 314, 427
- Optical intradomain routing, 323–330
  - routing in all-optical networks, 328–330
  - routing in a single area, 324–328
- Optical transmission systems, 2–12
  - attenuation, 3
  - characterizing optical signals and performance, 9–10
  - dispersion, 3
  - DWDM systems, 10–12
  - nonlinear effects, 4
  - optical fiber, 4–6
  - optical transmitter and receivers, 6–7
  - overview, 2
  - regenerators, repeaters, and optical amplifiers, 7–9
- Optical transmitter and receivers, 6–7
- Opto-mechanical switches, 16–17
- Packet forwarding in IP networks, 330–333
- Partitioning and control interfaces, 139–144
- Path layer performance parameters, 87–88
- Path selection for diversity, 355–361
  - link diverse routing algorithms, 356–357
  - shortest link diverse paths algorithm, 357–361
- Path terminating equipment (PTE), 45, 47
- Payload envelopes and virtual containers, 27–35
- Payload mappings, 63–69
  - Ethernet over SONET/SDH, 69
  - generic framing procedure (GFP), 65–69
  - IP over ATM over SONET, 63–64
  - packet over SONET/SDH, 64–65
- Peer group identifiers (PGIDs), 311
- Performance measures, 85–88
  - line layer, 87
  - path layer, 87–88
  - physical layer, 86
  - section layer, 86–87
- Photodetectors, 7
- Physical media adjacency, 170
- Polarization mode dispersion (PMD), 3–4, 320
- Positive-intrinsic-negative (PIN) photodiode, 7
- Preemptible link, 319
- Private network-network interface (P-NNI), 158–163
  - addressing and identification, 161–163
  - hierarchy, 158–160
  - routing, 311–312
  - signaling adaptations for optical networks, 259–265
    - connection establishment/deletion, 262–265
    - designated transit list (DTL), 261–262
    - signaling protocol, 259–261
- Problem localization and signal maintenance, 79–81
  - alarm indication signals, 79
  - remote defect indication, 79–81
- Protected link, 319
- Protection. *see* Linear protection; Mesh protection; Ring-based protection
- Protection and restoration, signaling for, 267–293
  - discussion, 287–292
    - performance aspects and MPLS fast reroute, 287–291
    - restoration, 291–292
  - end-to-end dedicated mesh protection, 277–281
    - bidirectional 1+1 protection, 277–278
    - messages, 278–280
    - signaling procedures, 280–281
    - unidirectional 1+1 protection, 277
  - end-to-end shared mesh protection, 282–287
    - functional description, 282–284
    - messages, 284–285
    - signaling procedures, 285–287
  - span protection, 270–277
    - functional description, 270–273
    - messages, 273–274
    - preventing unintended connections, 275
    - reversion, 275
    - signaling mechanisms, 275–277
- Protection and restoration techniques, 91–94, 130
  - bandwidth efficiency, 92–93
  - interoperability, 94
  - methods, properties of, 130
  - recovery time, 93–94
  - reliability/robustness of, 92
- Protocols for systems management, 411–415
- common management information protocol (CMIP), 414
- CORBA based management, 414–415
- simple network management protocol (SNMP), 413–414
- transaction language 1 (TL1), 411–413
- Provisioning in a multiarea network, 334–335
- Quality monitoring, 82–84
  - BLIPS and BIPS, 82–84
- Quality of service (QoS), 309
- Rayleigh scattering, 3
- Refractive index, 4
- Regenerators, repeaters, and optical amplifiers, 7–9
- Regenerator section layer, 43–45
  - scrambling, 43–45
- Remote defect indication (RDI), 79–81
- Remote error monitoring, 84
- Restoration, 291–292; *see also* Mesh restoration; Protection and restoration
- Right of way (ROW) diversity, 317
- Ring-based protection, 111–125
  - BLSRs (bidirectional line switched rings), 114–122
    - intro/background, 111
    - protection cycles, 124–125
    - software defined BLSRs, 122
    - theoretical background on rings, 111–112
    - transoceanic rings, 123–124
  - USPRs (unidirectional path switched rings), 112–113
- Route computation and path selection, 345–372
  - network optimization, 361–372
    - batch processing, 363–364
    - formulating and solving multicommodity optimizations, 366–372
    - multicommodity flow: mathematical formulation, 365–366
    - shortest path: mathematical formulation, 364
  - path selection for diversity, 355–361
    - link diverse routing algorithms, 356–357
    - shortest link diverse paths algorithm, 357–361
  - routing with simple constraints, 352–355
    - bandwidth constraints, 352–355
    - link protection example, 352
  - shortest path computation, 347–352
    - Bellman-Ford algorithm, 348–349
    - comparison of algorithms, 352, 351
    - Dijkstra's algorithm, 349–351

- Routing, 295–312
    - across multiple areas, 330–342
      - multiarea traffic engineering based on OSPF, 340–342
    - packet forwarding in IP networks, 330–333
    - provisioning in a multiarea network, 334–335
    - shared mesh protection in a multiarea network, 335–340
    - summarizing resource information, 333–334
  - area (RA), 381–382
  - with constraints, 317–320
    - link characteristics, 318–319
    - optical constraints, 319–320
  - control domain (RCD), 382
  - controller (RC), 381
  - history of, 296–300
    - routing in the internet, 299–300
    - routing in the telephone network, 297–299
  - interdomain, 387–392
    - information categorization, 387–390
    - routing within a hierarchy, 390–392
  - internet routing protocols, 305–311
    - interdomain, 310–311
    - intradomain, 306–309
  - and management, 417–418
  - optical intradomain, 323–330
    - routing in all-optical networks, 328–330
    - routing in a single area network, 324–328
  - with physical diversity, 316–317
  - P-NNI, 311–312
  - protocol basics, 301–305
    - IP routing protocols, types of, 303–305
    - routing and forwarding, 301
    - routing design tenets, 301–302
  - with simple constraints, 352–355
    - bandwidth constraints, 352–355
    - link protection example, 352
- RSVP, 224–233
  - basic model, 224
  - deleting a reservation: PathTear and ResvTear, 231–232
  - establishing a reservation: path and resv, 228–230
  - messages, 224–225
  - objects, 225–228
    - Filterspec, 227–228
    - Flowspec, 227
    - sender template, 226
    - sender Tspec, 227
    - session, 225–226
  - path and resv errors, and reservation confirmation, 232–233
  - refresh reduction, 243
  - soft state approach, 230–231
- RSVP-TE, 233–243
  - establishing an LSP tunnel, 239–240
  - GMPLS extensions to, 243–259
    - connection deletion under, 255–258
    - connection establishment under, 252–255
    - notify message, 252
    - objects, 244–252
    - restart procedures, 258
    - signaling at the UNI and the NNI, 258–259
  - hello protocol, 242
  - objects, 233–239
    - explicit route, 234–236
    - label, 234
    - label request, 234
    - LSP tunnel identification, 236–237
    - record route, 236
    - session attributes, 237–239
    - removing an LSP tunnel, 242–243
    - soft state, 240–242
- Scalability, 375–376
- SDH/SONET linear 1:N protection, 100–101
- Section layer performance parameters, 86–87
- Section Terminating Equipment (STE), 43, 47
- Self-phase modulation, 4
- Semiconductor lasers, 7
- Shared mesh protection in a multiarea network, 335–340
  - area-wise protection, 338–340
  - incremental protection path establishment, 337–338
  - protection path computation using route servers, 336–337
- Shared risk link group (SRLG), 316
- Shortest link diverse paths algorithm, 357–361
  - link disjoint path pair, 358–361
- Shortest path computation, 347–352
  - Bellman-Ford algorithm, 348–349
  - comparison of algorithms-352, 351
  - Dijkstra's algorithm, 349–351
  - mathematical formulation, 364
- Signaling, 203–266, 418–419
  - for connection provisioning, 203–266
  - and management, 418–419
  - for protection and restoration, 267–293
- Simple network management protocol (SNMP), 413–414
- Single-mode optical fiber, 5
- SONET/SDH, 21–49
  - concatenation, 52–60
    - arbitrary, 54–55
    - standard signals, 53–54
    - virtual, 55–60
  - connection parameters, GMPLS encoding of, 221–223
  - K1/K2 linear APS (LAPS) protocol, 101–106
  - layering, 42–49
    - higher-order virtual container layer, 45–46
      - multiplex section layer, 45
      - regenerator section layer, 43–45
      - tandem connection layer, 45
      - transparency, 47–49
      - VT path layer, 46–47
  - line protection, 100
  - link capacity adjustment scheme (LCAS), 60–63
  - payload mappings, 63–69
    - ethernet over SONET/SDH, 69
    - generic framing procedure (GFP), 65–69
    - IP over ATM over SONET, 63–64
    - packet over SONET/SDH, 64–65
  - problems, discovering the cause of, 75–88
    - localization and signal maintenance, 79–81
    - performance measures, 85–88
    - quality monitoring, 82–84
    - remote error monitoring, 84
    - transport problems and their detection, 76–78
  - signals, 24–42
    - basic signal types, 25–27
    - payload envelopes and virtual containers, 27–35
    - synchronous multiplexing, 35–42
  - terminology, correspondence between, table, 37
  - time division multiplexing (TDM), 22–24
  - transparency services, 70–75
    - methods for overhead transparency, 72–74
    - packages, 75
- SONET/SDH K1/K2 linear APS (LAPS) protocol, 101–106
  - bidirectional case, 104–105
  - reversion and wait to restore, 105–106
  - unidirectional case, 103
- Source routing, 322
- Span protection, 270–277
  - functional description, 270–273
  - messages, 273–274
    - failure indication, 273
    - switchover request, 273–274
    - switchover response, 274
- preventing unintended connections, 275
- reversion, 275
- signaling mechanisms, 275–277
- Splitting/merging areas, 385
- State-dependent routing (SDR), 298
- Subnetwork, 136
  - connection (SNC), 138
- Synchronous digital hierarchy (SDH), 26
- Synchronous multiplexing, 35–42
  - byte interleaving and frequency compensation, 38–42
  - SDH multiplex hierarchy, 36–38
  - SONET multiplex hierarchy, 35–36
- Synchronous payload envelope (SPE), 26–29
- Synchronous transport signal-level 1 (STS-1), 25–29
- Tandem connection terminating equipment (TCTE), 47
- Telephone network, routing in, 297–299
- Thermo-optic switches, 18–19
- Time dependent routing (TDR), 298
- Time division multiplexing (TDM), 22–24, 155
  - capable interface, 318
- Traffic engineering multi-protocol label switching (MPLS-TE), 153–154
- Trail, 138
- Trail termination function, 139
- Transaction language 1 (TL1), 411–413
  - basic command message format, 412–413
- Transparency, 47–49, 70–75
  - methods for overhead transparency, 72–74
  - service packages, 75
- Transparent optical switches. *see* OOO
- Transport network model and layering, 135–139
  - adaptation function, 138–139
  - client and server layer networks, 136
  - link, 136
  - link connection (LC), 136–137
  - network connection, 138
  - subnetwork, 136
  - subnetwork connection (SNC), 138
  - trail, 138
  - trail termination function, 139
- Transport problems and their detection, 76–78
  - alignment monitoring, 78
  - connectivity supervision, 76–77
  - continuity supervision, 76
  - signal quality supervision, 77–78
- Transport systems management, 396–400
  - functionality provided by management systems, 396–399
    - accounting, 397
    - configuration management, 397
    - fault management, 397
    - performance monitoring, 398
    - security management, 398
    - levels of system management, 400
- Tributary unit (TU), 37
- Two fiber bidirectional line switched ring (2F-BLSR), 114
- Ultraband cross-connects, 13–14
- Unidirectional path switched rings (UPSRs), 112–113
- Unprotected link, 319
- User Network Interface (UNI), 143
- Virtual concatenation, 55–60
  - higher order (HOVC), 56–58
  - lower order (LOVC), 58–60
- Virtual Containers (VCs), 27–35
- Virtual Tributaries (VTs), 31
- Waveguide dispersion, 3
- Wavelength Division Multiplexing (WDM), 10–12
  - narrowband, 10–11
  - wideband, 10
- Wideband cross-connects, 13–14