

NDEX

Α

AAL (ATM Adaptation Layer), 169, 172–173 ABR (Available Bit Rate), 173-175 access rates, case study, 56-60 access-list 101 command, 136 ACK (acknowledgement), 315 action policies, traffic, 47 active flows, 136 adaptability, TE tunnels, 253 adaptive FRTS, 188 adaptive traffic shaping, Frame Relay, 194 Address Resolution Protocol (ARP), 287 Address Extension (AE), 186 adjacency tables, 289 AE (Address Extension), 186 AF (Assured Forwarding), 25, 28 algorithms **MDRR**, 122 Nagle, 315 scheduling, 67-72 allocation bandwidth, 82, 91, 121-123 case study, 87 downstream label, 214 upstream label, 216 alternate priority mode, 115 application-level traffic, LFI, 319-321 application-specific integrated circuit (ASIC), 48 applications, 190 identification, 34 levels of QoS, 6 multicast, 147-151 policies, 282-283 RSVP, 148-152 approaches, TE, 258 architecture diffserv, 22-28 intserv, 21

ARP (Address Resolution Protocol), 287 ASIC (application-specific integrated circuit), 48 assignment of bandwidth per ToS class, 88 Assured Forwarding (AF), 25 Asynchronous Transfer Mode (ATM), 279 ATM (Asynchronous Transfer Mode), 172, 279 CLP bit based on IP Precedence, 185 differentiated services, 183-184 interworking, 178-179 Layer 2, 169-184 MPLS, 218 atm abr rate-factor 8 8 command, 175 ATM Adaptation Layer (AAL), 169 atm pvp configuration command, 176 atmpolicy Policy/Map information, 182 attacks denial-of-service, 51 smurf. 141–142 attributes available bandwidth, 253 link resource, 253 resource class, 253 TE path selection policies, 254 TE tunnels, 251-253 audio, 313 RSVP, 147-152 RTP header compression, 316 autoroute announce command, 268 Autosense, FRTS, 192, 194 available bandwith attribute, 253 Available Bit Rate (ABR), 173 average queue size computation, 131 avoidance, congestion, 13, 130-132 SPD, 139-140 TCP, 127-128

В

backbone routers, deployment, 291-297 Backward Explicit Notification (BECN), 54 bandwidth, 10, 316 allocation, 82 assignment per ToS class, 88 commands, 86 custom queuing, 94–97 end-to-end, 157-162, 240 higher allocation case study, 86 QoS-group classification case study, 91 TE tunnels, 251 BECN (Backward Explicit Notification), 54, 186-187 Frame Relay case study, 194–195 integration, 189 behavior PHB, 26–28 TCP. 129 Best-Effort service, 6 BGP (Border Gateway Policy), 35, 301, 307 bgp-policy destination ip-prec-map command, 309 bgp-policy source ip-prec-map command, 309 binding labels, 213-216 Border Gateway Protocol. See BGP boundaries network interfaces, 281 traffic conditioners, 25-26 bumping traffic, 179 burst size, 172 business-site FRTS configuration, 194 byte-by-byte round-robin GPS Scheduler simulation, 73-74 byters, 95

С

C/R (Command and Response), 186 caches, route-cache forwarding, 287–288 CAR (Committed Access Rate), 35, 279 configuring, 37, 40 rate-limiting function, 43-48 case studies, 183-184 ABR PVC. 175 ATM CLP bit based on IP Precedence, 185 bandwidth assignment per ToS class, 88 QoS-group classification, 91 for voice traffic, 121-123 class-based MWRR scheduling, 113-114 congestion avoidance, 133-135 differentiated IP packet discards, 180 downstream label ditribution, 219–222 enforcing public exchange point traffic, 52 - 53flow-based WFQ, 80-82 fragmentation (Frame Relay), 199 Frame Relay adaptive traffic shaping, 194 FRTS with Autosense, 192 high bandwidth, 86 IP Precedence, 41 limiting traffic, 48-50 mapping Frame Relay, 198 minimum interface bandwidth with different protocols, 95–98 MPLS CoS, 225–227 TE tunnel configuration, 258–272 VPN QoS, 240-241 multiple PVCs (Frame Relay), 196, 198 packets classification, 37-39 prioritization, 93 per-VC WFQ (Frame Relay), 198 preventing denial-of-service attacks, 51

priority queuing, 92 RSVP, 157-163 smurf attacks, 141-142 subrate IP services, 50 traffic shaping, 56-61 VP traffic shaping, 176 WFO scheduling, 82-83 CBFWO (Class-Based Weighted Fair Queuing), 76, 89-91, 319 CBR (Constant Bit Rate), 172–173 CDP (Cisco Discovery Protocol), 303 CDR (Committed Delivery Rate), 237 CE (Congestion Experienced), 139 CEF (Cisco Express Forwarding), 13, 287 backbone routers, 291-297 Cell Loss Priority (CLP), 171 route-cache switching, 297-298 CIR (Committed Information Rate), 187, 237 Cisco Discovery Protocol (CDP), 303 Cisco Express Forwarding. See CEF **Class Based Weighted Fair Queuing** (CBWFO), 76, 89-91, 319 class-based distributed WFQ, 89-91 class-based MWRR scheduling, 113 class-based WFQ, 85-86 class-map configuration command, 279 classes, 172-173 bandwidth assignment per ToS class, 88 MWRR ToS allocation, 112–113 traffic, 280 classification, packets, 34-39 classifiers, 12, 26 packets, 12 CLI (command line interface), 279 CLP (Cell Loss Priority), 171 coloring packets, 34 Command and Response (C/R), 186 command line interface (CLI), 279 commands, 142, 193, 268 access-list 101, 136 atm abr rate-factor, 175 atm pvp, 176 bgp-policy source ip-prec-map, 309

class-map, 86, 279 cos-queue group cos-a, 122 de-group, 199 de-list, 199 fair-queue, 86, 158 fair-queue interface, 80 fair-queue gos-group, 91 frame-relay fragment, 200 frame-relay priority-dlci-group, 196 ip cef, 219, 294 ip local policy route-map, 306 ip policy route-map, 306 ip route-cache flow accelerate, 303 ip rsvp resrvation, 159 ip rsvp sender, 158 ip rtp priority, 99, 200 ip spd headroom, 142 ip spd mode aggressive, 142 ip tcp path-mtu-discovery, 316 map, 295 match, 305 match access-group 101, 136 max-reserved bandwidth, 99 mpls traffic-eng attribute-flag 0x1, 264 mpls traffic-eng tunnels, 259 no mpls ip propagate-ttl, 218, 272 policy-map, 281 policy-map wred, 136 ppp mulitlink, 321 ppp multilink fragement-delay 20, 321 ppp multilink interleave, 321 priority keyword, 100 qos switching, 114 random-detect, 134 random-detect flow, 138 random-detect flow average-depth-factor 6,138 random-detect flow count, 138 req-qos guaranteed-delay, 163 route-map, 280 route-target import 200;1, 233 rx-cos slot, 122 service nagle, 315

service-policy, 182, 282 service-policy output febandwidth, 87 set, 305 shape average, 58 show, 49, 304 show atm vc, 177 show atm vp, 176 show atm vp 2, 177 show class, 86 show controllers fefab/tofab cos-queue length/parameters/variables, 123 show frame-relay pvc, 196 show frame-relay gos-autosense, 193 show interface Hssi0/0/0, 143 show interface rate, 49 show interface shape, 58 show interface tunnel0, 266 show interfaces switching, 143 show ip cache verbose, 293 show ip cef 222.222.222.3 internal, 268 show ip policy, 305 show ip route, 292 show ip routre vrf green, 232 show ip rsvp installed, 161–162 show ip rsvp interface, 160 show ip rsvp neighbor, 161 show ip rsvp request, 161 show isis mpls traffic tunnel, 266 show isis mpls traffic-eng advertise, 267 show mpls forwarding-table, 220–221 show mpls idp bindings, 220 show mpls idp parameters, 221 show mpls traffic-eng tunnel tunnel0, 263-264 show policy, 86 show policy-map, 182 show queue, 81 show queue interface, 81 show queue s0, 162 show queue serial0, 87 show queueing custom, 97 show queueing fair, 82 show queueing priority, 93, 197

show queueing random-detect, 134, 138 show route-map tasman, 305 show traffic-shape statistics, 58 show-traffic shape, 193 shpae peak, 58 slot-table cos, 122 table-a slot-table cos, 122 traffic-shape fecn-adapt, 190 traffic-shape_adaptive, 190 tunnel mode mpls traffic-en, 259 tunnel mpls traffic-eng autoroute announce, 268 tunnel mpls traffic-eng record route, 264 tx-queue-limit, 78 vofr. 200 Committed Access Rate (CAR), 35, 279 Committed Delivery Rate (CDR), 237 Committed Information Rate (CIR), 187, 237 Common Open Policy Service (COPS), 30 comparisons, CEF switching/route-cache switching, 297-298 components control, 213-216 forwarding, 212 **RSVP**, 150 compression, RTP headers, 316 computation, 131 conditioners, network boundary traffic, 25–26 conferencing RSVP, 147-152 configuration ABR PVC, 175 ATM CLP bit based on IP Precedence, 185 business-site FRTS, 194 CAR, 37-38 CoS. 123 FRTS with Autosense, 193 IP Precedence case study, 41 **IP-ATM QoS interworking**, 181 MLPP link-layer fragmentation, 321 multiple PVC bundles, 184 per-VC WFO, 198 QoS-based DWFQ, 90 **QPPB**, 40

RSVP-related, 159 TE tunnel, 258–272 voice traffic, 121-123 confirm-action statement, 47 congestion avoidance, 13 ECN, 139 enhancing link utilization with WRED, 133-135 Frame Relay, 186–187 RED, 130-132 support, 67-70, 72 TCP, 127-128 Congestion Avoidance Policy, 121–123 Congestion Experienced (CE), 139 connections performance, 9, 11 TCP (Nagle Algorithm), 315 traffic shaping, 56, 58-60 Constant Bit Rate (CBR), 172–173 contract restrictions, VP shaping, 174 control Frame relay congestion, 186–187 MPLS, 211-217 controlled load service, 155 conversation queues, 80 COPS (Common Open Policy Service), 30 core network interfaces, 282 CoS configuring, 123 MPLS case study, 225–227 cos-queue group cos-a command, 122 critical traffic, higher bandwidth allocation, 86-87 CU (currently unused), 24 currently unused (CU), 24 custom queuing, 94-100

D

data terminal equipment (DTE), 187 data-link connection identifier (DLCI), 185 DCEF (Distributed Cisco Express Forwarding), 83, 291 DE (Discard Eligible), 186-187, 198 Deficit Round Robin (DRR), 84, 106 definitions policies, 281 traffic class, 280 QoS policies, 279 TE trunks, 251 de-group command, 199 de-list command, 199 deleting labels, 222 denial-of-service attacks, preventing, 51 deploying CEF backbone routers, 291–297 designated SBM (DSBM), 204 differentiated IP packet discards, 180 differentiated MPLS VPN QoS, 237-238 Differentiated Service Code Point (DSCP), 279 differentiated services, ATM case study, 183-184 differentiated services byte (DS byte), 22 Differentiated Services Code Point (DSCP), 12.22 - 28diffserv architecture, 22-28 Discard Eliglible (DE), 186-187 discard strategies, cells, 173-174 distinct reservations, 152 Distributed Cisco Express Forwarding (DCEF), 83, 291 Distributed Traffic Shaping (DTS), 55 distributed WFQ (DWFQ), 83-85 distribution downstream label case study, 219-222 local link resource information, 254

DLCI (data-link connection identifier), 185 domains, 22 downstream label allocation, 214 drop probability, 132–135 dropper function, 26 DRR (Deficit Round Robin), 84, 106 DS byte (differentiated services byte), 22 DSBM (designated SBM), 204 DSCP (Differentiated Services Code Point), 12, 22, 85, 323–325 DTE (data terminal equipment), 187 DTS (Distributed Traffic Shaping), 55 DWFQ (distributed WFQ), 83–84 QoS-based, 90 ToS-based, 89–90

Ε

early packet discard (EPD), 173-174 ECN routers, 139 EF (Expedited Forwarding), 25 EIR (Excess Information Rate), 187 election, DSBM, 205 enabling Frame relay fragmentation, 199 Nagle Algorithm, 315 Path MTU Discovery, 316 polices, 282-283 encapsulation, labels, 216-217 end-tend guaranteed bandwith, 240 end-to-end bandwidth, reserving with, 157-160, 162 end-to-end IP QoS, 225 end-to-end QoS, 15 enforcing IP Precedence setting case study, 41 public exchange point traffic, 52-53 engineering traffic, 214 enhancing link utilization with WRED, 133-135 Enterprise Resource Planning (ERP), 190 EPD (early parket discard), 173–174

ER-LSP (Explicitly Routed Label Switched Path), 255 ERP (Enterprise Resource Planning), 190 exceed-action statement, 47 Excess Infromation Rate (EIR), 187 execution, order of policies, 284 expanded traffic capability, LANs, 200–203 Expedited Forwarding (EF), 25 Explicitly Routed Label Switched Path (ER-LSP), 255 extensions IGP routing protocol, 257 RSVP, 205

F

fair allocation schemes, 69–70 Fair Queuing (FQ), 67 fair-queue command, 86, 158 fair-queue interface command, 80 fair-queue qos-group command, 91 fast switching, 287 FCS (Frame Check Sequence), 186 FDDI (Fiber Distributed Data Interface), 52 FECN (Forward Explicit Congestion Notification), 54, 186–187 Frame Relay case study, 194–195 integration, 189 FF (Fixed Filter), 152 Fiber Distributed Data Interface (FDDI), 52 FIFO (first-in, first-out), 9, 68–69 File Transfer Protocol (FTP), 6, 155, 283 first-in, first-out (FIFO), 9, 68-69 Fixed Filter (FF), 152 flow WRED, 136-138 flow-based DWFQ (distributed WFQ), 83-85 flow-based WFQ, 75-78 case study, 80–82 strict priorty queue for voice, 100 FlowSpec, 152 formats, ATM cells, 169-170

Forward Explicit Congestion Notification (FECN), 54 forwarding CEF, 289 MPLS, 211-212, 214-217 route-cache, 287-288 FO (Fair Oueuing), 67, 73 FRAD (Frame Relay Access Device), 190 fragmentation Frame Relay, 190–191, 199 LFI, 319 sizes, 320 Frame Check Sequence (FCS), 186 Frame Relay, 185–199 fragmentation, 190-191 interwoking, 192 traffic shaping, 60-61 Frame Relay Access Device (FRAD), 190 Frame Relay Forum (FRF), 190 Frame Relay Traffic Shaping (FRTS), 187– 189, 279 Frame Relay virtual circuit (VC), 279 frame-relay fragment command, 200 frame-relay priority-dlci-group command, 196 frame relay qos-autosense, 193 frame-relay gos autosense command, 193 frame-relay traffic-shaping, 193 frame-relay traffic-shaping command, 193 FRF (Frame Relay Forum), 190 FRTS (Frame Relay Traffic Shaping), 192, 279 FTP (File Transfer Protocol), 82-83, 155, 283 functional blocks in diffserv architecture, 22 functions, 12. See also commands congestion avoidance, 13 dropper, 26 identification, 34-35 LFI (Link Layer and INterleaving), 319-321 metering, 26 packet classifier and marker, 12

policing, 42 QoS Signaling Protocol, 13 rate-limiting, 43–48 resource allocation, 12 routing, 13 shaper, 26 shaping, 42 switching, 13

G

GB (guaranteed bandwidth), 240 generalized processor sharing (GPS), 71–72 Generic Traffic Shaping (GTS), 55, 279 global synchronization, 129 goldservice, 86 GPS (generalized processor sharing), 71–73 GTS (Generic Traffic Shaping), 55, 279 guaranteed bandwidth (GB), 240 guaranteed bit rate service, 155 guaranteed QoS, 238–239 guaranteed services, 7

Η

hard QoS, 7 head-end router, 255 headers, 316 HEC (Header Error Control), 171 hierarchical policies, 283 high bandwidth allocation case study, 86 High-Speed Serial Interface (HSSI), 37, 88 histories, 8–9 holding priorities, TE tunnels, 251 hosting, Web services, 51 HSSI (High-Speed Serial Interface), 37, 88

L

ICMP (Internet Control Message Protocol), 51 identification function, 34-35 IEEE (Institute of Electronic Engineers), 14, 200-203 IETF (Internet Engineering Task Force), 9, 21 IGPs (Interior Gateway Protocols), 257, 302 ILMI (Interim Local Manement Interface), 179 implementation MDRR, 119, 121 MWRR, 112-113 queuing, 68 traffic measurement, 44, 54 WFQ, 79-80 incoming traffic, 307–309 initialization, SBM, 204 input, interface queues, 119 Institute of Electronic Engineers (IEEE), 14, 200 - 203integrated services, 155 Integrated Services (intserv), 9 Integrated Services over Specifiuc Lower Layers (ISSLL), 203 integration, BECN/FECN, 189 interfaces network boundary, 281 policies, 282 virtual-template, 321 Interim Local Management Interface (ILMI), 179 Interior Gateway Protocols (IGPs), 302 Intermediate System-to-Intermediate System (IS-IS), 302 Internet Control Message Protocol (ICMP), 51 Internet Engineering Task Force (IETF), 9, 21 Internet Router (IR), 303 Internet service provider (ISP), 113, 291 inter-policy feature ordering, 284

interworking ATM, 178-179 Frame Relay, 192 intra-feature execution orders, 284 intserv, 9, 21 IP (Internet Protocol), 30 flow-based WFO, 75-78 Precedence, 34–35, 323–325 case study, 37-41 **DSCP**, 36 limiting traffic, 49–50 mapping Frame Relay DE bits, 198 **OPPB**, 39 networks, 302-303 priority queuing case study, 92 OoS history, 8-9 services, 50 ip cef command, 219, 294 ip local policy route-map command, 306 ip policy route-map command, 306 ip priority queue, 142 ip route-cache flow accelerate command, 303 ip rsvp reservation command, 159 ip rsvp sender command, 158 ip rtp priority command, 99, 200 ip spd headroom command, 142 ip spd mode aggressive command, 142 ip tcp path-mtu-discovery command, 316 IR (Internet Router), 303 IS-IS (Intermediate System-to-Intermediate System), 302 **IS-IS** modifications, 258 ISP (Internet service provider), 113, 291 backbone, 240 CEF based packet forwarding, 291–297 ISSLL (Integrated Services over Specific Lower Layers), 203 its, 306

J-K-L

iitter minimum, 121-123 packet. 10 Label Edge Router (LER), 212 Label Information Base (LIB), 212 Label Switched Path (LSP), 247 Label Switching Router (LSR), 212 labels binding, 213-216 downstream distribution, 219-222 encapsulation, 216-217 switching, 14 LANs (local-area networks), 200-203 Layer 2 ATM. 169-170-184 overlay model, 247-248 QoS technologies, 14 LER (Label Edge Router), 212, 227 levels of QoS, 6 LIB (Label Information Base), 212 limiting traffic, 48–50 link admission control. TE tunnels, 256 link resource attributes, 253 Link State Advertisement (LSA), 257 links, enhancing utilization, 133-135 local link resource information. distribution of, 254 lookups, process switching, 287 loss, packet, 11 low-latency queues, 98, 115 LSA (Link State Advertisement), 257 LSP (Label Switched Path), 247 LSR (Label Switching Router), 212, 227

Μ

MAC (Media Access Control), 280 maintenance, TE path, 256 management policies, 301-305 queues, 130-132 traffic rate, 42-48 managers, policy, 29 map commands, 295 mapping, Frame Relay, 198 mark probability denominator, 132 marking packets, 34-39 match access-group 101 command, 136 match commands, 305 match subcommand, 280 matching traffic specification, 44 max-min fair-share allocation scheme, 69-70 max-reserved bandwidth command, 99 maximum burst size (MBS), 172 maximum segment size (MSS), 127 MBS (maximum burst size), 172 MCR (Minimum Cell Rate), 173 MDRR (Modified Deficit Round Robin), 114 - 121measuring traffic, 42, 54 mechanisms, voice traffic, 98-101 Media Access Control (MAC), 280 media support, RSVP, 156 messages, RSVP, 151 metering function, 26 Minimum Cell rate (MCR), 173 MINCIR (minimum CIR), 188 minimum jitter, 121–123 MLPP (Multilink Point-to-Point), 99 models, Layer 2 overlay, 247-248

modes alternate priority, 115 strict priority, 115 modification custom queues, 100 IS-IS. 258 Modified Deficit Round Robin (MDRR), 114 - 121Modified Weighted Round Robin (MWRR), 105 - 113modular CLI (command-line interface), 89-91 MPLS (Multi Protocol Label Switching), 14, 211, 247, 302 ATM, 218 case study, 258–272 CoS case study, 225–227 OoS, 223 VPN, 227–237 VPN QoS, 237-241 mpls traffic-eng attribute-flag 0x1 command, 264 mpls traffic-eng tunnels command, 259 MSS (maximum segment size), 127 Multi Protocol Label Switching. See MPLS multicast applications, RSVP, 147 multidimensional policies, 282 Multilink Point-to-Point (MLPP), 99 multimedia, RSVP, 147-152 multiple PVCs case study, 196 configuring bundles, 184 MWRR (Modified Weighted Round Robin), 105 - 114

Ν

Nagle Algorithm, 315 NBAR (Network Based Application recognition), 34 Network Based Application Recognition (NBAR), 34 Network File System (NFS), 148 Network Layer Reachability Information (NLRI), 228 Network-to-Node Interface (NNI), 169-170 networks ATM interworking, 178-179 Layer 2, 169-184 boundary interfaces, 281 boundary traffic conditioners, 25-26 end-to-end IP OoS, 225 Frame Relay, 185–199 LANs, 200-203 Layer 2 overlay, 247-248 levels of QoS, 6 Path MTU Discovery, 315 perfomance, 9, 11 policy-based routing, 302–303 priority queuing, 91–92 provisioning, 28 RRR, 248-249 support, 67–72 traffic rate management, 42 WAN (wide-area network), 8, 319 NFS (Network File System), 148 NLRI (Network Layer Reachability Information), 228 NNI (Network-to-Node Interface), 169-170 no mpls ip propagate-ttl command, 218, 272 nonadaptive flows, congestion avoidance, 138 nRT-VBR (Non-Real Time Variable Bit Rate), 172

0

Open Shortest Path First. *See* OSPF optimization bandwidth, 316 routing, 301, 303–305 TE path, 256 order of policy execution, 284 OSPF (Open Shortest Path First), 258, 289 outgoing traffic, 307–309 output, interface queue, 119

Ρ

packets cell discard strategies, 173–174 classification. 34-39 classifier and marker, 12 coloring, 34 delay and jitter, 10 differentied IP discards, 180 drop policy, 13 drop probability, 132-135 FIFO queuing, 68-69 flow WRED, 136–138 Frame Relay, 190–191 label encapsulation, 216–217 loss, 11 marking, 34 Path MTU Discovery, 315 prioritization, 93 priority queuing, 91–92 process switching, 287 route-cache forwarding, 287-288 scheduling, 106 size, 305 TE trunks, 251 traffic shaping, 53-60 WRR (Weighted Round Robin), 106–108 parameters, 93 partial packet discard (PPD), 173-174 PATH messages, 151 Path MTU Discovery, 315 Path State Block (PSB), 151, 205 paths selection, 253-254 TE maintenance, 256 Payload Type Identifier (PTI), 171 PBR (Policy-Based Routing), 35, 38 PCR (Peak Cell Rate), 172

PEP (Policy Enforcement Point), 30 performance, 9-11. See also optimization Per-INterface Rate Configuration (PIRC), 48 permanent virtual circuits (PVCs), 54, 169 permium services, EF PHB, 27 per-VC WFO, 198 PHB (per-hop behavior), 26–28 MDRR, 114-121 MWRR, 105–113 resource allocation policy, 28-30 PIRC (Per-Interface Rate Configuration), 48 Point-to-Point Protocol (PPP), 319 Points of Presence (POP), 258 policies action, 47 applications, 282-283 defining, 281 hierarchical, 283 incoming traffic, 307-309managers, 29 order of execution, 284 outgoing traffic, 307-309 packet drop, 13 path selection, 254 resource allocation, 28-30 routing, 301-305 policing traffic, 43-48 Policy Enforcement Point (PEP), 30 Policy-Based Routing (PBR), 35, 302-303 policy-map command, 281 policy-map wred command, 136 POP (Points of Presence), 258 popping labels, 222 PPD (partial packet discard), 173-174 PPP (Point-to-Point Protocol), 319 ppp mulitlink command, 321 ppp multilink fragement-delay 20 command, 321 ppp mulitlink interleave command, 321 PQ (priority queue), 83 precedence, 34-35, 303-304, 323-325. See also IP (Internet Protocol)

pre-hop behavior (PHB), 22 preventing denial-of-service attacks, 51 smurf attacks, 141–142 priorities packets, 93 TE tunnels, 251 priority keyword command, 100 priority queue (PQ), 83, 91-93 proactive queue management for congestion avoidance, 130-132 probability, packet drops, 132 process switching, 287-288 propagation, 307 protocols FTP (File Transfer Protocol), 6, 155 ICMP (Internet Control Message Protocol), 51 IGP routing extensions, 257 IP (Internet Protocol), 8–9 minimum interface bandwidth, 95–98 MPLS (Multi Protocol Label switching), 14 QoS Signaling Portocol, 13 RSVP (Resource Reservation Protocol), 21 RTP (Real-time Transport Protocol), 99 SBM (Subnet Bandwidth Manager), 203-205 TCP (Transmissin Control Protocol), 151 TCP/IP (Transmission Control Protocol/ Internet Protocol), 8 UDP (User Datagram Protocol), 151 Provider Edge routers, 228 provisioning networks, 28 PSB (Path State Block), 151, 205 PTI (Payload Type Identifier), 171 public exchange point traffic, enforcing, 52-53 PVCs (permanent virtual circuits), 54, 169

Q

OoS. 172 end-to-end IP, 225 **MPLS. 223** MPLS VPN, 237-241 packet classification, 36 policies, 279, 301-305, 307 propagation, 307 QoS Policy Propagation BGP (QPPB), 287 **QoS Signaling Protocol**, 13 gos switching command, 114 QoS-based DWFQ, 90 QoS-based routing, 301–302 **QPPB** (QoS Policy Propagation BGP), 287 **IP** Precedence, 39 QoS groups, 40 quantum values, 114 queues ATM interworking, 178–179 average size computation, 131 conversation, 80 input interface, 119 IP priority, 142 low-latency, 115 output interface, 119 RED, 130–132 ToS-based DWFQ, 89–90 WRR (Weighted Round Robin), 106 queuing custom, 94–97, 100 FIFO, 68-69 implementing, 68 priority, 91–92

R

random-detect command, 134 random-detect flow average-depth-factor 6 command, 138 random-detect flow command, 138 random-detect flow count command, 138 rate-limiting function, 43-45, 47-48 rates access. 56-60 ICMP, 51 traffic, 48-50 traffic management, 42-48 RD (route distinguisher), 228 Real-time Transfer Control Protocol (RTCP), 313 Real-time Transport Protocol (RTP), 99, 313 Real-Time Variable Bit Rate (RT-VBR), 172 receivers controlled load services. 155 guaranteed bit rate services, 155 RED, congestion avoidance, 130-132 req-qos guaranteed-delay command, 163 reservation styles, RSVP, 152-162 resilience. TE tunnels, 253 resource allocation, 12 resource allocation policy, 28-30 resource class affinity, TE tunnel, 252 resource class attribute, 253 Resource Management (RM), 173 Resource Reservation Protocol (RSVP), 21.313 **RESV** (RSVP reservation request), 79 retransmit timer (RTT), 128 RM (Resource Management), 173 round numbers, 72 round-robin, byte-by-byte GPS Scheduler simulation. 73-74 route distinguisher (RD), 228

route-cache forwarding, 287-288 switching, 297-298 route-map command, 280 route-target import 200colon1 command (change in edit), 233 routers ABR PVC, 175 backbone, 291-297 class-based WFO, 85-86 ECN, 139 head-end, 255 Layer 2 overlay model, 247-248 packets, 34 Provider Edge, 228 **RSVP-related configuration**, 159 SPD, 139-140 support, 67-72 TE trunks, 251 traffic rate management, 42-48 routing, 13 IGP protocol extensions, 257 IP precedence, 303–304 packet size, 305 policy-based, 302-303 OoS, 301-305 RRR (Routing by Resource Reservation), 247-249, 253 RSVP (Resource Reservation Protocol), 21, 313, 147 case study, 157-163 controlled load service, 155 extensions, 205 guaranteed bit rate service, 155 media support, 156 resrvation styles, 152 scalability, 156 TE-RSVP, 256–257 WFQ interaction, 79 at VPN sites only, 239 **RSVP** reservation request (RESV), 79

RSVP-related configuration, 159 RT (Route Target), 228 RTCP (Real-time Transfer Control Protocol), 313 RTP (Real-time Transport Protocol), 99, 313 RTT (retransmit timer), 128 RT-VBR (Real-Time Variable Bit Rate), 172 rx-cos slot command, 122

S

SAR (segmentation and reassembly), 169 SBM (Subnet Bandwidth Manager), 203 scalability, RSVP, 156 schedulers, process switching, 287 scheduling class-based MWRR, 113-114 GOS. 71–72 MDRR. 114–121 mechanisms for voice traffic, 98-101 MWRR, 105-113 sequence number computation-based WFQ, 72–73 support, 67-72 WFQ, 79, 82 schemes max-min fair-share allocation, 69-70 switching, 297–298 token buckert, 42 SCR (Sustained Cell Rate), 172 SE (Shared Explicit), 153 segmentation and reassembly (SAR), 169 self-clocking, 128 Sequence Number (SN), 73 sequence number computation-based WFQ, 72 - 73Service Level Agreements (SLAs), 306 service nagle command, 315 service-policy command, 182, 282 service-policy output febandwidth command, 87

services ABR case study, 175 best-effort, 6 controlled load, 155 diffserv architecture, 22-26 PHB, 26-28 resource policy, 28-30 guaranteed, 7 guaranteed bit rate, 155 IP subrate, 50 Web hosting, 51 set commands, 305 setup priorities, TE tunnels, 251 shape average command, 58 shape peak command, 58 shaper function, 26 shaping FRTS (Frame Relay Traffic Shaping), 187 - 189traffic, 53-60 Frame Relay, 60-61 VP case study, 176 VP, 174 shaping functions, 42 Shared Explicit (SE), 153 shared reservations, 152 Shortest Path First (SPF), 254 show atm vc command, 177 show atm vp command, 176 show atm vp 2 command, 177 show class command, 86 show command, 49 show commands, 304 show controllers frfab/tofab cos-queue length/ parameters/varaibles command, 123 show frame-relay pvc command, 196 show frame-relay qos-autosense command, 193 show interface Hssi0/0/0 command, 143 show interface rate commad, 49

show interface shape command, 58 show interface tunnel0 command, 266 show interfaces switching command, 143 show ip cache verbose command, 293 show ip cef 222.222.22.3 internal command, 268 show ip policy command, 305 show ip route, 268 show ip route command, 268, 292 show ip route vrf green command, 232 show ip rsvp installed command, 161–162 show ip rsvp interface command, 160 show ip rsvp neighbor command, 161 show ip rsvp request command, 161 show ip spd, 142 show ip spd command, 142 show isis mpls traffic tunnel command, 266 show isis mpls traffic-eng advertise command, 267 show mpls forward-table command, 220 show mpls forwarding-table command, 221 show mpls idp bindings command, 220 show mpls idp parameters command, 221 show mpls traffic-eng tunnel tunnel0 command, 263-264 show policy command, 86 show policy-map command, 182 show queue command, 81 show queue interface command, 81 show queue s0 command, 162 show queue serial0 command, 87 show queueing custom command, 97 show queueing fair command, 82 show queueing priority command, 93, 197 show queueing random-detect command, 134, 138 show route-map tasman command, 305 show traffic-shape command, 193 show traffic-shape statistics command, 58 signaled QoS, 29 simulation, byte-by-byte GPS Scheduler, 73 - 74

sizes fragements, 320 packets, 305 SLAs (Service Level Agreements), 306 slot-table-cos command, 122 slow start avoidance, TCP, 127-128 slow start threshold (ssthresh), 128 smurf attacks, 141-142 SN (Sequence Number), 73 SONET (Synchronous Optical Network), 121 SOO (Source of Origin), 228 Source Route Object (SRO), 255 specifications, traffic matching, 44 SPF (Shortest Path First), 254 SRAM (Static Random Access Memory), 85 SRO (Source Route Object), 255 ssthresh (slow start threshold), 128 statements confirm-action, 47 exceed-action, 47 Static Random Access Memory (SRAM), 85 strategies, cell discard, 173-174 strict priority mode, 115 strict priority queue for voice, 100 studies, Frame Relay adaptive traffic shaping, 195 Subnet Bandwidth Manager (SBM), 203 subrate IP services, 50 support class-based WFO, 85-86 custom queuing, 101 DWFO (distributed WFO), 83-85 **RSVP**, 156 scheduling, 67-72 Sustained Cell Rate (SCR), 172 SVCs (switched virtual circuits), 54, 169 switches, MPLS, 218 switching, 13 fast, 287 MPLS, 14, 211-217 process, 287 Synchronous Optical Network (SONET), 121

Τ

table-a slot-table cos command, 122 tables, adjacency, 289 tail drop, 13 TCP (Tranmission Control Protocol), 127-128, 283.315 congestion, 139 slow start avoidance, 127-128 traffic. 129 TCP/IP (Transmission Control Protocol/ Internet Protocol), 8, 316 TCP-police-hierarchical policies, 284 TE (traffic engineering), 258, 302 path, 256 trunks, 251 tunnels, 251-272 telent-ftp-police policies, 284 TE-RSVP, 256–257 thresholds, packet drop probability, 132 Time-to-Live (TTL), 272 tinygrams, 315 token buckets, 42-44, 54 tools, routing decisions, 301–305 ToS (Type of Service), 22, 112–113 ToS-based DWFQ, 89-90 traffic action policies, 47 ATM QoS, 172 bandwidth assignment per ToS class, 88 bumping, 179 CAR, 37–40 class definition, 280 custom queuing, 94-97 engineering, 214 flow-based WFQ, 80-82 Frame Relay, 186–189 higher bandwidth allocation case study, 86-87 incoming, 307-309 IP precedence, 303–304 LANs, 200–203 Layer 2 overlay model, 247–248

levels of OoS, 6 limiting, 49-50 measuring, 42, 54 mechanisms, 99 multimedia, 147–151 network boundary conditioners, 25-26 outgoing, 307-309 PHB (per-hop behavior), 26 policing, 43-48 priority queuing, 91–92 public exchange point, 52-53 **OPPB**, 39 rate management, 42-48 rates, 48-50 RRR, 248-249 RTP, 313 shaping, 53–54 case study, 56-60 Frame Relay, 60-61 SPD, 139-140 TCP behavior in tail-drop scenario, 129 voice configuring, 121-123 scheduling mechanisms, 98-101 VP shaping, 174 Web hosting services, 51 traffic engineering (TE), 302 traffic matching specification, 44 traffic shaping (TS), 42 traffic-shape fecn-adapt command, 190 traffic-shape_adaptive command, 190 Transmission Control Protocol. See TCP Transmission Control Protocol/Internet Protocol. See TCP/IP troubleshooting performance, 9, 11 **RSVP**, 156 scheduling, 67-72 TE path, 256 traffic rate management, 42–48 trunks, TE, 251 TS (traffic shaping), 42 TTL (Time-to-Live), 272

tunnel mode mpls traffic-eng command, 259
tunnel mpls traffic-eng autoroute announce command, 268
tunnel mpls traffic-eng record-route command, 264
tunnels, 251–272. See also TE
tx-queue-limit command, 78
Type of Service (ToS), 22
types of AAL, 172–173

U

UBR (Unspecified Bit Rate), 173 UDP (User Datagram Protocol), 151, 302 under, 301 UNI (User-to-Network Interface), 169–170 unicast traffic, 148 Universal Resource Locator (URL), 34 Unspecified Bit Rate (UBR), 173 upstream label allocation, 216 URL (Universal Resource Locator), 34 User Datagram Protocol (UDP), 151, 302 User-to-Network Interface (UNI), 169–170

V

values quantum, 114 SOO, 228 VBR (Variable Bit Rate), 172–173 VC (virtual circuit), 185–199, 279 VCI (virtual channel identifier), 170 Versatile Interface Processor (VIP), 48, 83 video, 147–151, 313. *See also* RSVP VIP (Versatile Interface Processor), 48, 83 virtual channel identifier (VCI), 170 virtual circuit (VC), 185–199, 279 virtual path (VP), 170 Virtual Private Network. *See* VPN virtual-template interface, 321 vofr command, 200 voice, 100 flow packets case study, 82–83 traffic, 98
VoIP (Voice over IP), 93, 98, 162–163
VP (virtaul path), 170
VPN (Virtual Private Network), 148 MPLS, 227–237 RSVP, 240

W

WAN (wide area network), 185–199, 319 Web hosting services, 51 Weighted Fair Queuing. See WFQ weighted flow classes, GPS, 71-72 Weighted Random Early Detection. See WRED Weighted Round Robin (WRR), 105–108 WF (Wildcard Filter), 153 WFQ (weighted Fair Queuing), 83-85, 279, 320 case study, 82-83 class-based, 85-86 flow-based, 75–78 bandwidth allocation case study, 82 case study, 80-81 strict priority queue for voice, 100 implmenting, 79-80 per-VC WFQ, 198 sequence number computation-based, 72 - 73WG (Working Group), 21 wide area network (WAN), 185–199, 319 Wildcard Filter (WF), 153 Working Group (WG), 21 WRED (Weighted Random Early Detection), 279 congestion avoidance, 133–135 flow WRED, 136-138 WRR (Weighted Round Robin), 105-108