



INDEX

A

- access concentrators, 354–356
- Address field (Frame Relay), 20
- addresses
 - IP. *See* IP, addresses
 - prefix, LFIB, 61–63
- address-family sibmode, 108
- addshelf command, 211, 226, 238
 - parameters, 225–226
- ADJACENCY messages (LDP), 65
- AF (assured forwarding), 309
- AF PHB, 311
- amplifiers, Optical networking, 388
- architecture, 45–74, 46–52
 - DiffServ, 310
 - forwarding, 45–46
 - Internet, 6–7
 - MPLS connectionless VPNs, 92
 - node, 46–52
 - Control pane, 51–52
 - forwarding plane, 46–51
 - Optical networking. *See* Optical networking
 - assured forwarding (AF), 309
- ATM, 3, 17, 21–32
 - ATM-to-Frame Relay interworking, 30
 - cells, 24–26
 - circuits, 28–29
 - design criteria, 350–351
 - "everywhere" concept, 17
 - header fields, 24–25
 - ILMI, 29–30
 - interfaces, 26–28
 - IP integration, 6, 36–41
 - direct class service implementation, 40
 - IGPs, 36–39
 - MPLS versus traditional IP over ATM, 39–41
 - overlay model versus integrated model, 37–39
 - reduced loads, 41
 - reliability, 40
 - RSVP, 40
 - traffic engineering, 41
 - VPN manageability, 40

- VPN scalability, 40
- layers, 23–24
- LSRs, 56–58, 181
 - allocation procedure, 58
 - design criteria, 351
 - ordered control method, 57
 - VCI, 58
 - VPI, 58
- management, 29–30
- migration into ATM networks, 346–350
- NNI, 26–28
- OSI Model, 22
- QoS, 31
- reference model planes, 23
- signaling, 26–28
- UNI, 26–28
- virtual channels, 28–29
- virtual paths, 28–29
- VPNs, 179–244, 343–345
 - case study, 229–244
 - cell interleaving, 186–188
 - configuration, 209–229
 - control component, 184–186
 - forwarding component, 183–184
 - hybrid, 345–346
 - IP+ATM, 194–198
 - label virtual circuits, 190–191
 - LSCs, 190–193
 - packet-based, 182–183, 199–209
 - tag switching, 180–181
 - VC Merge, 188
 - VSI, 193–197
- ATM adaption layer (AAL), 24
- ATM Edge LSR, 181

B

-
- backbone link sizing, 357–364
 - adjusting redundancy, 362–363
 - assigning link capacity, 362
 - equipment, 363
 - estimating traffic, 357–360
 - link bandwidths, 361–362
 - trunk topology, 360–361
 - backbone networks, customer carriers, 158–160

backward explicit congestion notification (BECN),
21
bandwidth command, 250
BECN (backward explicit congestion notification),
21
BGP (Border Gateway Protocol), 247
 confederations, 149–157
 full mesh, 139
 route reflectors, 138–141
 sessions
 Internet access over MPLS VPNs, 165–168
 next-hop configuration, 165–166
 VPN routing, 100–101
BGP4 (Border Gateway Protocol Version 4), 6, 37
 PE-to-CE routing configuration, 109–110
bidirectional traffic, backbone link sizing designs,
359–360
Border Gateway Protocol. *See* BGP
Border Gateway Protocol Version 4. *See* BGP4
BPV 8650, configuration, 210–227
BPX configuration, ATM-based MPLS VPN case
 study, 238–244
bridge-and-roll, 258
BXM cards
 connection allocation, 216
 maximums, 217

C

CAR (Committed Access Rate), 311, 320
 configuration of ingress PE, 327–328
carrier-over-carrier MPLS VPNs, 157–160
carriers, MPLS capabilities, 41–42
case studies
 ATM-based MPLS VPN, 229–244
 BPX configuration, 238–244
 IP addresses, 231–232
 LSC configuration, 234–237
 PE configuration, 231–234
 PE deployment, 230
 VPN configuration, 230
 VPN deployment, 229
 Layer 3 design, 370–378
 destination prefixes, 366–367
 Edge LSRs, 368–370

VC merge, 367–368
MPLS VPN design and implementation, 115–138
 Chicago CE configuration, 124–125
 Chicago PE configuration, 122–124
 IP addresses, 117
 Miami CE configuration, 134–135
 Miami PE configuration, 132–134
 P1 router configuration, 118–119
 P2 router configuration, 119–120
 P3 router configuration, 120–121
 PE deployment, 117
 San Diego CE configuration, 131–132
 San Diego PE configuration, 129–131
 Seattle CE configuration, 128
 Seattle PE configuration, 126–128
 service provider network, 116–118
 Washington CE configuration, 138
 Washington PE configuration, 135–137
packet-based MPLS over ATM VPN, 200–208
 configuration, 201–206
 PE configuration, 205–209
 PVC configuration, 203
QoS, 329–339
 attaching service policies to input
 interfaces, 336–339
 creating service policies, 332–336
 creating traffic classes, 329–332
Traffic Engineering Network (IS-IS), 269–296
 R1, 270–273
 R2, 281–283
 R3, 273–276
 R4, 283–285
 R5, 285–286
 R6, 286–288
 R7, 288–289
 R8, 276–281
Traffic Engineering Network (OSPF), 290–296
 R1 configuration, 290–291
 R3 configuration, 292–293
CBWFQ (Class-Based Weighted Fair Queuing),
311–312, 320
CE router configuration, 113–115
 ATM-based MPLS VPNs, 210
 packet-based MPLS over ATM VPNs, 200–204
 VPN case study, 124–125, 128, 131–135, 138
CEF (Cisco Express Forwarding), 103

- cell interleaving, 186–188
- Cell Loss Priority (CLP) field, 25
- cell switching, 16–21
 - ATM, 17, 21–32. *See also* ATM
 - ATM-to-Frame Relay interworking, 30
 - cell delay, 31
 - cell loss, 31
 - cells, 24–26
 - circuits, 28–29
 - header fields, 24–25
 - ILMI, 29–30
 - interfaces, 26–28
 - IP integration, 6, 36–41
 - layers, 23–24
 - LSR, 56–58
 - management, 29–30
 - NNI, 26–28
 - OSI Model, 22
 - QoS, 31
 - reference model planes, 23
 - signaling, 26–28
 - UNI, 26–28
 - virtual channels, 28–29
 - virtual paths, 28–29
 - SMDS, 17
- cells
 - ATM, 24–26
 - VPNs, 81–82
- centralized services, MPLS connectionless VPNs, 92
- Chicago CE configuration, VPN case study, 124–125
- Chicago PE configuration
 - ATM-based MPLS VPN case study, 231–232
 - packet-based MPLS over ATM VPN case study, 204–205
 - VPN case study, 122–124
- CIDR (classless interdomain routing), 6
- CIR (Committed Information Rate), 19
- circuits
 - ATM, 28–29
 - switching, TDM, 11–16
- Cisco Express Forwarding. *See* CEF
- Cisco Service Management. *See* CSM
- Cisco View, 174
- Cisco Works 2000 WAN Manager, 174
- class command, 324
- Class-Based Weighted Fair Queuing (CBWFQ), 311–312, 320
- class-default default, 333–335
- class-map command, 322
- class-map match-all command, 322
- class-selector PHB, 308
- classes of service. *See* CoS
- classless interdomain routing. *See* CIDR
- cnfqbin command, 223, 240
 - parameters, 224
- cnfrsrc command, 211–216, 221, 223, 238, 240
- colored thread algorithm (loop prevention), 72–73
- commands, 407–422
 - addshelf, 211, 225–226, 238
 - bandwidth, 250
 - class, 324
 - class-map, 322
 - class-map match-all, 322
 - cnfqbin, 223–224, 240
 - cnfrsrc, 211–216, 221, 223, 238, 240
 - dspd, 211, 218, 240
 - dspcds, 221
 - dspqbin, 224
 - import map, 106
 - ip cef, 103
 - ip explicit-path, 261
 - ip ospf cost, 250
 - match, 322
 - match-all, 322
 - MQC, 419–421
 - neighbor next-hop-self, 142, 145, 149, 153
 - Netflow, 422
 - policy-map, 324
 - redistribute, 108, 112
 - redistribute bgp metric transparent, 109
 - redistribute connected subnets, 142, 145, 149, 153
 - route-map, 108
 - route-target, 106
 - router ospf, 111
 - service-policy, 326
 - show ip rsvp host EXEC, 268
 - show ip rsvp interface, 267
 - show isis mpls traffic-eng adjacency-log EXEC, 268
 - show isis mpls traffic-eng advertisements EXEC, 268

- show mpls traffic-eng topology, 269
- show mpls traffic-eng tunnel, 265
- show mpls traffic-eng tunnel brief, 266
- show mpls traffic-eng tunnel summary, 269
- tag switching, 180
- traffic engineering, 414–419
- uptrk, 212
- variance n, 251
- VPN, 413–414
- Committed Access Rate (CAR), 311, 320
 - configuration of ingress PE, 327–328
- Committed Information Rate. *See CIR*
- Common Object Request Broker Architecture (CORBA), 396
- configuration
 - ATM-based MPLS VPNs, 209–229
 - CE routers, 210
 - core switches, 210–227
 - PE routers, 209
 - BGP confederations, 149–157
 - AS1, CE1, 150
 - AS1, EBGP1, 152–153
 - AS1, EBGP2, 153–155
 - AS1, P1, 152
 - AS1, PE1, 150–151
 - AS2, CE2, 157
 - AS2, P2, 155–156
 - AS2, PE2, 156–157
 - BGP sessions
 - EBGP multi-hop, 166–168
 - next-hop, 165–166
 - BPV 8650, 210–227
 - BPX, ATM-based MPLS VPN case study, 238–239
 - CAR (Committed Access Rate), ingress PE, 327–328
 - Inter-Provider MPLS VPN, 142–149
 - AS1, CE1, 142
 - AS1, EBGP1, 145
 - AS1, EBGP2, 145–146
 - AS1, P1, 144
 - AS1, PE1, 143–144
 - AS2, CE2, 149
 - AS2, P2, 147–148
 - AS2, PE2, 148–149
 - LSCs, 227–229
- ATM-based MPLS VPN case study, 234–237
- MQC (Modular QoS) verification, 326–327
- packet-based MPLS over ATM VPN, 200–201
- PE routers
 - ATM-based MPLS VPN case study, 231–234
 - ingress, 321
- PVC, packet-based MPLS over ATM VPN, 204–208
- QoS for MPLS VPNs, 321–328
 - service policy, 324–326
 - traffic class configuration, 322–323
- R2 traffic engineering policy, 281–283
- R3, OSPF Traffic-Engineering Network case study, 292–293
- R4
 - IS-IS Traffic-Engineering Network case study, 283–285
 - traffic engineering policy, 283–285
- R5
 - IS-IS Traffic-Engineering Network case study, 285–286
 - traffic engineering policy, 285–286
- R6 traffic engineering policy, 286–288
- R7
 - IS-IS Traffic-Engineering Network case study, 288–289
 - traffic engineering policy, 288–289
- R8
 - IS-IS Traffic-Engineering Network case study, 278–281
 - OSPF Traffic-Engineering Network case study, 293–296
 - traffic engineering policy, 278–281
 - router-based VPNs, 103–114
 - CE routers, 113–115
 - defining, 105–106
 - IGP, 104
 - interfaces, 104
 - P routers, 112–113
 - PE-to-CE routing, 107–112
 - PE-to-PE routing, 106–107
 - required IOS services, 103
 - static routes
 - CE1, 164

PE1, 164–165
 traffic engineering, 259–269
 explicit path, 261
 IS-IS for MPLS TE, 262–264
 OSPF for MPLS TE, 264–265
 RSVP signaling and IGP flooding, 260
 TE tunnel devices, 259
 tunnels, 259–262
 unequal-cost load balancing, 265
 congestion control (Frame Relay), 21
 connection-oriented VPNs, 78–86
 Layer 2, 78–82
 Cell-based VPNs, 81–82
 Frame-based, 79–81
 TDM-based, 79
 Layer 3, 82–86
 GRE Tunneled, 83–84
 IPSec Tunneled VPNs, 84
 virtual private dialup, 84–86
 connectionless VPNs, 86–89
 conventional, 86–88
 MPLS, 88–89
 advantages, 90–93
 packet-based. *See* packet-based VPNs
 conservative label retention mode, LDP, 66
 consolidation, MPLS connectionless VPNs, 92
 constraint-based routing, 253–256
 control, loops, 68–73
 detection, 70
 prevention, 71–73
 survival, 68–69
 Control component
 ATM-based MPLS, 184–186
 Layer 3 routing, 32
 control packet looping, LDP, 67
 Control plane (ATM), 23, 51–52
 control_id parameter (addshelf command), 225–226
 control_vci_start parameter (addshelf command),
 225–226
 control_vpi parameter (addshelf command), 225–
 226
 Controlled Load Service (IntServ), 301
 conventional connectionless VPNs, 86–88
 CORBA (Common Object Request Broker
 Architecture), 396
 core routers, VPNs, 98, 103

CoS (classes of service), 4
 field, 48
 MPLS connectionless VPNs, 93
 CPE (customer premises equipment), 11
 CSM (Cisco Service Management), 93
 customer carriers, backbone networks, 158–160
 Customer edge routers, VPNs, 98, 100, 103
 customer premises equipment. *See* CPE
 customer routers, VPNs, 98, 100, 103

D

D4 framing, 13–15
 data packet looping, 67
 data-link connection identifier. *See* DLCI
 default PHB, 308
 design, 343–381
 ATM criteria, 350–351
 backbone link sizing, 357–364
 adjusting redundancy, 362–363
 assigning link capacity, 362
 equipment, 362–363
 estimating traffic, 357–360
 link bandwidths, 361–362
 trunk topology, 357–360
 equipment design specifications, 425–431
 Internet routing tables, 379
 Layer 3, 364–366
 LVC sizing, 366–378
 LVC exhaustion, 380
 PoP, 352–356
 access concentrators, 354–356
 multiple ATM Edge LSR, 352–354
 single ATM Edge LSR, 352
 traffic constraints, 379
 virtual path tunnel constraints, 380
 dense wavelength division multiplexing. *See*
 DWDM
 detection loops, 70
 device-type parameter (addshelf command), 225–
 226

- DiffServ, 307–312
 — architecture, 310
 CAR (Committed Access Rate), 311
 domains (DS domain), packets, 313
 GTS (Generic Traffic Shaping), 311
 implementation, 313–315
 per-hop behavior (PHB), 307–309
 enforcement, 311–312
 scheduling class, 314–315
 Traffic Conditioner Block (TCB), 310
- Digital Signal level. *See* DS level
- DISCOVERY messages (LDP), 65
- distance vector protocols (DV), 255
- DLCI (data-link connection identifier), 18
- downstream on demand (LDP), 57, 66
 — ATM control component, 185
- DS level (Digital Signal level), 11
 — framing, 13–15
 — hierarchy, 12–13
- DSCP pools, 313
- dspcd command, 211, 218, 240
- dspcds command, 221
- dspqbin command, 224
- dspqbin screen, 225
- DV (distance vector) protocols, 255
- DWDM (dense wavelength division multiplexing), 384–387
- Egress Committed Rate (ECR), 318
- EIGRP, unequal-cost load balancing, 251–252
- electrical-to-optical (EO), 384
- end-to-end QoS, MPLS connectionless VPNs, 92
- EO (electrical-to-optical), 384
- equipment
 — backbone link sizing designs, 363
 — design specifications, 425–431
 — VPNSC, 174
- ESF (Extended Super Frame), 13–15
- establishment, LSP, 59–64
 — independent control, 59–63
 — ordered control, 64
- everywhere concept (ATM), 17
- Exp field (shim header), 314, 321
- expedited forwarding (EF), 309
- explicit path, configuration, 261
- Extended Super Frame (ESF), 13–15
- Exterior Gateway Protocol. *See* EGP
- external ISPs, Internet access over MPLS VPNs, 161–162
 — CE1 configuration, 162–163
 — PE1 configuration, 163
- external LSCs, 191

E

-
- E-LSPs, 314–315
- e/d parameter
 — cnfqbin command, 224
 — cnfrsrc command, 214
- EBGP, multihop configuration, 166–168
- ECR (Egress Committed Rate), 318
- Edge LSRs
 — design
 — criteria, 351
 — multiple ATM, 352–356
 — single ATM, 352
- Layer 3 design calculations, 368–370
- VPNs, 98, 100, 103
- EF (expedited forwarding), 309
- EFCI_threshold parameter (cnfqbin command), 224
- EGP (Exterior Gateway Protocol), 6, 37, 247

F

-
- fast rerouting, traffic engineering, 257
- FCS field (Frame Relay), 20
- FEC (Forwarding Equivalency Class), 33
- FECN (forward explicit congestion notification), 21
- fields
 — ATM header, 24–25
 — Frame Relay, 19–20
- Flag field (Frame Relay), 19
- flooding, IGP, 260
- forward explicit congestion notification (FECN), 21
- forwarding, 45–46
 — packet-based VPNs, 99–103
- Forwarding component
 — ATM-based MPLS, 183–184
 — Layer 3 routing, 32
- Forwarding Equivalency Class (FEC), 33

forwarding plane, 46–51
 label forwarding algorithm, 50–51
 LFIB, 49–50
 MPLS Label formats, 47–48
 FRAD (Frame Relay access device), 17–18
 Frame fields (Frame Relay), 19–20
 Frame Relay, 16–21
 ATM-to-Frame Relay interworking, 30
 CIR, 19
 congestion control, 21
 DLCI, 18
 FRAD, 17–18
 frame fields, 19–20
 LMI, 20–21
 port speed, 18
 UNI, 18
 Frame Relay access device. *See* FRAD
 Frame-based VPNs, 79–81
 framing (DS level), 13–15

G

gateways, Optical networking, 389
 Generic flow control (GFC) field, 24
 Generic Traffic Shaping (GTS), 311
 global keyword, 163
 GRE Tunnels, 83–84
 GTS (Generic Traffic Shaping), 311
 Guaranteed Service, IntServ, 301

H

headend source routers, 254
 Header error control (HEC) field, 25
 High_CLP_threshold parameter (cnfqbin command), 224
 history of MPLS, 5
 hop count method, loop detection, 70
 hose model (VPN QoS), 318–320
 HSRP (Hot Standby Router Protocol), 168–170
 hybrid VPNs, 345–346

I

IBGP (Interior Border Gateway Protocol), 247
 ICR (Ingress Committed Rate), 318
 IGP (Interior Gateway Protocols), 36–39, 247
 configuration, 104
 flooding, 260
 tunnel configuration, 261–262
 ILMI (Interim Local Management Interface), 29–30
 implicit null label, penultimate hop popping (LSR), 55–56
 import map command, 106
 in-band signaling (TDM), 12
 incoming label (LFIB), 60–63
 independent control LSP establishment, 59–63
 Information field (Frame Relay), 20
 Ingress Committed Rate (ICR), 318
 CAR configuration, 327–328
 input interfaces, attaching service policies to, 337–339
 inter-autonomous system MPLS VPNs, 141–157
 BGP confederations, 149–157
 Inter-Provider VPN, 141–149
 Inter-Provider MPLS VPN, configuration
 AS1, CE1, 142
 AS1, EBGP1, 145
 AS1, EBGP2, 145–146
 AS1, P1, 144
 AS1, PE1, 143–144
 AS2, CE2, 149
 AS2, P2, 147–148
 AS2, PE2, 148–149
 interexchange carrier. *See* IXC
 interfaces
 ATM, 26–28
 input, attaching service policies to, 337–339
 Optical User Network Interface (O-UNI), 391–392
 PNNI (Private Network Node Interface), 255
 router-based VPNs, 104
 Virtual Switch Interface. *See* VSI
 VRF HSRP support, 168–170
 Interim Local Management Interface. *See* ILMI
 Interior Border Gateway Protocol. *See* IBGP
 Interior Gateway Protocols. *See* IGPs
 intermediate reach (IR) SMF segments, 385

- Intermediate System-to-Intermediate System. *See also* IS-IS
 internal LSCs, 191
 Internet
 access over MPLS VPNs, 160–168
 BGP sessions, 165–168
 external ISPs, 161–162
 static default routes, 162–165
 architecture, 6–7
 routing tables, 379
 traffic engineering, 247–297
 advantages, 253
 assigning traffic to tunnels, 256–257
 configuration, 259–269
 distribution of constraint-based routing information, 254–256
 IS-IS case study, 269–296
 LSP tunnels, 254
 metric manipulation, 252
 need for, 247–249
 rerouting, 257–259
 RSVP, 253–254
 verifying, 265–269
 interworking functions (IWFs), 30
 IntServ, 300–301
 IP precedence, 305–306
 MPLS implementation, 303–305
 RSVP, 301–303
 services, 301
 IP (Internet Protocol)
 addresses
 ATM-based MPLS VPN case study, 229–244
 packet-based MPLS over ATM VPN case study, 200–208
 VPN design and implementation case study, 117
 ATM integration, 6, 36–41
 direct class service implementation, 40
 IGPs, 36–39
 MPLS versus traditional IP over ATM, 39–41
 overlay model versus integrated model, 37–39
 reduced loads, 41
 reliability, 40
 RSVP, 40
 traffic engineering, 41
 VPN manageability, 40
 VPN scalability, 40
 forwarding paradigm, 3
 IGPs (Interior Gateway Protocols), 36–39
 precedence
 IntServ, 305–306
 MPLS E-LSP, 314
 PHB (per-hop behavior), 308
 ip cef command, 103
 ip explicit-path command, 261
 ip ospf cost command, 250
 IP Security. *See* IPSec
 IP+ATM
 networks, 197–198
 switches, 195–197
 IPSec (IP Security), 7
 tunneled VPNs, 84
 IR (intermediate reach) SMF segments, 385
 IS-IS (Intermediate System-to-Intermediate System), 247, 255
 configuration, 262–264
 traffic engineering case study, 269–296
 R1 configuration, 270–271
 R1 policy, 270–271
 ISPs. *See* service providers
 IWFs (interworking functions), 30
 IXC (interexchange carrier), 12

K-L

-
- keywords, global, 163
- LABEL ADVERTISEMENT messages (LDP), 65
 Label Distribution Protocol. *See* LDP
 label edge devices, LSCs as, 228–229
 Label field, 48
 label forwarding algorithm, forwarding plane, 50–51
 label forwarding information base. *See* LFIB
 Label LSPs, 314–315
 Label Switch Controllers. *See* LSCs
 Label Virtual Circuits. *See* LVCs
 label virtual circuits, 188–189
 label-based switching, 4–5, 34–35
 forwarding, 45–46

- Label-Controlled ATM interface. *See* LC-ATM interface
- Label-Switched Path. *See* LSP
- Label-Switched Router. *See* LSR
- Labeled-Switched Path. *See* LSP
- LANE (LAN Emulation), 36
- Layer 2 connection-oriented VPNs, 78–82
 - Cell-based VPNs, 81–82
 - Frame-based, 79–81
 - TDM-based, 79
- Layer 3 connection-oriented VPNs, 82–86
 - GRE Tunneled, 83–84
 - IPSec Tunneled VPNs, 84
 - virtual private dialup, 84–86
- Layer 3 connectionless VPNs, 86
- Layer 3 design, 364–366
 - case studies, 370–378
 - LVC sizing, 366–378
 - destination prefixes, 366–367
 - Edge LSRs, 368–370
 - VC merge, 367–368
- Layer 3 routing, 32–33
 - control component, 32
 - FEC (Forwarding Equivalency Class), 33
 - forwarding component, 32
 - versus MPLS, 34–35
- LC-ATM interface, 180
- LCNs
 - default allocation, 216
 - port group allocations, 247
 - VSI partition LCN allocation, 217
- LDP (Label Distribution Protocol), 65–67, 180
 - classes of messages, 65
 - conservative label retention mode, 66
 - control packet looping, 67
 - downstream-on-demand mode, 66
 - liberal label retention mode, 66
 - loop detection, 70
 - peers, 392
 - sessions, 392
 - unsolicited downstream mode, 66
- leased lines, 12
- LEC (local exchange carrier), 12
- LED (light-emitting diode), 384
- LFIB (label forwarding information base)
 - address prefix, 61–63
 - forwarding plane, 49–50
 - incoming label, 60–63
 - next hop, 60–63
 - outgoing interface, 60–63
 - outgoing label, 61–63
- liberal label retention mode (LDP), 66
- light-emitting diode (LED), 384
- LightStream 1010, 209
- Link State Advertisements (OSPF), 256
- links (backbone link sizing designs)
 - bandwidths, 361–362
 - capacity, 362
 - redundancy, 364
- LMI (Local Management Interface), 20–21
- local exchange carrier. *See* LEC
- Local Management Interface. *See* LMI
- loops
 - control, 68–73
 - detection, 70
 - prevention, 71–73
 - survival, 68–69
 - routing, 67
- Low_EPD_threshold parameter (cnfqbin command), 224
- LSCs (Label Switch Controllers), 190–193
 - configuration, 227–229, 234–237
 - external, 191
 - integrated software, 190
 - internal, 191
 - as label edge devices, 228–229
 - signaling, 192
- LSP (Label-Switched Path), 4, 59–64
 - establishment, 59–64
 - independent control, 59–63
 - ordered control, 64
 - loop detection, 70
 - tunnels, traffic engineering, 254
- LSRs (Label-Switched Router), 4, 53–58, 180–181
 - ATM, 56–58
 - allocation procedure, 58
 - design criteria, 351
 - ordered control method, 57
 - VCI, 58

VPI, 58
 ATM Edge, 181
 ATM LSR, 181
 Edge
 design criteria, 351
 Layer 3 design calculations, 368–370
 multiple ATM, 352–356
 single ATM, 352
 label actions, 53
 packet-based operation, 54–55
 packet-based, 181
 penultimate hop popping, 55–56
 LVCs (Label Virtual Circuits), 56, 188–189
 exhaustion, 380
 Ordinary, 189
 Signaling, 189
 sizing, 366–378
 case studies, 370–378
 destination prefixes, 366–367
 Edge LSRs, 368–370
 VC merge, 367–368

M

make-before-break, 258
 management
 ATM, 29–30
 VPNs, 40
 Management plane (ATM), 23
 match command, 322
 match-all command, 322
 maxpvcbw parameter (cnfrsrc command), 214
 maxpvclcns parameter (cnfrsrc command), 214
 maxvsilcns parameter (cnfrsrc command), 214
 MBGP (Multiprotocol Border Gateway Protocol), 41
 messages, LDP, 65
 metric manipulation versus traffic engineering, 252
 MGX 8220, 354
 Miami
 CE configuration (VPN case study), 134–135
 PE configuration
 ATM-based MPLS VPN case study, 228–229
 packet-based MPLS over ATM VPN case study, 207

VPN case study, 132–134
 Microsoft Point-to-Point Encryption Protocol. *See*
 MPPE
 migration, 343–381
 into ATM networks, 346–350
 MPLS connectionless VPNs, 93
 minvsilcns parameter (cnfrsrc command), 214
 MMF (multimode fiber), 384
 Modular QoS. *See* MQC
 MPLS (Multiprotocol Label Switching)
 benefits, 5–6
 forwarding paradigm, 3
 history, 5
 network topology, 4–5
 versus Layer 3 routing, 34–35
 MPPE (Microsoft Point-to-Point Encryption Protocol), 85–86
 MQC (Modular QoS), 312–313
 commands, 419–421
 configuration verification, 326–327
 Multicast forwarding, 32
 multimode fiber (MMF), 384
 Multiprotocol Border Gateway Protocol. *See* MBGP
 Multiprotocol Label Switching. *See* MPLS
 Multiprotocol Lambda Switching, 389–391
 multiservice access concentrators, 355–356

N

NBAR (Network Based Application Recognition), 313
 neighbor next-hop-self command, 142, 145, 149, 153
 Netflow commands, 422
 Network Based Application Recognition (NBAR), 313
 Network Node Interface. *See* NNI
 network statements, 108, 163
 next hop
 BGP sessions, 165–166
 LFIB, 60–63
 NHRP (Next Hop Resolution Protocol), 39

NNI (Network Node Interface), 24, 26–28
 ATM cells, 24–26
 interdomain, 402
 intradomain, 401–402
 O-UNI with static NNI, 400–401
 node architecture, 46–52
 control plane, 51–52
 forwarding plane, 46–51
 label forwarding algorithm, 50–51
 LFIB, 49–50
 MPLS Label formats, 47–48
 non-TTL, loop survival, 68–69
 nonstate merging LSPs, 71
 NOTIFICATION messages (LDP), 65

O

O-UNI (Optical User Network Interface), 391–392
 with static NNI, 400–401
 OADM (Optical Add Drop Multiplexer), 388
 OIF (Optical Internetworking Forum), 383
 Open Shortest Path First. *See* OSPF
 Optical Add Drop Multiplexer (OADM), 388
 Optical Cross-Connect (OXC), 389
 Optical Internetworking Forum (OIF), 383
 Optical networking, 383–389
 amplifiers, 388
 DWDM (dense wavelength division multiplexing), 384–387
 gateways, 389
 Multiprotocol Lambda Switching. *See*
 Multiprotocol Lambda Switching
 OADM (Optical Add Drop Multiplexer), 388
 OXC (Optical Cross-Connect), 389
 UCP (Unified Control Plane), 392–404
 control architecture, 394–396
 deployment options, 397–404
 management, 394–396
 overlay model, 396–397
 peer model, 397
 wavelength converters, 388
 Optical User Network Interface. *See* O-UNI
 optimized rerouting, traffic engineering, 257
 ordered control LSP establishment, 64
 ordered control method (ATM LSRs), 57
 Ordinary LVCs, 189

OSI Model and ATM, 22
 OSP (Open Shortest Path), unequal-cost load balancing, 249–250
 OSPF (Open Shortest Path First), 247, 255
 configuration for MPLS TE, 264–265
 Link State Advertisements, 256
 PE-to-CE routing, configuration, 110–112
 Traffic-Engineering Network case study, 290–296
 R1 configuration, 290–291
 R3 configuration, 292–293
 R8 configuration, 293–296
 outgoing interface, LFIB, 60–63
 outgoing label, LFIB, 61–63
 overlay model (UCP), 396–397
 oversubscription, CIR port speed, 19
 OXC (Optical Cross-Connect), 389

P

P router configuration, 112–113, 200–201
 P1 router configuration, 118–119
 P2 router configuration, 119–120
 P3 router configuration, 120–121
 packet-based LSR, 54–55, 181
 packet-based VPNs, 97–176, 343
 forwarding, 99–103
 hybrid, 345–346
 MPLS over ATM VPN, 200–208
 PE configuration, 205–209
 PVC configuration, 203
 routers, 98
 routing, 99–103
 trace route enhancements, 170
 verifying operation, 115
 packets, 45–46
 DiffServ domains (DS domain), 313
 Frame Relay switching, 16–21
 label-based switching, 4–5
 prioritization, 321
 tag switching, 5
 TTL trace route enhancements, 170
 partition_id parameter (addshelf command), 225–226
 partitionID parameter (cnfrsrc command), 214

- partitions
- link resources (IP+ATM), 197–198
 - resource, 222
- Payload type (PT) field, 25–26
- PCM (pulse code modulated), 11
- PE routers
- configuration
 - ATM-based MPLS VPNs, 209–229
 - ingress, 321, 327–328
 - packet-based MPLS over ATM VPNs, 182–183, 199–209
 - QoS case study, 329–332
 - VPN case study, 122–137
 - VPN case study deployment, 117
- PE-to-CE routing, configuration, 107–112
- BGP4, 109–110
 - OSPF, 110–112
 - RIPv2, 108–109
 - static, 107–108
- PE-to-PE routing configuration, 106–107
- peak cell rate, ATM QoS, 31
- peer model, UCP, 397
- penultimate hop popping (LSR), 55–56
- PHB (per-hop behavior), 307–309
- AF (assured forwarding), 309
 - class-selector, 308
 - default, 308
 - EF (expedited forwarding), 309
 - enforcement, 311–312
 - AF PHB, 311
 - CBWFQ (Class-Based Weighted Fair Queuing), 311–312
 - default, 308
 - LLQ (Low Latency Queuing), 311
 - scheduling class, 314–315
- Physical layer (ATM), 23
- pipe model (VPN QoS), 316–318
- PNNI (Private Network Node Interface), 255
- Point-to-Point Tunneling Protocol, 85–86
- policy-map command, 324
- pop actions, LSR labels, 53
- PoP design, 352–356
- access concentrators, 354–356
 - multiple ATM Edge LSR, 352–354
 - single ATM Edge LSR, 352
- port group allocations, LCNs, 247
- port speed, Frame Relay, 18
- PPTP (Point-to-Point Tunneling Protocol), 85–86
- prevention loops, 71–73
- Private Network Node Interface (PNNI), 255
- PSTN (Public Switched Telephone Network), 84
- Public Switched Telephone Network (PSTN), 84
- pulse code modulated. *See* PCM
- push actions (LSR labels), 53
- PVCs
- configuration, packet-based MPLS over ATM
 - VPN, 204
 - MPLS Access, 198
 - traditional, 198
-
- ## Q
-
- Qbin_discard_threshold parameter (cnfqbin command), 224
- Qbin_number parameter (cnfqbin command), 224
- QoS (quality of service), 4–5, 299–339
- ATM, 31
 - case study, 329–339
 - attaching service policies to input interfaces, 336–339
 - creating service policies, 332–336
 - creating traffic classes, 329–332
 - DiffServ, 307–312
 - architecture, 310
 - CAR (Committed Access Rate), 311
 - domains (DS domain), 313
 - GTS (Generic Traffic Shaping), 311
 - implementation, 313–315
 - per-hop behavior (PHB), 307–315
 - Traffic Conditioner Block (TCB), 310
 - implementation, 320–321
 - ingress PE router configuration, 321
 - IntServ, 300–301
 - IP precedence, 305–306
 - MPLS implementation, 303–305
 - RSVP, 301–303
 - services, 301
 - MQC (Modular QoS), 312–313
 - packet prioritization, 321
 - VPNs, 316–320
 - configuration, 321–328
 - hose model, 318–320
 - pipe model, 316–318

R

R1

- configuration, OSPF Traffic-Engineering
 - Network case study, 290–291
 - traffic engineering policy, 270–271

R3

- configuration, OSPF Traffic-Engineering
 - Network case study, 292–293
 - traffic engineering policy, 273–274

R8

- configuration, OSPF Traffic-Engineering
 - Network case study, 293–296
 - traffic engineering policy, 276–278
- redistribute bgp metric transparent command, 109
- redistribute command, 108, 112
- redistribute connected subnets command, 142, 145, 149, 153
- redundancy
 - backbone link sizing designs, 362–363
 - HSRP, 168–170
- reference model planes (ATM), 23
- rerouting traffic engineering, 257–259

Resource Manager Essentials, 174

- resource partitioning, cnfrsrc command, 222
- Resource Reservation Protocol. *See* RSVP
- RIPv2 PE-to-CE routing configuration, 108–109
- Route Processor Modules (RPMs), 344
- route reflectors (BGP), 138–141
- route-map command, 108
- route-target command, 106
- router ospf command, 111
- router-based VPN configuration, 103–114

- CE routers, 113–115
- defining VPNs, 105–106

IGP, 104

- interfaces, 104
- P routers, 112–113
- PE-to-CE routing, 107–112
- PE-to-PE routing, 106–107
- required IOS services, 103

routing

- Layer 3, 32–33
 - control component, 32
 - FEC (Forwarding Equivalency Class), 33
 - forwarding component, 32

versus MPLS, 34–35

loops, 67

packet-based VPNs, 99–103

routing and forwarding instances. *See* VRFs

routing tables, 379

RPMs (Route Processor Modules), 344

RSVP (Resource Reservation Protocol), 40

IntServ, 301–303

signaling, 260

traffic engineering, 253–254

S

San Diego

CE configuration, VPN case study, 131–132

PE configuration

ATM-based MPLS VPN case study, 233

packet-based MPLS over ATM VPN case study, 206

VPN case study, 129–131

scalability, 40, 91

screens, dspqbin, 224

Seattle

CE configuration, VPN case study, 128

PE configuration

ATM-based MPLS VPN case study, 232–239

packet-based MPLS over ATM VPN case study, 205–206

VPN case study, 126–128

security

IPSec, 7

MPLS connectionless VPNs, 91

service layer classes, ATM, 31

service policies

attaching to input interfaces, 337–339

configuration, 324–326

creating, QoS case study, 332–336

traffic classes, 336

service providers

MPLS capabilities, 41–42

underutilized bandwidth, 249

VPN case study, 116–118

service-policy command, 326

services, IntServ, 301

SF (Super Frame), 13–15

shared explicit, 258
show ip rsvp host EXEC command, 268
show ip rsvp interface command, 267
show isis mpls traffic-eng adjacency-log EXEC command, 268
show isis mpls traffic-eng advertisements EXEC command, 268
show mpls traffic-eng topology command, 269
show mpls traffic-eng tunnel brief command, 266
show mpls traffic-eng tunnel command, 265
show mpls traffic-eng tunnel summary command, 269
signaling
 ATM, 26–28
 LSCs, 195
 LVCs, 192
 RSVP, 260
single-mode fiber (SMF), 384
slave model, VSI (Virtual Switch Interface), 198
slot.port parameter
 addshelf command, 225
 cnfqbin command, 224
 cnfrsrc command, 213
SMDS (Switched Multimegabit Data Service), 17
SMF (single-mode fiber), 384
SONET (Synchronous Optical Network), 15–16
 DCC channels, 398–400
 hierarchy, 15–16
splicing, traffic engineering, 257
Stack field, 48, 49
stacking, traffic engineering, 257
standards, MPLS connectionless VPNs, 92
state merging LSPs, 71
static PE-to-CE routing, configuration, 107–108
static routes, Internet access over MPLS VPNs, 162–165
 CE1 configuration, 164
 PE1 configuration, 164–165
status polling, LMI, 20–21
Super Frame (SF), 13–15
survival, loop control, 68–69
switch-control VCs, 192–193
Switched Multimegabit Data Service. *See* SMDS
switches
 configuration, ATM-based MPLS VPNs, 210–227
 IP+ATM, 195–197

switching
 cell. *See* cell switching
 circuit, TDM, 11–16
 Frame Relay, 16–21
 ATM-to-Frame Relay interworking, 30
 CIR, 19
 congestion control, 21
 DLCI, 18
 FRAD, 17–18
 frame fields, 19–20
 LMI, 20–21
 port speed, 18
 UNI, 18
 label-based, 4–5, 34–35
 Multiprotocol Lambda Switching, 389–391
 tag, 5, 180
Synchronous Optical Network. *See* SONET

T

Tag Distribution Protocol. *See* TDP
tag switching, 5, 180
tail end destination routers, 254
TCB (Traffic Conditioner Block), 310
TDM (time-division multiplexing), 11–16
 circuit switching, 11–16
 circuits, 11, 12
 DS level
 framing, 13–15
 hierarchy, 12–13
 in-band signaling, 12
 PCM, 11
 SONET hierarchy, 15–16
 VPNs, 79
TDP (Tag Distribution Protocol), 180
time-division multiplexing. *See* TDM
topology (network), 4–5
trace routes, enhancements, 170
traditional PVCs, 198
traffic
 backbone link sizing designs, estimating, 357–360
 classes
 configuration, 322–323
 creating, 329–332

- service policies, 336
- constraints and design, 379
- engineering. *See* traffic engineering
- Traffic Conditioner Block (TCB), 310
- traffic engineering, 5, 41, 247–297
 - advantages, 253
 - assigning traffic to tunnels, 256–257
 - commands, 414–419
 - configuration, 259–269
 - explicit path, 261
 - IS-IS for MPLS TE, 262–264
 - OSPF for MPLS TE, 264–265
 - RSVP signaling and IGP flooding, 260
 - TE tunnel devices, 259
 - tunnels, 260–261
 - tunnels for IGP use, 261–262
 - unequal-cost load balancing, 265
 - distribution of constraint-based routing information, 254–256
 - IS-IS case study, 269–296
 - R1 configuration, 271–273
 - R1 policy, 270–271
 - R2 configuration, 281–283
 - R3 configuration, 274–276
 - R3 policy, 273–274
 - R4 configuration, 283–285
 - R5 configuration, 285–286
 - R6 configuration, 286–288
 - R7 configuration, 288–289
 - R8 configuration, 278–281
 - R8 policy, 276–278
 - LSP tunnels, 254
 - metric manipulation, 252
 - MPLS connectionless VPNs, 92
 - OSPF case study, 290–296
 - R1 configuration, 290–291
 - R3 configuration, 292–293
 - R8 configuration, 293–296
 - rerouting, 257–259
 - optimized, 257
 - splicing, 257
 - stacking, 257
 - RSVP, 253–254
 - trunks, 254
 - unequal-cost load balancing, 249–252
 - EIGRP, 251–252
- OSPF, 249–250
- verifying, 265–269
- trunks
 - backbone link sizing designs, 360–361
 - traffic engineering, 254
 - VPI/VCI space, 196–197
- TTL (time-to-live)
 - field, 48–49
 - loop survival, 68–69
 - trace route enhancements, 170
- tunnels
 - assigning traffic to, 256–257
 - configuring, 260–261
 - configuring devices to support, 259
 - LSP, traffic engineering, 254

U

- UCP (Unified Control Plane), 392–404
 - control architecture, 394–396
 - deployment options, 397–404
 - interdomain NNI, 402
 - intradomain NNI, 401–402
 - O-UNI with static NNI, 400–401
 - phased deployment, 398
 - SONET DCC channels, 398–400
 - management, 394–396
 - overlay model, 396–397
 - peer model, 397
- unequal-cost load balancing
 - configuring MPLS tunnels, 265
 - traffic engineering, 249–252
 - EIGRP, 251–252
 - OSPF, 249–250
- UNI (User-Network Interface), 18, 26–28
- Unicast forwarding, 32
- unidirectional traffic, backbone link sizing designs, 359
- Unified Control Plane. *See* UCP
- unsolicited downstream mode (LDP), 66
- uptrk command, 212
- User plane (ATM), 23
- User-Network Interface. *See* UNI

V

-
- variance n command, 251
 - VCI (virtual channel identifier), 4, 24
 - ATM LSRs, 58
 - values, 25
 - VC merge, 188
 - VCs (virtual circuits), 179
 - label, 188–189
 - merge, 187, 367–368
 - packet-based MPLS over ATM, 182–183
 - switch-control, 192
 - virtual channel identifier. *See* VCI
 - virtual channels (ATM), 28–29
 - virtual circuits. *See* VCs
 - virtual path identifier. *See* VPI
 - virtual paths
 - ATM, 28–29
 - tunnel constraints and design, 380
 - virtual private dialup VPNs, 84–86
 - Virtual Private Networks. *See* VPNs
 - Virtual Switch Interface. *See* VSI
 - virtual trunk parameter (`cnfrsrc` command), 213
 - VoIP (Voice Over IP), 3
 - VPDN (virtual private dialup networks), 84–86
 - VPI (virtual path identifier), 4, 24
 - ATM LSRs, 58
 - values, 25
 - VPI/VCI space, trunks, 196–197
 - VPN Solutions Center. *See* VPNSC
 - VPNs (Virtual Private Networks), 3, 5, 77–94
 - ATM, 179–244, 343–345
 - case study, 229–244
 - cell interleaving, 186–188
 - configuration, 209–229
 - control component, 184–186
 - forwarding component, 183–184
 - IP+ATM, 194–198
 - label virtual circuits, 190–191
 - LSCs, 190–193
 - packet-based, 182–183, 199–209
 - tag switching, 180–181
 - VC Merge, 188
 - carrier-over-carrier, 157–160
 - commands, 413–414
 - compared, 89–93
 - connection-oriented, 78–86
 - Layer 2, 78–82
 - connectionless, 86–89
 - conventional, 86–88
 - Layer 3, 86
 - MPLS, 88–93
 - MPLS packet-based. *See* packet-based VPNs
 - design and implementation case study, 115–138
 - Chicago CE configuration, 124–125
 - Chicago PE configuration, 122–124
 - IP addresses, 117
 - Miami CE configuration, 134–135
 - Miami PE configuration, 132–134
 - P1 router configuration, 118–119
 - P2 router configuration, 119–120
 - PE deployment, 117
 - P3 router configuration, 120–121
 - San Diego CE configuration, 131–132
 - San Diego PE configuration, 129–131
 - Seattle CE configuration, 128
 - Seattle PE configuration, 126–128
 - service provider network, 116–118
 - Washington CE configuration, 138
 - Washington PE configuration, 135–137
 - hybrid, 345–346
 - inter-autonomous system, 141–157
 - BGP confederations, 149–157
 - Inter-Provider VPN, 141–149
 - Internet access over MPLS VPNs, 160–168
 - BGP sessions, 165–168
 - external ISPs, 161–162
 - static default routes, 162–165
 - IPSec, 7
 - management, 40
 - packet-based, 343
 - trace route enhancements, 170
 - verifying operation, 115
 - QoS, 316–320
 - configuration, 321–328
 - hose model, 318–320
 - pipe model, 316–318
 - scalability, 40

VPNSC (VPN Solutions Center), 170–174
 advantages, 172–173
 collections architecture, 171–172
 key functions, 173–174
 supported equipment, 174
VRF (routing and forwarding instances), 99–103
 HSRP support, 168–170
VSI (Virtual Switch Interface), 193–194
 controllers, 197
 partition LCN allocation, 217
 slave model, 193–194
vsiendvpi parameter (cnfrsrc command), 215
vsimaxbw parameter (cnfrsrc command), 215
vsiminbw parameter (cnfrsrc command), 215
vsistartvpi parameter (cnfrsrc command), 215

W-Z

WAN technology, 7
Washington CE configuration, VPN case study, 138
Washington PE configuration
 ATM-based MPLS VPN case study, 234
 packet-based MPLS over ATM VPN case
 study, 208
 VPN case study, 135–137
wavelength converters, Optical networking, 388
Weighted Random Early Detection (WRED), 320
WRED (Weighted Random Early Detection), 320

y/n parameter (cnfqbin command), 224