

Index

10-BASE 2 Ethernet, 21
10-BASE 5 Ethernet, 21
10/100-BASE T Ethernet, 21
100-BASE FX Ethernet, 21
100-BASE T Ethernet, 21
1000-BASE T Ethernet, 21
1000-BASE ZX Ethernet, 21

A

access attacks, mitigating, 191–192
access layer (three-layer hierarchical model), 31
acknowledgment number (TCP), 35
Ad Hoc mode, 175
address learning (switches), 125
administrative distances
 dynamic routers, 205–206
 EIGRP routing source, 206
 OSPF routing source, 206
 RIP routing source, 206
 static routers, 205–206
ANDing, 67
Anomaly Guard and Protector, 194
Application layer
 TCP/IP network model, 46–47
 OSI model, 33–34
APs (access points)
 BSS, 176
 ESS, 176
 rogue APs, 178
ARP (Address Resolution Protocol), 43
ASA (Adaptive Security Appliance), 194
ASIC chips (application-specific integrated circuit), 128

authentication

PPP

CHAP, 143

configuring, 144–145

PAP, 143

WLANs, 178

automatic security configuration, enabling on SDM, 236**Autonomous mode, 175****AUX port (Cisco devices), external connections, 86****availability, 189****B****backing up Cisco IOS Software, image configurations, 110–112****Backoff Algorithm time calculations, Ethernet collisions, 20****BECN (Backward Explicit Congestion Notification), Frame Relay, 148–149****Bellman-Ford algorithm (RIP), 211****binary numbering**

IP addresses

decimal conversions, 54–55

high-order bits, 55

low-order bits, 55

values represented, 54

IP addresses, 54

versus hexadecimal numbering, 56–57

bridges

collision isolation, 124

frames per second, 129

function of, 124

number of ports, 129

source-route translational, 125

source-route, 125

transparent, 125

versus switches, 128–129

bridges, 20**broadcast frames, forwarding, 126****broadcast IDs, subnetting, 67–69****broadcast storms, switch looping problem, 133–134****BSS (Basic Service Set), 176****bus topology, 19****C****CD-ROM**

installing, 320–321

test modes

certification mode, 319

custom mode, 320

study mode, 319

CDP (Cisco Discovery Protocol), remote router management, 115–116**cell-switched WANs, 23****certification mode (CD-ROM), 319****CHAP (Challenge Handshake Authentication Protocol), 143–145****chart (subnetting), creating, 72–74****CIDR (Classless Inter-Domain Routing), 61****CIR (committed information rate), 148****circuit-switched WANs, 22, 140–141****Cisco HDLC (High-level Data-Link Control), 141****Cisco Anomaly Guard, 194****Cisco ASA (Adaptive Security Appliance), 194****Cisco CSA (Cisco Security Agent), 194****Cisco DDoS Guard, 194****Cisco devices**

command line modes

interface configuration, 94

line configuration, 94

privileged exec, 93

router configuration, 94

user exec, 93

command shortcuts, error messages, 94–95
configuration register, 91
context-sensitive help, 95–96
Ethernet ports, duplex settings, 97–97
exam prep questions, 102–105
external connections
 AUX port, 86
 console port, 84–86
 Ethernet port, 86–87
 serial port, 87–88
management IP addresses, setting, 96
memory types, 89
passwords
 logon requirements, 99
 recovery process, 91–93
routers
 information retrieval, 101
 interfaces, enabling, 98
 naming conventions, 108–110
 securing, 98–101
 serial ports, configuring, 97
 SSH access, configuring, 100–101
Setup mode, 91
switches
 hostnames, setting, 96
 securing, 100–98

Cisco IOS Software

backing up, 110–111
images
 backup/restore configuration, 111–112
 transferring to/from servers (TFTP), 110–111
startup process, 89–91

Cisco SDN (Self Defending Network) solutions, 193–195

Cisco SWAN (Structured Wireless-Aware Network), 179

Cisco three-layer hierarchical network model, 30

access layer, 31
benefits, 32
core layer, 31
distribution layer, 31

class A IP addresses, 59

class B IP addresses, 59

class C IP addresses, 59

class D IP addresses, 59

class E IP addresses, 59

classful networks, 63

classless routing protocols, 214

CLI (command line interface), switch configuration, 246–248

collision domains, 20

collisions

Ethernet

Backoff Algorithm time calculations, 20

CSMA/CD (Carrier Sense Multiple Access with Collision Detection), 19–20

domains, 20

effect of, 20

elimination of, 20

Full Duplex connections, 20

isolating on bridges, 124

isolating with switches, 124

jam signals, 20

command line modes, Cisco devices

Interface configuration, 94

Line configuration, 94

privileged exec, 93

Router configuration, 94

user exec, 93

commands

context-sensitive help, 95–96

enable secret, 99

shortcuts, error messages, 94–95

show flash, 101

- show interface, 101
 - show running-config, 101
 - show startup-config, 101
 - show version, 101
 - compression identifiers, router images, 109**
 - confidentiality, 189**
 - configuration register, Cisco devices, 91**
 - configuring**
 - Cisco devices
 - command line modes, access levels, 93
 - command line modes, access levels, 94
 - command shortcuts, 94–95
 - configuration register, 91
 - IOS startup process, 89–91
 - memory locations, 89
 - password recovery process, 91–93
 - Setup mode, 91
 - SSH access, 100–101
 - duplex communication, 132
 - Frame Relay, 151
 - LMI, 152
 - troubleshooting guidelines, 154–155
 - verification of, 154–155
 - PPP, authentication, 144–145
 - RIP, 212–214
 - routers with SDMExpress
 - DHCP Server, 232
 - firewall, 235
 - IP addressing, 230–231
 - NAT, 234
 - user credentials, 230
 - WAN interfaces, 232–234
 - switches with CLI
 - default gateway, configuring, 248
 - management IP, configuring, 247
 - security, 246–247
 - WLANs, 181–182
 - connecting Cisco devices**
 - command line modes, access levels, 93–94
 - command shortcuts, 94–95
 - configuration register, 91
 - IOS startup process, 89–91
 - memory locations, 89
 - password recovery process, 91–93
 - Setup mode, 91
 - connection-oriented communication, 35**
 - connectionless communication, 35**
 - connectivity, testing with SDM, 243**
 - console port**
 - external connections, 84–86
 - local management connections, 85
 - rollover cable pinouts, 85
 - terminal session settings, 86
 - content networks, 24**
 - context-sensitive help, Cisco devices, 95–96**
 - core layer (three-layer hierarchical model), 31**
 - CRC (Cyclic Redundancy Check), Store and Forwarding switching, 130**
 - CSA (Cisco Secure Agent), 194**
 - CSMA/CD (Carrier Sense Multiple Access with Collision Detection), 19–20**
 - custom mode (CD-ROM), 320**
 - cut-through mode switching, 130**
-
- D**
-
- data link layer (OSI model)**
 - flat addressing, 43
 - frame types, 43
 - MAC addresses, 44
 - DDoS attacks, mitigating, 192–193**
 - DDoS Guard, 194**
 - debug ppp authentication command, 146**
 - decapsulation, 46**

- decimal numbering,** conversion from hexadecimal system, 57–58
 converting to binary system, 54–56
- dedicated leased lines, expense of,** 22
- default gateway switch configuration,** 248
- default masks,** 62–63
- default routes** configuring with SDM, 242
 routers
 creating, 203–204
 example of, 204
 uses, 203
- default subnet masks,** 59–60
- destination ports,** 39
- devices, external connections** AUX port, 86
 console port, 84
 console port, 85–86
 Ethernet port, 86–87
 serial port, 87–88
 external connections, 84
- DHCP (Dynamic Host Configuration Protocol),** 34
- DHCP server, configuring with SDM Express,** 232
- distance vector routing protocols** control and prevention of routing loops, 207–210
 maximum hop count, 208
- distribution layer (three-layer hierarchical model),** 31
- DLCI (data-link connection identifier),** 147
- DNS (Domain Name System),** 34
- DSSS (direct sequence spread spectrum),** 173
- Dynamic Key Exchange,** 180
- Dynamic NAT,** 161–162
- dynamic routes** administrative distance, 205–206
 EIGRP, 204, 211
 OSPF, 204
 RIP, 204
-
- ## E
- EIGRP (Enhanced Interior Gateway Routing Protocol),** 204
 administrative distance, 206
 combination of link state and distance vector routing, 211
 routing metrics, 206–207
- enable secret command,** 99
- encapsulation,** 45–46
 Frame Relay, selecting, 152
 HDLC, 140–141
 PPP, 140–141
 authentication, 144–145
 CHAP, 143
 LCP, 142–143
 NCP, 142–143
 PAP, 143
 troubleshooting configuration, 146
 verifying configuration, 146
 Serial Line IP, 140–141
- encryption** enable secret command, 99
 WLANs, 179
- ESS (Enhanced Service Set),** 176
- Ethernet** 10-BASE 2, 124
 10-BASE 5, 124
 bridges
 collision isolation, 124
 function of, 124
 versus switches, 128–129
 cabling
 10-BASE 2, 21
 10-BASE 5, 21

10/100-BASE T, 21
 100-BASE FX, 21
 100-BASE T, 21
 1000-BASE T, 21
 1000-BASE ZX, 21
 collisions, 19–20
 development of, 19
 exam prep questions, 25–28
 IEEE 802.3 specification, 19
 ports
 duplex settings, configuring, 97
 external connections, 86–87
 speed settings, configuring, 97
 straight-through cables, 86–87
 segments, 19
 specifications, 21
 speeds, 20
 switching
 address learning, 125
 collision isolation, 124
 Cut-Through mode, 130
 duplex connection configuration, 132–133
 exam prep questions, answers to, 137–138
 Fragment-Free mode, 131
 frame filters, 127
 frame forwarding, 125–127
 full-duplex connections, 131–132
 function of, 124
 half-duplex connections, 131
 looping problems, 133–134
 STP, 134
 Store and Forward mode, 130
 versus bridges, 128–129

exam, MeasureUp, 320–321

extended NAT entry, 162–164

external connections, Cisco devices

AUX port, 86
 console port, 84–86
 Ethernet port, 86–87
 serial port, 87–88

F

features sets, Cisco routers, 108

FECN (Forward Explicit Congestion Notification), 148–149

FHSS (Frequency Hopping Spread Spectrum), 172

firewalls, configuring with SDM Express, 235

flash memory, Cisco devices, 89

flat addressing, 43

flat topologies, 42

Fragment-Free switching, 131

frame duplication, switch looping problem, 133–134

frame filters, 127

frame forwarding, MAC addresses, 125–127

frames

Frame Relay

configuring, 151–154
 data transmission rates, 148–149
 encapsulation types, selecting, 152
 inverse-arp, 149
 LMI, configuring, 152
 NBMA media, 150
 PVCs
 CIRs, 148
 DLCIs, 147
 LMI, 147–148
 split horizon problem, 150–151
 subinterfaces, configuring, 152
 troubleshooting, 154–155
 verifying configuration, 154–155

frame-relay map command, 152

frames, 43

CRC, 130
 runts, 131

FTP (File Transfer Protocol), 33

full mesh topology, 19

Full-Duplex connections, 131–132

G-H

global addresses (NAT), 157

hackers, 178

half-duplex connections, 131

HDLC (High-Level Data-Link Control), 140–141

headers, TCP/UDP, 40–41

help

- context-sensitive commands, 95–96
- technical support, 322

hexadecimal numbering

- conversion from decimal system, 58
- decimal conversions, 58
- versus binary values, 56–57
- versus decimal values, 56–57

high-order bits, binary numbering system, 55

hold-down timer, 210

hop count, monitoring, 208–209

host devices, 18

host field, IP addresses, 61

hostname, assigning to Cisco devices, 96, 230

hosts

- broadcast frames, forwarding, 126
- IP addresses, 66–67
- multicast frames, forwarding, 127
- subnetting, 66–67, 71
- unicast frames, forwarding, 125

HTTP (HyperText Transfer Protocol), 33

hubs, 125–128

I

IANA (Internet Assigned Numbers Authority), port number ranges, 38–39

ICMP (Internet Connection Management Protocol)

- network layer, 43
- ping command, 116–117
- traceroute command, 116–117

IDS (intrusion detection system), 179

IEEE 802.3 (Ethernet), 19

IEEE 802.11 standard, 23, 171

IEEE 802.11a standard, 172

IEEE 802.11b standard, 173–174

IEEE 802.11i standard, WPA2, 181

IEEE 802.11n standard, 174

images (Cisco IOS)

- backup/restore configurations, 111–112
- transferring to/from servers (TFTP), 110–111

Increment, subnetting

- requirements, determining, 72
- spacing between, 63–65

Infrastructure mode, 175

inside addresses (NAT), 156–157

installing

- CD-ROM, system requirements, 320–321
- WLANs, 181–182

integrity, 189

Interesting octets, 64

interface configuration mode, Cisco devices, 94

interfaces, shutdown states, 98

internal attacks, 178

Internet layer, TCP/IP network model, 46–47

inverse-arp command, 149

IP addressing

- binary numbering, 54–56
- classful networks, 63
- decimal numbering, 58
- default subnet masks, 59–60
- exam prep questions, 75–78, 80–81
- hexadecimal numbering, 56–58
- host fields, 61
- host requirements, determining, 71
- Increment requirements, determining, 72
- network field, 60–61
- non-default subnet masks, 61
- router configuration, 230–231
- subnet fields, 61–62
- subnetting
 - Broadcast IDs, 67–69
 - chart, creating, 72–74
 - class determination, 62–63
 - default mask, 62–63
 - Increment, 63–65
 - logical AND operation, 67
 - number of hosts, 66–67
 - number of hosts, calculating, 66
 - number of subnets, 69–71
 - requirements, determining, 71–72
 - Subnet Zero Rule, 70–71

ip default-network command, 204**IPS (Intrusion Prevention System), 179, 194****IPX (Internetwork Packet Exchange), 43****IS-IS (Intermediate System-Intermediate System), 210****ISM (Industrial, Scientific, Medical) bands, 170****J-K-L****jam signals, 20****LANs**

- collisions, 19
- Ethernet
 - 10-BASE 2, 21
 - 10-BASE 5, 21
 - 10/100-BASE T, 21
 - 100-BASE FX, 21
 - 100-BASE T, 21
 - 1000-BASE T, 21
 - 1000-BASE ZX, 21
 - collisions, 19–20
 - development of, 19
 - IEEE 802.3 specification, 19
 - segments, 19
 - exam prep questions, 25–28

Layer 2. *See* data link layer**Layer 3. *See* network layer****Layer 4. *See* transport layer****Layer 5, 34****Layer 6, 34****Layer 7. *See* application layer****LCP (Link Control Protocol), PPP sub-layer, 142–143****leased lines**

- encapsulation types, 140–141
- expense of, 22

Lightweight mode, 175**line configuration mode, Cisco devices, 94****link state routing protocols, 210****LMI (local management interface), 147–148****load distribution (NAT), 158****logging in to SDM Express, 227–229****logical AND operation, 67**

loops, 133-134

- control and prevention of, 207–210
- hold-down timer, 210
- hop count, maintaining, 208–209
- poison reverse, 209
- route poisoning, 209
- split-horizon rule, 209

low-order bits, binary numbering system, 55**LWAPP (Lightweight Access Point Protocol), 175****M****MAC addresses**

- Data Link layer, 44
- OUI, 44
- switches
 - address learning functions, 125
 - frame filtering functions, 127
 - frame forwarding functions, 125–127
 - table instability, switch looping problem, 133–134

management IP, switch configuration, 247**MANs (metropolitan area networks), 23****mapping TCP/IP model layers to OSI model layers, 47****MARS (Security Monitoring, Analysis, and Response System), 195****maximum hop count, monitoring, 208-209****MeasureUp practice tests, 320-321****memory, 89****mesh topology, 19****metrics, 206-207****metropolitan area networks (MANs), 23****microsegmentation, 132****MIMO (Multiple Input Multiple Output), 174****mitigating security threats, 189**

- access attacks, 191–192
- DDoS attacks, 192–193
- reconnaissance attacks, 190–191

MITM attacks, 191–192**multicast frames, forwarding, 127****multipoint subinterfaces, resolving split horizon problems, 151****N****NAC (Network Access Control), 195****naming routers, 108–110****NAT (Network Address Translation), 155**

- advantages, 158–159
- configuring with SDM Express, 234
- disadvantages, 159
- Dynamic, 161–162
- global addresses, 157
- inside addresses, 156–157
- load distribution, 158
- outside addresses, 156–157
- overlapping address space problem, resolving, 158
- PAT, 162–164
- Static, 159, 161
- translations

- troubleshooting, 164–165

- verifying, 164–165

- typical setup, 156

- Well-Meaning Admin Error problem, resolving, 158

NCP (network control protocol), PPP sublayer, 142–143**network devices, 18****network field, 60-61****Network Interface layer, TCP/IP network model, 46–47****network layer**

- hierarchical organization of, 42

- packets, 42

- path determination, 41

- protocols

- ARP, 43

- ICMP, 43

- IP, 42–43

- IPX, 43

networks

Cisco three-layer hierarchical model, 30
 access layer, 31
 benefits, 32
 core layer, 31
 distribution layer, 31
 content networks, 24
 MANs, 23
 OSI model
 application layer, 33–34
 data link layer, 43–44
 layer sequence, 32–33
 network layer, 41–43
 physical layer, 44–45
 presentation layer, 34
 sending data between hosts, 45–46
 session layer, 34
 transport layer, 35–41
 versus TCP/IP model, 47
 SANs, 24
 TCP/IP model
 application layer, 46–47
 Internet layer, 46–47
 Network Interface layer, 46–47
 transport layer, 46–47
 versus OSI model, 47
 topologies
 bus, 19
 full mesh, 19
 partial mesh, 19
 point-to-point, 18
 ring, 18
 star, 18
no auto-summary command, 213
nonbroadcast multi-access (NBMA) media, 150
non-default subnet masks, 61
NTP (Network Time Protocol), 34
NVRAM (Non-Volatile RAM) memory, 89

0

OFDM (Orthogonal Frequency Division Multiplexing), 172
OSI (Open System Interconnect) model, 32
 application layer, 33–34
 data link layer, 43–44
 exam prep questions, 48–51
 layer sequence, 32–33
 network layer
 ARP, 43
 hierarchical organization of, 42
 ICMP, 43
 IP, 42–43
 IPX, 43
 packets, 42
 path determination, 41
 physical layer, 44–46
 presentation layer, 34
 session layer, 34
 transport layer
 connection-oriented, 35
 connectionless, 35
 port numbers, 38–40
 reliable communication with TCP, 35–37
 TCP, 36–40
 UDP, 40–41
 versus TCP/IP network model, 47
OSPF (Open Shortest Path First), 204
 administrative distance, 206
 routing metrics, 206–207
OUI (Organizationally Unique Identifier), 44
outside addresses (NAT), 156–157
overlapping address space problem, resolving, 158

P

packet-switched WANs, 22–23, 140–141
packets, 42, 202
PAP (Password Authentication Protocol), 143–145
PAR (positive acknowledgment and retransmission), 36
PAT (Port Address Translation), 162–164
partial mesh topology, 19
passwords
 encrypting, 99
 logging into SDM Express, 228–229
 recovery process, 91–93
 requiring for device logon, 99
 router remote access, enabling, 113
path determination, 41
physical layer, 44–46
ping command (ICMP), 116–117
point-to-point subinterfaces, resolving split horizon problems, 151
point-to-point topology, 18
poison reverses (distance vector routing protocol), 209
POP3 (Post Office Protocol 3), 34
port numbers
 transport layer (OSI)
 destination ports, 39
 multiplex connections, 39
 segments, 40
 source ports, 39
 transport layer (OSI), 38–39
port numbers (TCP/UDP), 38–39
PPP (Point-to-Point Protocol), 142
 authentication
 Challenge Handshake Authentication Protocol (CHAP), 143
 configuring, 144–145
 Password Authentication Protocol (PAP), 143
 debug ppp authentication command, 146

encapsulation, 140–142
 show interfaces command, 146
 sublayers
 link control protocol (LCP), 142–143
 network control protocol (NCP), 142–143
 troubleshooting configuration, 146
 verifying configuration, 146
practice exams, 320–321
presentation layer, 34
privileged exec accesss, 93
PVCs (permanent virtual circuits)
 CIRs, 148
 DLCI, 147
 LMI, 147–148

Q-R

RAM, 89
reconnaissance attacks, mitigating, 190–191
reconnecting to router, 237–238, 242
reliable transmission, 35, 41
remote router management
 CDP protocol, 115–116
 ICMP protocol, 116–117
 SSH, 114–115
 telnet protocol, 112–113
restoring Cisco IOS images, 111–112
resuming telnet sessions, 113
ring topology, 18
RIP (Routing Information Protocol), 204
 administrative distances, 206
 Bellman-Ford algorithm, 211
 configuring, 212–214
 no auto-summary command, 213
 routing metrics, 206–207
 troubleshooting, 214–217
 updates, 211
 verifying configuration of, 214–217
 versions, 211–213

rogue APs, 178

rollover cable pinouts, terminal session settings, 85-86

ROM (read-only memory), 89

route poisoning (distance vector routing protocol), 209

router configuration mode, Cisco devices, 94

routers

Cisco devices

 interfaces, enabling, 98

 serial ports, configuring, 97

classless routing protocols, 214

compression identifiers, 109

default routes

 configuring with SDM, 242

 creating, 203–204

 example of, 204

 uses, 203

distance vector protocols

 loops, controlling, 207–210

 maximum hop counter, 208

distance vector protocols, 207

dynamic routes, 204–206

exam prep questions, 118–223

feature sets, 108

information retrieval, 101

interfaces, 98

IOS naming conventions, 108–110

link state protocols, 210

 neighboring connected devices, viewing, 115–116

path determination, 41

remote telnet access, enabling), 113

remote management, 112–117

RIP

 Bellman-Ford algorithm, 211

 configuring, 212–214

 metrics, 206–207

 troubleshooting, 214–217

 updates, 211

verifying configuration of, 214–217

versions, 211

securing, 98–101

SSH access, configuring, 100–101

static routes

 administrative distances, 205–206

 example of, 202–203

 syntax, 202

 uses, 202

telnet sessions, resuming/suspending, 113

runts, 131**S****SANs (storage area networks), 24****SDM (Security Device Manager), 226.**

See also SDM Express

automatic security configuration, 236

connectivity, testing, 243

hostname, configuring, 230

logging in, 227–229

reconnecting after router configuration, 237–238, 242

routers, configuring, 242

 DHCPserver, 232

 firewall, 235

 IP addressing, 230–231

 NAT, 234

 WAN interfaces, 232–234

 user credentials, configuring, 230

SDN (self-defending network) solutions, 193–195**security**

best practices, 195

Cisco SDN solutions, 193–195

goals of, 189

need for, 188

routers, 98, 100–101

switches, 98, 100–101, 246–247

- threats to, mitigating, 189
- access attacks, 191–192
- DDoS attacks, 192–193
- reconnaissance attacks, 190–191
- WLANs, 177–179
 - WEP, 179–180
 - WPA, 181
 - WPA2, 181
- segments, 19–40**
- sequence numbers (TCP), 35**
- serial ports, 87–88, 97**
- session layer, 34**
- Setup mode, Cisco devices, 91**
- shortcuts (MeasureUp practice tests), creating, 321**
- show cdp neighbors command, 115–116**
- show cdp neighbors detail command, 116**
- show cdp neighbors entry command, 116**
- show flash command, 101, 109–110**
- show interface command, 101, 146**
- show ip nat statistics command, 164–165**
- show ip nat translations command, 164–165**
- show running-config command, 101**
- show sessions command (telnet), 113**
- show startup-config command, 101**
- show version command, 101**
- sliding windows (TCP), 37**
- SLIP (Serial Line IP) frame encapsulation, 140–141**
- SMTP (Simple Mail Transfer Protocol), 33**
- SNMP (Simple Network Management Protocol), 34**
- source ports, 39**
- source-route bridges, 125**
- source-route translational bridges, 125**
- split-horizon rule, 150–151, 209**
- SSH access, configuring on Cisco routers, 100–101, 114–115**
- SSID (Service Set Identifier), 176**
- standards, WLANs, 171**
 - IEEE802.11a, 172
 - IEEE802.11b, 173
 - IEEE802.11g, 174
 - IEEE802.11n, 174
- star topology, 18**
- Static NAT, 159–161**
- static routes**
 - administrative distances, 205–206
 - example of, 202–203
 - syntax, 202
- Store and Forward switching, 130**
- STP (Spanning Tree Protocol), 134**
- straight-through cables, Ethernet port connections, 86–87**
- study mode (CD-ROM), 319**
- study resources, 323–325**
- subinterfaces, Frame Relay**
 - configuring, 152
 - resolving split horizon problems, 151
- subnet fields, 61–62**
- subnet masks**
 - default (IP addresses), 59–60
 - non-default (IP addresses), 61
- Subnet Zero Rule, 70–71**
- subnetting**
 - Broadcast IDs, 67–69
 - chart, creating, 72–74
 - default masks, 62–63
 - exam prep questions, 75–81
 - hosts, 66–67
 - Increment, spacing between IP addresses, 63–65
 - IP addresses
 - host requirements, 71
 - Increment requirements, 72
 - subnet requirements, 71–72
 - IP class determination, 62–63
 - logical AND operation, 67
 - requirements, determining, 71–72
 - Subnet Zero Rule, 70–71

suspending telnet sessions

suspending telnet sessions, 113

switches

- address learning, 125
- ASIC chips (Application-Specific Integrated Circuit), 128
- basic operation of, 124
- Cisco device hostnames, setting, 96
- CLI, 246–247
- collision isolation, 124
- Cut-Through mode, 130
- duplex connections, configuring, 132–133
- exam prep questions, 135–138
- Fragment-Free mode, 131
- frame filters, 127
- frame forwarding, 125–127
- frames per second, 129
- Full-Duplex connections, 131–132
- function of, 124
- Half-Duplex connections, 131
- loops, 133–134
- number of ports, 129
- securing, 98–101
- Store and Forward mode, 130
- STP, loop prevention, 134
- versus bridges, 128–129
- versus hubs, 125–128

system requirements, CD-ROM installation, 320

T

TCP (Transmission Control Protocol), 35

- headers, 40
- port numbers, 38–39
- sliding windows, 37
- three-way handshake, 36–37

TCP/IP network model

- application layer, 46–47
- Internet layer, 46–47
- layers, mapping to OSI model layers, 47

Network Interface layer, 46–47

transport layer, 46–47

versus OSI model, 47

technical support, 322

telnet, 34

- passwords, enabling for access, 113
- routers, remote management, 112–113
- sessions, resuming/suspending, 34

terminal sessions, console port settings, 86

test modes (CD-ROM)

- certification mode, 319
- custom mode, 320
- study mode, 319

testing connectivity with SDM, 243

tests (practice), MeasureUp, 320–321

TFTP(Trivial File Transfer Protocol), 34, 110

- application layer (OSI), 34
- IOS images
 - backup/restore configurations, 111–112
 - transferring to/from servers, 110–111
 - troubleshooting tips, 111

Thicknet (10-Base 5 Ethernet), 124

Thinnet (10-Base 2 Ethernet), 124

threats to security, mitigating, 189

- access attacks, 191–192
- DDoS attacks, 192–193
- reconnaissance attack, 190–191
- WLAN security, 177–178

three-layer hierarchical model, 30

- access layer, 31
- benefits, 32
- Core layer, 31
- distribution layer, 31

three-way handshake, 36–37

TKIP (Temporal Key Integrity Protocol), 181

topologies

- bus, 19
- flat, 42
- full mesh, 19
- partial mesh, 19
- point-to-point, 18
- ring, 18
- star, 18

traceroute command, 116–117**translations, NAT, 164–165****transparent bridges, 125****transport layer (OSI) , 35**

- connection-oriented, 35
- connectionless, 35
- port numbers
 - destination ports, 39
 - IANA ranges, 38–39
 - multiplex connections, 39
 - segments, 40
 - source ports, 39
- unreliable communication with UDP, 40–41

reliable communication with TCP, 35–37

TCP

- headers, 40
- port numbers, 38–39
- sliding windows, 37–38
- three-way handshake, 36–37

UDP, 40–41**troubleshooting**

- Frame Relay configuration, 154–155
- PPP configuration, 146, 214–217

twisted-pair cabling, 20

U-V

UDP (User Datagram Protocol) , 35,

- headers, 40–41
- port numbers, 38–39
- transport layer, unreliability of connections, 40–41

unicast frames, forwarding, 125**UNII (Unlicensed National Information Infrastructure) bands, 170****unlicensed radio bands, 170–171****unreliable communication, UDP, 40–41****user credentials, assigning with SDM Express, 230****user exec access, Cisco devices, 93****verifying PPP configuration, 146, 214–217****version 2 command, 213****viruses, 192****VTY lines, 99**

W-X-Y-Z

WANs, 21

- cell-switched, 23
- circuit-switched, 22, 140–141
- dedicated leased line connections, expense of, 22
- encapsulation types
 - HDLC, 140–141
 - PPP, 140–142
 - SLIP, 140–141

exam prep questions, 25–28, 167

Frame Relay

- BECN, 148–149
- configuring, 151–154
- encapsulation types, selecting, 152

FECN, 148–149**inverse-arp, 149****LMI configuration, 152****nonbroadcast multi-access (NBMA) media, 150****PVCs, 147–148****split horizon problem, 150–151****subinterfaces, configuring, 152****troubleshooting configuration, 154–155****verifying configuration, 154–155**

interfaces, configuring with SDM Express, 232–234

leased lines, 22, 140–141

packet-switched, 22–23, 140–141

wireless networks, 23

war driving, 178

Well-Meaning Admin Error problem, resolving (NAT), 158

WEP (Wired Equivalent Privacy), 179–180

Wi-Fi, 171–172

wireless networks, 23

WLANS

APs, 176

configuring, 181–182

IEEE 802.11, 171

IEEE 802.11a, 172

IEEE 802.11b, 173

IEEE 802.11g, 174

IEEE 802.11n, 174

operational modes, 175

security, 177–179

 WEP, 179–180

 WPA, 181

 WPA2, 181

 security methods

 unlicensed radio bands, 170–171

WPA (Wi-Fi Protected Access), 181

WPA2, 181

zero subnets rule, 70–71